

Sika ThermoCoat[®]-1/3 HS White

DECLARATION OF PERFORMANCE

No. 87787219

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	87787219
2	INTENDED USE/S:	EN998-1:2016 General purpose rendering / plastering mortar for external and internal use (GP)
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN998-1:2016
	Notified body/ies:	-

Declaration of Performance

Sika ThermoCoat[®]-1/3 HS White

87787219

2022.07 , Version 2

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1	System 4	EN998-1:2016
Water absorption	W _c 2		
Water vapour permeability	$\mu \leq 20$		
Adhesion	≥ 1.2 MPa - FP:B (Fracture Pattern : Concrete)		
Thermal conductivity	($\lambda_{10,dry}$) 0.49 W/m·K (tab. mean value, P= 50 %)		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Angeliki Zacharopoulou
Function: QEHS Manager
At Athens on 18 July 2022

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 18 July 2022

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sika ThermoCoat® System	ETA 11/0358 acc. to EAD 040083-00-0404	50808934

Declaration of Performance

Sika ThermoCoat®-1/3 HS White
87787219
2017.10 , Revision 1



17

Sika Hellas ABEE, Athens - Greece

DoP No. 87787219

EN998-1:2016

General purpose rendering / plastering mortar for external and internal use, GP

Reaction to fire	Class A1
Water absorption	W_c 2
Water vapour permeability	$\mu \leq 20$
Adhesion	≥ 1.2 MPa - FP:B (Fracture Pattern : Concrete)
Thermal conductivity	$(\lambda_{10,dry})$ 0.49 W/m·K (tab. mean value, P= 50 %)

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika ThermoCoat®-1/3 HS White

87787219

2017.10 , Revision 1



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
Sika ThermoCoat®-1/3 HS White
87787219
2017.10 , Revision 1