
SikaMur[®] Grout+

DECLARATION OF PERFORMANCE

No. 28111117

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	28111117
2	INTENDED USE/S	EN 998-2:2010 Masonry Mortar
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 4
6a	HARMONISED STANDARD:	EN 998-2:2010
	Notified body/ies:	0546

Declaration of Performance

SikaMur[®] Grout+
28111117
2016.11, ver. 2
1026

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Compressive strength	Category M10	System 2+	EN 998-2:2010
Bond strength	0.15 N/mm ² (tab. value)	System 2+	
Chloride content	≤ 0,1% Cl	System 2+	
Water vapour permeability	μ 5/20	System 2+	
Thermal conductivity	0,27 W/mK	System 2+	
Reaction to fire	Euroclass A1	System 4	
Durability (against freeze-thaw):	evaluation based on provisions valid in the intended place of use of the mortar	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 23 April 2020

Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 23 April 2020



.....



.....

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaMur® Grout+
28111117
2016.11, ver. 2
1026



13

Sika Services AG, Zurich, Switzerland

DoP No. 28111117

EN 998-2:2010

Notified Body 0546

Masonry Mortar

Compressive strength	Category M10
Bond strength	0.15 N/mm ² (tab. value)
Chloride content	≤ 0,1% Cl
Water vapour permeability	μ 5/20
Thermal conductivity	0,27 W/mK
Reaction to fire	Euroclass A1
Durability (against freeze-thaw):	evaluation based on provisions valid in the intended place of use of the mortar

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaMur® Grout+
28111117
2016.11, ver. 2
1026



Sika Hellas ABEE
Protomagias 15
14568, Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
SikaMur® Grout+
28111117
2016.11, ver. 2
1026