

## PRODUCT DATA SHEET

# Sarnafast<sup>®</sup> Washer KT

METAL WASHER FOR SPOT FASTENING IN OVERLAPS AND INTERMEDIATE FASTENING  
IN MECHANICALLY FASTENED ROOFING SYSTEMS



## DESCRIPTION

Zinc plated steel washes with diamond-shaped reinforcement and specially stamped barbs for the mechanical fastening of roof waterproofing membranes. Hole diameter 4.9 mm.

## USES

Mechanically fastened roof waterproofing membranes by spot fastening in overlaps and / or intermediate spot fastening in combination with fastener Sarnafast<sup>®</sup> SF-4.8.

Only for fastening roof waterproofing membranes over compressible thermal insulation (not for use on hard substrates).

## CHARACTERISTICS / ADVANTAGES

- Lightweight
- Resistance to common environmental influences
- Easy to use and install with recommended tools
- Recyclable

## APPROVALS / STANDARDS

- Quality Management System EN ISO 9001/14001
- European Technical Approval ETA-08/0262
- Factory Mutual Class No. 4470

## PRODUCT INFORMATION

<b>Packaging</b>	Wire bound, packaging unit 10 stack at 50 pieces each Article No.: 111 098
<b>Appearance / Colour</b>	Surface <u>smooth</u>



<b>Shelf life</b>	Sarnafast® Washer KT does not expire during correct storage.
<b>Storage conditions</b>	Sarnafast® Washer KT shall be stored in dry conditions.
<b>Dimensions</b>	82 × 40 mm, hole diameter 4.9 mm, thickness 1 mm

## TECHNICAL INFORMATION

<b>Corrosion Resistance</b>	15 cycles Kesternich test (concentration SFW 2.0 S in accordance with DIN 50018) according to ETAG 006 - D.3.1.
-----------------------------	---

## SYSTEMS

<b>System Structure</b>	Ancillary product: Sarnafast® Fastener SF-4.8
-------------------------	--

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	-20 °C min. / +60 °C max.
<b>Substrate Temperature</b>	-30 °C min. / +60 °C max.

## APPLICATION INSTRUCTIONS

### APPLICATION

Installation works to be carried out only by experienced Sika trained roofing contractors. Additional measures may be required for installation at below +5 °C ambient temperature in accordance with all relevant local regulations.

### APPLICATION METHOD / TOOLS

Sarnafast® Washer KT must be installed in accordance with the Sika application manual and installation instructions. Sarnafast® Washer KT in combination with Sarnafast® Fastener SF-4.8 is used for the mechanical fastening of roof waterproofing membranes. For more information please refer to the Product Data Sheets for Sarnafast® SF-4.8 (fastening element).

## LIMITATIONS

### Geographical / Climate

The use of Sarnafast® Washer KT is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE  
15 Protomagias Str.  
14568 Kryoneri  
Attica-Greece  
Tel.: +30 210 8160 600  
Fax: +30 210 8160 606  
www.sika.gr | sika@gr.sika.com



SarnafastWasherKT\_en\_GR\_(05-2017)\_1\_1.pdf

Product Data Sheet  
Sarnafast® Washer KT  
May 2017, Version 01.01  
020945051100002001