

Revision Date: 09.03.2025 Date of last issue: 25.04.2023 Version 6.0

Print Date 09.03.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikagard<sup>®</sup>-63 N Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Special system, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person responsible for the SDS	:	EHS@gr.sika.com

#### **1.4 Emergency telephone number**

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>H302 + H332 Harmful if swallowed or if inhaled.</li> <li>H314 Causes severe skin burns and eye damage.</li> <li>H317 May cause an allergic skin reaction.</li> </ul>

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikagard<sup>®</sup>-63 N Part B



Revision Date: 09.03.2025 Date of last issue: 25.04.2023		Vers	sion 6.0	Print Date 09.03.2025
		H412 Harm	ful to aquatic life with long lastin	g effects.
Supplemental Hazard Statements	:	EUH071 (	Corrosive to the respiratory tract	•
Precautionary statements	:	Prevention:		
,			Avoid breathing dust/ fume/ gas/ pours/ spray.	′ mist/ va-
			Avoid release to the environmen	t.
			Wear protective gloves/ protective gloves/ protection.	ve clothing/
		Response:		
		a	53 IF ON SKIN (or hair): Take ately all contaminated clothing. F with water.	
		a	10 IF INHALED: Remove per air and keep comfortable for brea mediately call a POISON CENT	athing. Im-
		P305 + P351 + P3 v t t	38 + P310 IF IN EYES: Rinse with water for several minutes. R act lenses, if present and easy t tinue rinsing. Immediately call a CENTER/ doctor.	e cautiously Remove con- to do. Con-

#### Hazardous components which must be listed on the label:

3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) Adduct IXA-P (epoxy amine adduct, polymer)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

CAS-No.

EC-No.

**SECTION 3: Composition/information on ingredients** 

# Sikagard<sup>®</sup>-63 N Part B

Revision Date: 09.03.2025 Date of last issue: 25.04.2023

3.2 Mixtures

Components Chemical name Version 6.0

Classification

Print Date 09.03.2025

Concentration

(% w/w)

#### Registration number 3-aminomethyl-3,5,5-Acute Tox. 4; H302 >= 25 - < 40 2855-13-2 trimethylcyclohexylamine Skin Corr. 1B; H314 220-666-8 01-2119514687-32-Eye Dam. 1; H318 Skin Sens. 1A; H317 XXXX specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity estimate Acute oral toxicity: 1.030 mg/kg Acute Tox, 4: H302 >= 25 - < 40 m-phenylenebis(methylamine) 1477-55-0 216-032-5 Acute Tox. 4: H332 01-2119480150-50-Skin Corr. 1B: H314 Skin Sens. 1B; H317 XXXX Aquatic Chronic 3; H412 EUH071 Acute toxicity estimate Acute oral toxicity: 930 mg/kg Acute inhalation toxicity (dust/mist): 1,34 mg/l Adduct IXA-P (epoxy amine ad-212580-83-1 Acute Tox. 4; H302 >= 10 - < 20 duct, polymer) Skin Sens. 1; H317 Not Assigned Aquatic Chronic 4; H413



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikagard®-63 N Part B Revision Date: 09.03.2025

Date of last issue: 25.04.2023

Version 6.0

Print Date 09.03.2025

benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 10 - < 20
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 3 - < 5

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

## Sikagard<sup>®</sup>-63 N Part B



Revision Date: 09.03.2025 Date of last issue: 25.04.2023 Version 6.0

Print Date 09.03.2025

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Health injuries may be delayed. corrosive effects sensitising effects
	Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatical	ly.

#### **SECTION 5: Firefighting measures**

5.1	Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2	Special hazards arising from	the	substance or mixture
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.



Revision Date: 09.03.2025 Date of last issue: 25.04.2023	Version 6.0	Print Date 09.03.2025
6.2 Environmental precautions Environmental precautions	: Do not flush into surface water or sanit If the product contaminates rivers and respective authorities.	

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

	Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 (	Conditions for safe storage, in	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.

## Sikagard<sup>®</sup>-63 N Part B

Revision Date: 09.03.2025 Date of last issue: 25.04.2023

Version 6.0

Print Date 09.03.2025

### 7.3 Specific end use(s)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### **Occupational Exposure Limits**

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

### Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.
Environmental exposure contr	ols
General advice :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.





Revision Date: 09.03.2025 Date of last issue: 25.04.2023 Version 6.0

Print Date 09.03.2025

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state Colour Odour	: : :	liquid colourless amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	ca. 10 (20 °C) Concentration: 100 %
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
<b>Solubility(ies)</b> Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,07 hPa
Density	:	ca. 1,1 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

Version 6.0

## Sikagard<sup>®</sup>-63 N Part B

Revision Date: 09.03.2025 Date of last issue: 25.04.2023

Jale of last issue. 25.04.202

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid	:	No data available
	-	

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if swallowed or if inhaled.

#### Components:

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
	LD50 Oral (Rat): 1.030 mg/kg
:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
:	LD50 Dermal (Rabbit): > 2.000 mg/kg
	LD50 (Rabbit): > 2.000 - 5.000 mg/kg





Print Date 09.03.2025

#### Sikagard<sup>®</sup>-63 N Part B Revision Date: 09.03.2025 Version 6.0 Date of last issue: 25.04.2023 m-phenylenebis(methylamine): Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg Acute toxicity estimate: 930 mg/kg Method: Calculation method LC50 (Rat): 1.34 mg/l Acute inhalation toxicity : Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract. Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg benzyl alcohol: Acute toxicity estimate: 1.200 mg/kg Acute oral toxicity : Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008 LD50 Oral (Rat): 1.200 mg/kg 2,4,6-tris(dimethylaminomethyl)phenol: Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised **REGULATION (EC) No 1272/2008** Skin corrosion/irritation Causes severe burns. **Components:** 2,4,6-tris(dimethylaminomethyl)phenol: **Species** Rabbit • Assessment Corrosive Method **OECD** Test Guideline 404 : Assessment : irritating Remarks : Annex VI - Harmonised **REGULATION (EC) No 1272/2008** Serious eye damage/eye irritation Causes serious eye damage.

#### **Components:**

#### 2,4,6-tris(dimethylaminomethyl)phenol:

## Sikagard<sup>®</sup>-63 N Part B

Revision Date: 09.03.2025



Print Date 09.03.2025

-	sion Date: 09.03.2025 of last issue: 25.04.2023		Version 6.0	Print Date 09.03.202		
	Species Assessment	:	Rabbit Causes serious eye damage.			
	Assessment Remarks	:	irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008			
	Respiratory or skin sensitis	sati	on			
	<b>Skin sensitisation</b> May cause an allergic skin reaction.					
	Respiratory sensitisation Not classified based on available information.					
	Germ cell mutagenicity Not classified based on available information.					
	<b>Carcinogenicity</b> Not classified based on available information.					
	<b>Reproductive toxicity</b> Not classified based on available information.					
	<b>STOT - single exposure</b> Corrosive to the respiratory tract.					
	<b>STOT - repeated exposure</b> Not classified based on available information.					
	Aspiration toxicity Not classified based on available information.					
11.2	2 Information on other hazar	ds				
	Endocrine disrupting properties					
	Product: Assessment	:	The substance/mixture does not contain com ered to have endocrine disrupting properties REACH Article 57(f) or Commission Delegate (EU) 2017/2100 or Commission Regulation (F levels of 0.1% or higher.	according to ed regulation		

Version 6.0

## **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

: ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 Toxicity to algae/aquatic Country GR 00000034836

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikagard<sup>®</sup>-63 N Part B



Revision Date: 09.03.2025 Date of last issue: 25.04.2023	Version 6.0	Print Date 09.03.2025
plants	mg/l Exposure time: 72 h	
	NOEC (Desmodesmus subspicatus (green alg Exposure time: 72 h	ae)): 1,5 mg/l
m-phenylenebis(methylamine	):	
Toxicity to fish :	LC50 (Oryzias latipes (Japanese medaka)): > Exposure time: 96 h	10 - 100 mg/l
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 10 - 10 Exposure time: 48 h	0 mg/l
benzyl alcohol:		
Toxicity to fish :	LC50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 mg Exposure time: 48 h	g/l
<b>12.2 Persistence and degradability</b> No data available		
<b>12.3 Bioaccumulative potential</b> No data available		
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB asso	essment	
Product:		
Assessment :	This substance/mixture contains no component to be either persistent, bioaccumulative and to very persistent and very bioaccumulative (vPv) 0.1% or higher	xic (PBT), or
12.6 Endocrine disrupting properti	es	
Product:		
Assessment :	The substance/mixture does not contain comp ered to have endocrine disrupting properties a REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EI levels of 0.1% or higher.	ccording to I regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- :	An environmental hazard cannot be excluded i	in the event of
Country CB 00000024926		10/17

## Sikagard<sup>®</sup>-63 N Part B



Revision Date: 09.03.2025 Date of last issue: 25.04.2023 Version 6.0

Print Date 09.03.2025

mation

unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

13.1 Waste treatment methods		
Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR	:	UN 1760
IMDG	:	UN 1760
ΙΑΤΑ	:	UN 1760
14.2 UN proper shipping name		
ADR	:	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))
IMDG	:	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))
ΙΑΤΑ	:	Corrosive liquid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))

#### 14.3 Transport hazard class(es)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikagard<sup>®</sup>-63 N Part B



Revision Date: 09.03.2025 Version 6.0 Print Date 09.03.2025 Date of last issue: 25.04.2023 Class Subsidiary risks ADR 8 ÷ IMDG ÷ 8 ΙΑΤΑ 2 8 14.4 Packing group ADR Packing group Ш C9 Classification Code ÷ Hazard Identification Number : 80 Labels 8 1 Tunnel restriction code (E) : IMDG Packing group : Labels 8 1 EmS Code : F-A, S-B IATA (Cargo) Packing instruction (cargo 855 : aircraft) Packing instruction (LQ) 1 Y840 Packing group : Ш Labels : Corrosive IATA (Passenger) : 851 Packing instruction (passenger aircraft) Packing instruction (LQ) : Y840 Packing group Ш Labels Corrosive 14.5 Environmental hazards ADR Environmentally hazardous : no IMDG

Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikagard®-63 N Part B



Revision Date: 09.03.2025 Date of last issue: 25.04.2023 Version 6.0

Print Date 09.03.2025

## **SECTION 15: Regulatory information**

5.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors							
REACH Information:	All substances containe - registered by our upst - registered by us, and/ - excluded from the reg - exempted from the reg	trea ⁄or gula	am suppliers, and/or ation, and/or				
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	ingerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3				
REACH - Candidate List of Subs Concern for Authorisation (Articl		:	None of the components are listed (=> 0.1 %).				
REACH - List of substances sub (Annex XIV)	ject to authorisation	:	Not applicable				
Regulation (EU) No 2024/590 or plete the ozone layer	n substances that de-	:	Not applicable				
Regulation (EU) 2019/1021 on p tants (recast)	persistent organic pollu-	:	Not applicable				
Regulation (EU) No 649/2012 of ment and the Council concernin of dangerous chemicals		:	Not applicable				
	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable						
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 14,6% w/w				
	livestock rearing emissi and control)	ion	4 November 2010 on industrial and s (integrated pollution prevention ds (VOC) content: 14,6% w/w				

## Sikagard<sup>®</sup>-63 N Part B

Revision Date: 09.03.2025 Date of last issue: 25.04.2023 Version 6.0

Print Date 09.03.2025

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

Full text of H-Statements

:	Harmful if swallowed.
:	Causes severe skin burns and eye damage.
:	Causes skin irritation.
:	May cause an allergic skin reaction.
:	Causes serious eye damage.
:	Causes serious eye irritation.
:	Harmful if inhaled.
:	Harmful to aquatic life with long lasting effects.
:	May cause long lasting harmful effects to aquatic life.
tions	
:	Acute toxicity
:	Long-term (chronic) aquatic hazard
:	Serious eye damage
:	Eye irritation
:	Skin corrosion
:	Skin irritation
:	Skin sensitisation
:	European Agreement concerning the International Carriage of
	Dangerous Goods by Road
:	Chemical Abstracts Service
:	Derived no-effect level
:	Half maximal effective concentration
:	Globally Harmonized System
:	International Air Transport Association
:	International Maritime Code for Dangerous Goods
:	Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
:	Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
:	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
•	Occupational Exposure Limit
	Persistent, bioaccumulative and toxic
	Predicted no effect concentration
	Regulation (EC) No 1907/2006 of the European Parliament
•	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
	Substances of Very High Concern
:	Very persistent and very bioaccumulative
•	vory poroiotont and vory bioaccumulative
	tions





Revision Date: 09.03.2025 Date of last issue: 25.04.2023

SAFETY DATA SHEET

Version 6.0

**Classification procedure:** 

#### **Further information**

#### Classification of the mixture:

Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN