
Sikasil® WS-605 S

DECLARATION OF PERFORMANCE

No. 65462797

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	65462797
2	INTENDED USE/S	EN 15651-2:2012 Glazing application G CC
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONIZED STANDARD:	EN 15651-2:2012
	Notified body/ies:	1213

Declaration of Performance

Sikasil® WS-605 S

65462797

2017.10 , ver. 1

1024

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	Class E	System 3	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Loss of volume	≤ 10 %	System 3	
Vertical flow resistance	≤ 3 mm	System 3	
Adhesion/cohesion properties after exposure to heat water and artificial light	NF at 100 % elongation	System 3	
Elastic recovery	≥ 60 % at 100 % elongation	System 3	
Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C)	≤ 0,9 MPa at 100 % elongation	System 3	
Tensile properties (i.e. at maintained extension): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C)	NF at 100 % elongation	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Stamatios Kollias
 Function: TMM Sealing & Bonding/Industry
 At Athens on 08 August 2018

Name: Spyros Hatzifotis
 Function: Managing Director
 At Athens on 08 August 2018




End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikasil® WS-605 S
 65462797
 2017.10 , ver. 1
 1024



RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikasil® WS-605 S	EN 15651-1:2012	43385632

Declaration of Performance

Sikasil® WS-605 S
65462797
2017.10 , ver. 1
1024





14

Sika Services AG, Zurich, Switzerland

DoP No. 65462797

EN 15651-2:2012

Notified Body 1213

Glazing application G CC

Reaction to fire	Class E
Water tightness and air tightness	
Loss of volume	$\leq 10 \%$
Vertical flow resistance	$\leq 3 \text{ mm}$
Adhesion/cohesion properties after exposure to heat water and artificial light	NF at 100 % elongation
Elastic recovery	$\geq 60 \%$ at 100 % elongation
Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C)	$\leq 0,9 \text{ MPa}$ at 100 % elongation
Tensile properties (i.e. at maintained extension): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C)	NF at 100 % elongation
Durability	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikasil® WS-605 S
65462797
2017.10, ver. 1
1024

4/5

BUILDING TRUST



Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Athens-Greece
www.sika.gr

Declaration of Performance
Sikasil® WS-605 S
65462797
2017.10 , ver. 1
1024

5/5

BUILDING TRUST

