
SikaCeram[®] StarGrout

DECLARATION OF PERFORMANCE

No. 50124663

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	50124663
2	INTENDED USE/S	EN 12004:2007 + A1:2012 Adhesives for tiles in form of reaction resin adhesives for use in all internal and external tiling. Class R2T
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3 System 4
6a	HARMONISED STANDARD:	EN 12004:2007 + A1:2012
	Notified body/ies:	1599

Declaration of Performance

SikaCeram[®] StarGrout

50124663

2017.04, ver. 1

1171

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonized Technical Specification
Initial shear adhesion strength	≥ 2.0 N/mm ²	EN 12004:2007 + A1:2012
Shear adhesion strength after water immersion	≥ 2.0 N/mm ²	
Shear adhesion strength after thermal shock	≥ 2.0 N/mm ²	
Reaction to fire	Euroclass E	
Dangerous substances	NPD	


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
 Function: TMM Refurbishment
 At Athens on 23 April 2020

Name: Alexandros Melissourgos
 Function: Technical Manager
 At Athens on 23 April 2020



.....



.....

End of information as required by Regulation (EU) No 305/2011





15

Sika Services AG, Zurich, Switzerland

DoP No. 50124663

EN 12004:2007 + A1:2012

Notified Body 1599

Adhesives for tiles in form of reaction resin adhesives for use in all internal and external tiling. Class R2T

Initial shear adhesion strength	$\geq 2.0 \text{ N/mm}^2$
Shear adhesion strength after water immersion	$\geq 2.0 \text{ N/mm}^2$
Shear adhesion strength after thermal shock	$\geq 2.0 \text{ N/mm}^2$
Reaction to fire	Euroclass E

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaCeram® StarGrout

50124663

2017.04, ver. 1

1171

3/4

BUILDING TRUST





Sika Hellas ABEE
Protomagias 15
14568, Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
SikaCeram® StarGrout
50124663
2017.04, ver. 1
1171