

# PRODUCT DATA SHEET

## Sika® Primer-11 W+

UNIVERSAL SUBSTRATE PRIMER FOR TILE ADHESIVES OR LEVELLING COMPOUNDS



### DESCRIPTION

Sika® Primer-11 W+ is a synthetic resin primer applied before using tile adhesives and/or self-levelling compounds on indoor floors or walls to primarily reduce substrate absorbency and improve adhesion.

### USES

- Reduce substrate absorbency
- Improve substrate adhesion
- Protect substrate from moisture entering from tile adhesive or self-levelling compounds

### CHARACTERISTICS / ADVANTAGES

- Ready to use
- Can be diluted with water
- Easy to apply
- High coverage
- Short waiting time
- Indoor use
- Suitable for heated floors (Water and electric systems)
- Very low emissions

### SUSTAINABILITY

VOC emission classification GEV – Emicode EC1<sup>PLUS</sup>

### PRODUCT INFORMATION

<b>Chemical base</b>	Synthetic resin
<b>Packaging</b>	5 kg container
<b>Appearance / Colour</b>	Blue
<b>Shelf life</b>	12 months from date of production
<b>Storage conditions</b>	Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.
<b>Density</b>	1,0 kg/L

### APPLICATION INFORMATION

<b>Substrates</b>	<ul style="list-style-type: none"> <li>▪ Concrete</li> <li>▪ Cement screed</li> <li>▪ Calcium sulfate based screed</li> <li>▪ Gypsum boards</li> <li>▪ Gypsum plaster</li> <li>▪ Wood</li> </ul>
-------------------	--

Mixing Ratio	Substrate	Dilution
	Normal absorbency substrate (cementitious screed, concrete)	1 kg Sika® Primer-11 W+ : 3 L water
	Calcium sulphate substrate (calcium sulfate screed, gypsum plaster)	1 kg Sika® Primer-11 W+ : 1 L water
	Low absorbency substrate (chipboard, wooden substrate)	undiluted
<b>Consumption</b>	40-100 g/m <sup>2</sup> depending on substrate absorbency, application equipment and mixing ratio. These figures are theoretical and do not allow for any additional material due to surface porosity, surface profile, variations in level or wastage etc	
<b>Ambient Air Temperature</b>	+5 °C min. / +30 °C max.	
<b>Substrate Temperature</b>	+5 °C min. / +30 °C max.	
<b>Waiting Time / Overcoating</b>	Before applying tile adhesive or self-levelling compound to Sika® Primer-11 W+ :	
	<b>Substrate</b>	<b>Waiting time</b>
	Cementitious substrate (cementitious screed, concrete)	~ 10 minutes
	Wooden substrate and chipboard	~ 2 hours
	Low absorbent substrate (old water resistant adhesive)	~ 12 hours
	Calcium sulphate substrate (moisture proof)	~ 24 hours

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

Cementitious substrates must be sufficiently cured and dried (2-6 weeks), All substrates must be structurally sound, able to support the weight of the new tiling and provide a stable and securely fixed background. Surfaces shall be clean, dry, free of any loose or friable particles, contaminants such as dust, dirt, oil, wax, polish grease, cement laitance or efflorescence.

Depending on the substrate condition and contaminants to be removed from the surface, use adequate preparation techniques to remove all traces of any materials that could reduce the product's adhesion to the substrate. Smooth surfaces should be roughened lightly to improve adhesion. To confirm adequate surface preparation, primer compatibility and adhesion, carry out a small trial before full application.

### MIXING

Shake or stir Sika® Primer-11 W+ in product container before use.

### APPLICATION

Pour mixed diluted or undiluted primer onto the prepared substrate and apply by brush, roller or squeegee. Ensure a continuous, pore free coat covers the substrate. Avoid excessive primer consumption and the formation of puddles. Remove excess primer before applying tile adhesive or self-levelling compound

### CLEANING OF EQUIPMENT

Removal of fresh remnants from tools and application equipment can be carried out using water immedi-

ately after use. Hardened / cured material can only be mechanically removed.

## IMPORTANT CONSIDERATIONS

- Do not apply on metal, vinyl or ceramic surfaces.
- Do not apply outdoors.
- Do not add anything to the product that is not specified in this Product Data Sheet.
- Do not use for any applications not explicitly described in this Product Data Sheet.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Hellas ABEE

15 Protomagias Str.  
14568 Kryoneri  
Attica-Greece  
Tel.: +30 210 8160 600  
Fax: +30 210 8160 606  
www.sika.gr | sika@gr.sika.com



Product Data Sheet  
Sika® Primer-11 W+  
July 2018, Version 01.01  
020404030010000027

SikaPrimer-11W+-en-GR-(07-2018)-1-1.pdf