

Sika[®] Igoflex[®]-181 GR

DECLARATION OF PERFORMANCE No. 47949424

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	47949424
2	INTENDED USE/S	EN 15814:2011+A2:2014 Polymer modified bituminous thick coatings for waterproofing (W1-CB2-CB2)
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3 System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 15814:2011+A2:2014
	Notified body/ies:	1020

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Watertightness	W1	EN 15814:2011+A2:2014
Reaction to fire	Class E	
Crack bridging ability	CB2	
Resistance to rain	R1	
Water resistance	Passed	
Flexibility at low temperature	Passed	
Dimensional stability at high temperature	Passed	
Reduction of layer thickness when fully dried (durability)	Passed	
Resistance to compression	C2B	
Dangerous Substances	NPD	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Angeliki Zacharopoulou
Function: QEHS Manager
At Athens on 27 October 2021



Name : Stamatis Antonakos
Function: Target Market Manager
Waterproofing/Roofing
At Athens on 27 October 2021



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sika® Igoflex®-181 GR
47949424
2021.10 , Revision 1





21

Sika Hellas ABEE, Athens - Greece

DoP No. 47949424

EN 15814:2011+A2:2014

Notified Body 1020

Polymer modified bituminous thick coatings for waterproofing

Watertightness	W1
Reaction to fire	Class E
Crack bridging ability	CB2
Resistance to rain	R1
Water resistance	Pass
Flexibility at low temperature	Pass
Dimensional stability at high temperature	Pass
Reduction of layer thickness when fully dried (durability)	Pass
Resistance to compression	C2B
Dangerous Substances	NPD

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika® Igoflex®-181 GR
47949424
2021.10 , Revision 1



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance

Sika® Igoflex®-181 GR
47949424
2021.10 , Revision 1