



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-641

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE
15 Protomagias Street
145 68 Kryoneri / Athens
Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person responsible for the SDS : EHS@gr.sika.com

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:



P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine))
Hardener MI (Isophoronedim(morpholinoaldimine))
Isophorondiisocyanate homopolymer
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
Pentamethyl piperidylsebacate
4-morpholinecarbaldehyde
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)
maleic anhydride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenyl tolyl phosphate MCS	Not Assigned 945-730-9 01-2119511174-52-XXXX	Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 10 - < 20
Hardener MTJ (Polyoxypropylene-tri(morpholinoaldimine))	1379822-00-0 700-879-7 01-2120039480-63-XXXX	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 5 - < 10
propylene carbonate	108-32-7 203-572-1 01-2119537232-48-XXXX	Eye Irrit. 2; H319	>= 5 - < 10



Hardener MI (Isophoronedimethyl(morpholinoaldimine)) Contains: 2,2-Dimethyl-3-(4-morpholinyl)propanal <= 7 %	1217271-02-7 700-584-3 01-2119941782-33-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
Isophorondiisocyanate homopolymer Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate <= 0,49 %	53880-05-0 933-047-9 500-125-5 01-2119488734-24-XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 2,5 - < 5
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 2,5
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31-XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	>= 0,25 - < 0,5
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40-XXXX	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 1
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12-XXXX	Skin Sens. 1; H317	< 1



4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	64359-81-5 264-843-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 10	>= 0,1 - < 0,25
salicylic acid	69-72-7 200-712-3 01-2119486984-17-XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	< 1
maleic anhydride	108-31-6 203-571-6 01-2119472428-31-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Inhalation, Respiratory system) EUH071 EUH071 specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	>= 0,001 - < 0,1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.



- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Standard procedure for chemical fires.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
-



Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.



7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	2000/39/EC
		TWA	50 ppm 275 mg/m ³	GR OEL
	Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity of exposure to workers which are absorbed through the skin at the direct contact with these.			
		STEL	100 ppm 550 mg/m ³	GR OEL
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,01 ppm 0,09 mg/m ³	GR OEL
	Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity of exposure to workers which are absorbed through the skin at the direct contact with these.			
		STEL	0,02 ppm 0,18 mg/m ³	GR OEL
maleic anhydride	108-31-6	TWA	0,25 ppm 1 mg/m ³	GR OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.



- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Colour : dark grey
Odour : mild
Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
Boiling point/boiling range : No data available
- Flash point : 150 °C
Method: closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : 0,04 hPa



Relative vapour density	:	No data available
Density	:	ca. 1,427 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 4.000 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

|| Diphenyl tolyl phosphate MCS:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

|| Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

Acute oral toxicity : LD50 Oral (Rat): > 2.001 mg/kg

|| Hardener MI (Isophoronedim(morpholinoaldimine)):

Acute oral toxicity : LD50 Oral (Rat): > 2.001 mg/kg

|| 2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

|| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg
Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

|| Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

|| 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Acute oral toxicity : LD50 Oral (Rat): 1.636 mg/kg
Acute inhalation toxicity : LC50 (Rat): 0,26 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

|| salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg



Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

maleic anhydride:

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Components:

Hardener MI (Isophoronedimethyl(morpholinoaldimine)):

Method : Regulation (EC) No. 440/2008, Annex, B.46
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Hardener MI (Isophoronedimethyl(morpholinoaldimine)):

Method : OECD Test Guideline 405
Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Hardener MI (Isophoronedimethyl(morpholinoaldimine)):

Method : Regulation (EC) No. 440/2008, Annex, B.42 (LLNA)
Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.



Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Components:

|| Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 45,1 mg/l
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 12,5 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1,56 mg/l
Exposure time: 72 h

|| Hardener MI (Isophoronedi(morpholinoaldimine)):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 40,2 mg/l
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 17,1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 89 mg/l
Exposure time: 72 h

|| Pentamethyl piperidylsebacate:

Toxicity to fish : LC50 (Fish): 0,97 mg/l
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

|| 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Toxicity to fish : LC50 (Fish): 0,0027 mg/l
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 10



12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances



SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.



Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)

Volatile organic compounds (VOC) content: 5,27 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 12,28 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

- H226 : Flammable liquid and vapour.
- H302 : Harmful if swallowed.
- H314 : Causes severe skin burns and eye damage.
- H315 : Causes skin irritation.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H330 : Fatal if inhaled.
- H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H361d : Suspected of damaging the unborn child.
- H372 : Causes damage to organs through prolonged or repeated exposure.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.
- H411 : Toxic to aquatic life with long lasting effects.
- H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Aquatic Acute : Short-term (acute) aquatic hazard
- Aquatic Chronic : Long-term (chronic) aquatic hazard
- Eye Dam. : Serious eye damage
- Eye Irrit. : Eye irritation
- Flam. Liq. : Flammable liquids
- Repr. : Reproductive toxicity
- Resp. Sens. : Respiratory sensitisation
- Skin Corr. : Skin corrosion
- Skin Irrit. : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikalastic®-641



Revision Date: 16.02.2021

Version 2.0

Print Date 16.02.2021

Date of last issue: 11.09.2019

Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GR OEL	:	Greece. Exposure limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GR OEL / TWA	:	Long term exposure limit
GR OEL / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

Sikalastic®-641



Revision Date: 16.02.2021
Date of last issue: 11.09.2019

Version 2.0

Print Date 16.02.2021

GR / EN