

---

# Sikasil® Universal

---

## DECLARATION OF PERFORMANCE

### No. 79504437

---

|    |  |   |
|----|--|---|
| 1  | <b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b> | 79504437  |
| 2  | <b>INTENDED USE/S</b>                                  | EN 15651-2:2012<br>Glazing application G CC         |
| 3  | <b>MANUFACTURER:</b>                                   | Sika Services AG<br>Tüffenwies 16-22<br>8064 Zürich |
| 4  | <b>AUTHORISED REPRESENTATIVE:</b>                      |   |
| 5  | <b>SYSTEM/S OF AVCP:</b>                               | System 3  |
| 6a | <b>HARMONIZED STANDARD:</b>                            | EN 15651-2:2012                                     |
|    | Notified body/ies:                                     | 1213  |

#### Declaration of Performance

Sikasil® Universal  
79504437  
2017.10 , ver. 1  
1104

**7 DECLARED PERFORMANCE/S**

| Essential Characteristics  | Performance                  | AVCP     | Harmonized Technical Specification |
|--|------------------------------|----------|------------------------------------|
| Reaction to fire   | Class E                      | System 3 |                                    |
| Release of chemicals dangerous to the environment and health   | NPD                          |          |                                    |
| Water tightness and air tightness  |                              |          |                                    |
| Loss of volume   | ≤ 40 %                       | System 3 |                                    |
| Vertical flow resistance   | ≤ 3 mm                       | System 3 |                                    |
| Adhesion/cohesion properties after exposure to heat water and artificial light   | NF at 60 % elongation        | System 3 |                                    |
| Elastic recovery   | ≥ 60 % at 60 % elongation    | System 3 | EN 15651-2:2012                    |
| Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C)          | ≤ 0,9 MPa at 60 % elongation | System 3 |                                    |
| Tensile properties (i.e. at maintained extension): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C) | NF at 60 % elongation        | System 3 |                                    |
| Durability   | Pass                         | System 3 |                                    |

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Stamatios Kollias  
Function: TMM Sealing & Bonding/Industry  
At Athens on 30 November 2018

Name: Spyros Hatzifotis  
Function: Managing Director  
At Athens on 30 November 2018





End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikasil® Universal  
79504437  
2017.10 , ver. 1  
1104

## RELATED DECLARATION OF PERFORMANCE

| Product Name       | Harmonized technical specification | DoP Number |
|--------------------|------------------------------------|------------|
| Sikasil® Universal | EN 15651-1:2012                    | 14146486   |

|  |                              |
|--|------------------------------|
| <br>14  |                              |
| Sika Services AG, Zurich, Switzerland  |                              |
| DoP No. 79504437   |                              |
| EN 15651-2:2012  |                              |
| Notified Body 1213   |                              |
| Glazing application G CC   |                              |
| Reaction to fire   | Class E                      |
| Water tightness and air tightness  |                              |
| Loss of volume   | ≤ 40 %                       |
| Vertical flow resistance   | ≤ 3 mm                       |
| Adhesion/cohesion properties after exposure to heat water and artificial light   | NF at 60 % elongation        |
| Elastic recovery   | ≥ 60 % at 60 % elongation    |
| Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C)          | ≤ 0,9 MPa at 60 % elongation |
| Tensile properties (i.e. at maintained extension): - for non-structural low modulus sealants used in joints in cold climate areas(-30°C) | NF at 60 % elongation        |
| Durability   | Pass                         |
| <a href="http://dop.sika.com">http://dop.sika.com</a>  |                              |

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### Declaration of Performance

Sikasil® Universal  
79504437  
2017.10 , ver. 1  
1104

---

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---



**Sika Hellas ABEE**  
Protomagias 15  
14568 Kryoneri  
Attica - Greece  
[www.sika.gr](http://www.sika.gr)

### Declaration of Performance

Sikasil® Universal  
79504437  
2017.10 , ver. 1  
1104