

SikaDecor[®]-803 Plus

DECLARATION OF PERFORMANCE

No. 32834282

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	32834282
2	INTENDED USE/S:	EN 998-1:2016 General purpose rendering / plastering mortar
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 998-1:2016
	Notified body/ies:	-

Declaration of Performance

SikaDecor[®]-803 Plus
32834282
2022.07 , Revision 2

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Θλιπτική αντοχή	CS IV	System 4	EN 998-1:2016
Compressive strength	W _c 2	System 4	
Water absorption	μ ≤ 180	System 4	
Water vapour permeability	≥ 2.5 MPa - FP: C (Υπόστρωμα: σκυρόδεμα)	System 4	
Adhesion	(λ10,dry,mat: 1.05 W/m·K (tabulated mean value, P= 50 %)	System 4	
Thermal conductivity	NPD	System 4	
Reaction to fire	NPD	System 4	
Durability	NPD	System 4	
Dangerous substances:	NPD	System 4	

NPD = No performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Aggeliki Zacharopoulou
Function: QEHS Manager
At Athens on 20 July 2022

Name: Kostas Mourikis
Function: TMM Flooring
At Athens on 20 July 2022



.....



.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
SikaDecor®-803 Plus	EN 13813:2002	92159990

Declaration of Performance

SikaDecor®-803 Plus
32834282
2022.07, Revision 2



17

Sika Hellas ABEE, Athens - Greece

DoP No. 32834282

EN 998-1:2016

General purpose rendering / plastering mortar

Compressive strength	CS IV
Water absorption	W_c 2
Water vapour permeability	$\mu \leq 180$
Adhesion	≥ 2.5 MPa - FP: C (Substrate: Concrete)
Thermal conductivity	$(\lambda_{10,dry})$ 1.05 W/m·K (tab. mean value, P= 50 %)

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaDecor®-803 Plus

32834282

2022.07, Revision 2



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
SikaDecor®-803 Plus
32834282
2022.07, Revision 2