
Sika MonoTop[®]-910 S

DECLARATION OF PERFORMANCE

No. 56360253

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	56360253
2	INTENDED USE/S	EN 1504-4:2004 Structural bonding products for bonded mortar or concrete for use in buildings and civil engineering works Principle 4, method 4.4 of EN 1504-9:2008
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-4:2004
	Notified body/ies:	0370

Declaration of Performance

Sika MonoTop[®]-910 S

56360253

2018.03, ver. 1

1053

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Bond/adhesion strength	NPD		EN 1504-4:2004
Shear adhesion	≥ 6 N/mm ²	System 2+	
Workability	≤ 30 min at 23 °C	System 2+	
Shrinkage/expansion	≤ 0.1 %	System 2+	
Modulus of elasticity	≥ 2000 N/mm ²	System 2+	
Coefficient of thermal expansion	≤ 100 × 10 ⁻⁶ per K	System 2+	
Glass transition temperature	≥ 40 °C	System 2+	
Reaction to fire	Class A1/A1 _n	System 3	
Durability	NPD		
Release of dangerous substances	NPD		


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 23 April 2020

Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 23 April 2020



.....



.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sika MonoTop®-910 S	EN 1504-7:2006	82806764

Declaration of Performance

Sika MonoTop®-910 S
56360253
2018.03, ver. 1
1053





13

Sika Services AG, Zurich, Switzerland

DoP No. 56360253

EN 1504-4:2004

Notified Body 0370

Structural bonding products for bonded mortar or concrete for use in buildings and civil engineering works
Principle 4, method 4.4 of EN 1504-9:2008

Shear adhesion	$\geq 6 \text{ N/mm}^2$
Workability	$\leq 30 \text{ min at } 23 \text{ }^\circ\text{C}$
Shrinkage/expansion	$\leq 0.1 \%$
Modulus of elasticity	$\geq 2000 \text{ N/mm}^2$
Coefficient of thermal expansion	$\leq 100 \times 10^{-6} \text{ per K}$
Glass transition temperature	$\geq 40 \text{ }^\circ\text{C}$
Reaction to fire	Class A1/A1 _{fl}

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika MonoTop®-910 S
56360253
2018.03, ver. 1
1053



Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
Sika MonoTop®-910 S
56360253
2018.03, ver. 1
1053