
Sika® Sanisil®

DECLARATION OF PERFORMANCE

No. 82099856

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	82099856
2	INTENDED USE/S	EN 15651-3:2012 For non-structural use in sanitary areas S
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONIZED STANDARD:	EN 15651-3:2012
	Notified body/ies:	1213

Declaration of Performance

Sika® Sanisil®
82099856
2017.10 , ver. 1
1104

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	Class E	System 3	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3	
Loss of volume	≤ 20 %	System 3	
Tensile properties (i.e. elongation)	NF at 60 % elongation	System 3	
Microbiological growth	1	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Stamatios Kollias
Function: TMM Sealing & Bonding/Industry
At Athens on 30 November 2018

Name: Spyros Hatzifotis
Function: Managing Director
At Athens on 30 November 2018



End of information as required by Regulation (EU) No 305/2011


Declaration of Performance

Sika® Sanisil®
82099856
2017.10 , ver. 1
1104



RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sika® Sanisil®	EN 15651-1:2012	26062654

 14	
Sika Services AG, Zurich, Switzerland	
DoP No. 82099856	
EN 15651-3:2012	
Notified Body 1213	
For non-structural use in sanitary areas S	
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation)	NF at 60 % elongation
Microbiological growth	1
Durability	Pass
http://dop.sika.com	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika® Sanisil®
82099856
2017.10 , ver. 1
1104



Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica - Greece
www.sika.grs

Declaration of Performance

Sika® Sanisil®
82099856
2017.10 , ver. 1
1104