

Sika Injection-201 CE

DECLARATION OF PERFORMANCE No. 35859175

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	35859175
2	INTENDED USE/S	EN 1504-5:2004 Construction products: Concrete injection for ductile filling of cracks, voids and interstices (D). Intended use: In buildings and civil engineering works U(D1)W(2)(1/2/3)(9/30)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064, Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-5:2004
	Notified body/ies:	0761

Declaration of Performance

Sika Injection-201 CE
35859175
2016.09 , ver. 2
1063

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Adhesion capacity	approx 0.6 N/mm ²	System 2+	EN 1504-5:2004
Elongation capacity	>10%		
Watertightness	2 x 10 ⁵ Pa		
Glass transition temperature	<-60°C		
Workability: Injectability into dry medium	0.2 mm		
Workability: Injectability into non dry medium	0.2 mm		
Durability	<20%		
Corrosion behaviour	deemed to have no corrosive effect		
Release of dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Stamatis Antonakos
Function: TMM
Waterproofing/Roofing
At Athens on 28/09/2018



Name: Spyros Hatzifotis
Function: Managing Director
At Athens on 28/09/2018



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sika Injection-201 CE
35859175
2016.09 , ver. 2
1063



09

DoP No. 35859175

Sika Services AG, Tüffenwies 16, 8064 Zurich, Switzerland

EN 1504-5:2004

Notified Body 0761

Construction products: Concrete injection for ductile filling of cracks, voids and interstices (D).
Intended use: In buildings and civil engineering works
U(D1)W(2)(1/2/3)(9/30)

Adhesion capacity	approx 0.6 N/mm ²
Elongation capacity	>10%
Watertightness	2 x 10 ⁵ Pa
Glass transition temperature	<-60°C
Workability: Injectability into dry medium	0.2 mm
Workability: Injectability into non dry medium	0.2 mm
Durability	<20%
Corrosion behaviour	deemed to have no corrosive effect

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika Injection-201 CE
35859175
2016.09 , ver. 2
1063

3/4

BUILDING TRUST





Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
Sika Injection-201 CE
35859175
2016.09 , ver. 2
1063