

---

# Sikafloor®-156

---

## DECLARATION OF PERFORMANCE

### No. 33825004

---

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	33825004
2	<b>INTENDED USE/S</b>	EN 13813:2002 Synthetic resin screed for internal uses
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 4 (for internal uses)
6a	<b>HARMONIZED STANDARD:</b>	EN 13813:2002
	Notified body/ies:	0921 1508

#### Declaration of Performance

Sikafloor®-156  
33825004  
2017.10, ver. 3  
1008

<b>7</b>	<b>DECLARED PERFORMANCE/S</b>	Tested systems: primer Sikafloor®-156 underneath Sikafloor®-264		
	<b>Essential Characteristics</b>	<b>Performance</b>	<b>AVCP</b>	<b>Harmonized Technical Specification</b>
	Reaction to fire:	B <sub>fl</sub> <sup>1)</sup>	System 4	EN 13813:2002
	Release of corrosive substances:	SR	System 4	
	Water permeability:	NPD		
	Wear resistance:	≤ AR1 <sup>2)</sup>	System 4	
	Bond strength:	≥ B1,5	System 4	
	Impact resistance:	≥ IR10	System 4	
	Sound insulation:	NPD		
	Sound absorption:	NPD		
	Thermal resistance:	NPD		
	Chemical resistance:	NPD		

1) Tested as a part of a system build-up with Sikafloor®-156, Sikafloor®-220 W and Sikafloor®-262 AS N

2) Min. classification, please refer to the individual test certificate.

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis  
Function: TMM Flooring  
At Athens on 29 June 2019



Name: Alexandros Melissourgos  
Function: Technical Manager  
At Athens on 29 June 2019



.....

End of information as required by Regulation (EU) No 305/2011

**RELATED DECLARATION OF PERFORMANCE**

Product name	Harmonized standard	DoP number
Sikafloor-156	EN 1504-2:2004	60492300

**Declaration of Performance**

Sikafloor®-156  
33825004  
2017.10, ver. 3  
1008





08

Sika Services AG, Zurich, Switzerland

DoP No. 33825004

EN 13813:2002

Notified Body 0921, 1508

Synthetic resin screed for internal uses

Reaction to fire:	B <sub>fl</sub> <sup>1)</sup>
Release of corrosive substances:	SR
Wear resistance:	≤ AR1 <sup>2)</sup>
Bond strength:	≥ B1,5
Impact resistance:	≥ IR10

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sikafloor®-156  
33825004  
2017.10, ver. 3  
1008



**Sika Hellas ABEE**  
15 Protomagias Str.  
14568 Kryoneri  
Athens - Greece  
[www.sika.gr](http://www.sika.gr)

**Declaration of Performance**

Sika floor®-156  
33825004  
2017.10 , ver. 3  
1008