

Sikafloor[®]-156

DECLARATION OF PERFORMANCE

No. 60492300

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	60492300
2	INTENDED USE/S	EN 1504-2:2004 Surface protection products – Coating Ingress protection (1.3) Moisture control (2.2) Physical resistance (5.1) Chemical resistance (6.1) Increasing resistivity (8.2)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ (for uses in buildings and civil engineering works) System 3 (for uses subject to reaction to fire regulations)
6a	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	0921 1508

Declaration of Performance

Sikafloor[®]-156
60492300
2017.10, ver. 3
1008

7

DECLARED PERFORMANCE/STested systems: primer Sikafloor®-156
underneath Sikafloor®-264

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Linear shrinkage:	NPD		EN 1504-2: 2004
Compressive strength:	NPD		
Coefficient of thermal expansion:	NPD		
Abrasion resistance (Taber test) ¹⁾ :	weight loss < 3000 mg	System 2+	
Cross cut:	NPD		
Permeability to CO ₂ :	s _D > 50 m	System 2+	
Water vapor permeability:	Class III	System 2+	
Capillary absorption and permeability to water:	w < 0,1 kg/(m ² x h ^{0,5})	System 2+	
Thermal compatibility:	NPD		
Resistance to thermal shock	NPD		
Chemical resistance:	NPD		
Resistance to severe chemical attack ²⁾ :	Class II	System 2+	
Crack bridging ability:	NPD		
Impact resistance:	Class II	System 2+	
Adhesion strength by pull off test:	≥ 2,0 (1,5) ³⁾ N/mm ² ≥ 1,5 (1,0) ⁴⁾ N/mm ²	System 2+	
Reaction to fire ⁵⁾ :	B _{fl}	System 3	
Skid resistance:	NPD		
Artificial weathering:	NPD		
Antistatic behavior:	NPD		
Adhesion to wet concrete:	NPD		
Dangerous substances:	NPD		

¹⁾ Additionally the requirements according to EN 13813 have to be fulfilled

²⁾ Please refer to the Sikafloor® Chemical Resistance Chart

³⁾ Rigid systems; the value in brackets is the lowest accepted value of any reading.

⁴⁾ Flexible systems; the value in brackets is the lowest accepted value of any reading.

⁵⁾ Tested as a part of a system build-up with Sikafloor®-156, Sikafloor®-220 W and Sikafloor®-262 AS N

Declaration of Performance

Sikafloor®-156
60492300
2017.10, ver. 3
1008

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis
Function: TMM Flooring
At Athens on 29 June 2019



Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 29 June 2019



.....

.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product name	Harmonized standard	DoP number
Sikafloor®-156	EN 13813:2002	33825004

Declaration of Performance

Sikafloor®-156
60492300
2017.10 , ver. 3
1008





08

Sika Services AG, Zurich, Switzerland

DoP No. 60492300

EN 1504-2:2004

Notified Body 0921, 1508

Surface protection products – Coating: Ingress protection (1.3) Moisture control (2.2) Physical resistance (5.1)
Chemical resistance (6.1) Increasing resistivity (8.2)

Abrasion resistance (Tabertest) ¹⁾ :	weight loss < 3000 mg
Permeability to CO ₂ :	s _D > 50 m
Water vapor permeability:	Class III
Capillary absorption and permeability to water:	w < 0,1 kg/(m ² x h _{0,5})
Resistance to severe chemical attack ²⁾ :	Class II
Impact resistance:	Class II
Adhesion strength by pull off test:	≥ 2,0 (1,5) ³⁾ N/mm ² ≥ 1,5 (1,0) ⁴⁾ N/mm ²
Reaction to fire ⁵⁾ :	B _{fl}

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikafloor®-156
60492300
2017.10, ver. 3
1008



Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance

Sikafloor®-156
60492300
2017.10 , ver. 3
1008