

Sika MonoTop®-112 MultiUse Repair

DECLARATION OF PERFORMANCE

No. 69245044

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	69245044		
2	INTENDED USE/S	EN 1504-3:2005 Structural and non-structural repair products for concrete for use in buildings and civil engineering works Principle 3, method 3.1, Principle 4, method 4.4, Principle 7, method 7.1 & 7.2 of EN 1504-9:2008		
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich		
4	AUTHORISED REPRESENTATIVE:			
5	SYSTEM/S OF AVCP:	System 2+		
6a	HARMONISED STANDARD:	EN 1504-3:2005		
-	Notified body/ies:	0546		

Sika MonoTop®-112 MultiUse Repair 69245044 2017.06, ver. 1 1026

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Compression strength	R3 class	System 2+	
Chloride ion content	≤ 0.05 %	System 2+	
Adhesive bond	≥ 1.5 MPa	System 2+	
Carbonation resistance	Passes	System 2+	
Elastic modulus	≥ 15 GPa	System 2+	
Thermal compatibility freeze- thaw	≥ 1.5 MPa	System 2+	EN 1504-3:2005
Capillary absorption	≤ 0.5 kg.m ⁻² .h ^{-0.5}	System 2+	
Skid resistance	NPD		
Coefficient of thermal expansion	NPD		_
Reaction to fire	Class A1	System 3	
Dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos Function: TMM Refurbishment At Athens on 23 April 2020 Name: Alexandros Melissourgos Function: Technical Manager At Athens on 23 April 2020





13

Sika Services AG, Zurich, Switzerland

DoP No. 69245044

EN 1504-3:2005

Notified Body 0546

Structural and non-structural repair products for concrete for use in buildings and civil engineering works Principles 3 (method 3.1), 4 (method 4.4) & 7 (methods 7.1 & 7.2) of EN 1504-9:2008

Compression strength R3 class Chloride ion content ≤ 0.05 % Adhesive bond ≥ 1.5 MPa Carbonation resistance **Passes** ≥ 15 GPa Elastic modulus Thermal compatibility freeze- thaw ≥ 1.5 MPa $\leq 0.5.$ kg.m⁻².h^{-0.5} Capillary absorption

Reaction to fire Class A1

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

Protomagias 15 14568, Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

Sika MonoTop®-112 MultiUse Repair 69245044 2017.06 , ver. 1 1026

