according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex





# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCeram®-260 StarFlex

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage. Specific target organ toxicity - single ex- H335: May cause respiratory irritation.

posure, Category 3, Respiratory system

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

## according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex



Revision Date 14.01.2020 Version 1.0 Print Date 14.01.2020

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

Cement (chromium reduced)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

#### Components

| Chemical name             | CAS-No.             | Classification      | Concentration |
|---------------------------|---------------------|---------------------|---------------|
|                           | EC-No.              |                     | (% w/w)       |
|                           | Registration number |                     |               |
| Cement (chromium reduced) | 65997-15-1          | Skin Irrit. 2; H315 | >= 25 - < 40  |
|                           | 266-043-4           | Eye Dam. 1; H318    |               |
|                           |                     | STOT SE 3; H335     |               |
| calcium diformate         | 544-17-2            | Eye Dam. 1; H318    | >= 1 - < 2,5  |
|                           | 208-863-7           |                     |               |
|                           | 01-2119486476-24-   |                     |               |
|                           | XXXX                |                     |               |

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

Revision Date 14.01.2020

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex



In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

Version 1.0

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Revision Date 14.01.2020

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex



Further information : Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place. No decomposition if stored and applied

as directed.

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex



Revision Date 14.01.2020 Version 1.0 Print Date 14.01.2020

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

# **Environmental exposure controls**

General advice : Try to prevent the material from entering drains or water

courses.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : powder Colour : grey

Odour : characteristic
Odour Threshold : No data available

pH : 11 - 11,5

Melting point/range / Freezing : No data available

point

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex

Revision Date 14.01.2020 Version 1.0 Print Date 14.01.2020

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1,12 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex

Version 1.0



## 10.5 Incompatible materials

Revision Date 14.01.2020

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

### **Acute toxicity**

Not classified based on available information.

### **Components:**

#### calcium diformate:

Acute oral toxicity : LD50 Oral (Rat): 3.050 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.


### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

# SikaCeram®-260 StarFlex



### **SECTION 12: Ecological information**

### 12.1 Toxicity

No data available

Revision Date 14.01.2020

### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 17 01 06\* mixtures of, or separate fractions of concrete,

bricks, tiles and ceramics containing dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

Revision Date 14.01.2020

## according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex

Version 1.0 Print Date 14.01.2020

### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

# 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Cement (chromium reduced) (Number on list 47)

None of the components are listed

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals REACH Information:

: Not applicable

(=> 0.1 %).

Not applicable

Not applicable

Not applicable

: Not applicable

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

Country GR 100000008304

9/11

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex



Revision Date 14.01.2020 Version 1.0 Print Date 14.01.2020

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0,01 %

no VOC duties

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

#### Full text of other abbreviations

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

DNEL : Derived no-effect level EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

according to Regulation (EC) No. 1907/2006

# SikaCeram®-260 StarFlex



Revision Date 14.01.2020 Version 1.0

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
STOT SE 3 H335 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN