

# SikaLatex<sup>®</sup> Emulsion

## DECLARATION OF PERFORMANCE No. 28676645

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:</b>	28676645
2	<b>INTENDED USE/S:</b>	EN934-3:2009+A1:2012 To be used in masonry mortar Air entraining / Plasticizing admixture (Table 2)
3	<b>MANUFACTURER:</b>	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+
6a	<b>HARMONISED STANDARD:</b>	EN934-3:2009+A1:2012
	Notified body/ies:	1128

**7 DECLARED PERFORMANCE/S:**

Essential Characteristics	Performance	Harmonised Technical Specification	
<b>Table 2</b>			
Air content after standard mixing	Total air content $A_1 = (17 \pm 3) \%$ by volume	EN934-3:2009+A1:2012	
Air content after 1h standing	$\geq A_1 - 3 \%$		
Air content after extended mixing	$\leq A_1 + 5 \%$ and $\geq A_1 - 5 \%$		
Reduction in water requirement for standard consistence	$\geq 8 \%$ by mass		
Compressive strength	At 28 days: Test mix $\geq 70 \%$ of control mix		
<b>General Characteristics</b>			
Chloride ion content	Chloride free		
Alkali content	$\leq 3.0 \%$ by mass		
Corrosion behavior	Contains components only from EN934-1:2008, Annex A.1		
Dangerous Substances	NPD*		
*NPD - No performance determined			

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Manolis Mavratzotis  
Function: R&D/QC Manager  
At Athens on 05 October 2016

Name : Spyros Hatzifotis  
Function: General Manager  
At Athens on 05 October 2016

End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

SikaLatex® Emulsion  
28676645  
2016.10 , Revision 1



07

Sika Hellas ABEE, Athens - Greece

28676645

EN934-3:2009+A1:2012

1128

SikaLatex® Emulsion  
To be used in masonry mortar  
Air entraining / Plasticizing admixture  
(Table 2)

For essential characteristics please refer to Declaration of Performance

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

SikaLatex® Emulsion

28676645

2016.10 , Revision 1



**Sika Hellas ABEE**  
15 Protomagias Str.  
GR 145 68 Kryoneri  
Athens - Greece  
[www.sika.gr](http://www.sika.gr)

**Declaration of Performance**  
SikaLatex® Emulsion  
28676645  
2016.10 , Revision 1