according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika ViscoBond® GR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Concrete and mortar admixture

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-H412: Harmful to aquatic life with long lasting ef-

egory 3 fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Date of last issue: 23.04.2020

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

> P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P280

Wear protective gloves/ eye protection/ face

protection.

Disposal:

Prevention:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

triisobutyl phosphate

1,2-benzisothiazol-3(2H)-one (BIT)

2-octyl-2H-isothiazole-3-one (OIT)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components


Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
Alcohols, C9-11-iso-, C10-rich, ethoxylated	Registration number 78330-20-8 Not Assigned	Acute Tox. 4; H302 Eye Dam. 1; H318	>= 1 - < 2,5
triisobutyl phosphate	126-71-6 204-798-3 01-2119957118-32- XXXX	Skin Sens. 1B; H317	< 1

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Version 5.0

Print Date 29.10.2021



according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020



mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9 911-418-6 01-2120764691-48- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0002 - < 0,0015		
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100			
		specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %			
For explanation of abbreviations see section 16.					

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

Immediately flush eye(s) with plenty of water. In case of eye contact

Remove contact lenses.

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Allergic reactions

Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

Risks irritant effects

sensitising effects

May cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

In case of fire, use water/water spray/water jet/carbon diox-Suitable extinguishing media :

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Date of last issue: 23.04.2020

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid Colour : blue

Odour : characteristic

Boiling point/boiling range : No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

pH : ca. 5,5 (20 °C)

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0

Date of last issue: 23.04.2020



Concentration: 100 %

Viscosity

Viscosity, dynamic : < 100 mPa.s (20 °C)

Solubility(ies)

Water solubility : soluble

Vapour pressure : not determined

Density : ca. 1,01 g/cm3 (20 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020

Acute inhalation toxicity : LC50: 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

2-octyl-2H-isothiazole-3-one (OIT):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

triisobutyl phosphate:

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 11 mg/l

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : IC50 (Desmodesmus subspicatus (green algae)): 34,1 mg/l

plants Exposure time: 72 h

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 3 mg/l

aquatic invertebrates Exposure time: 48 h

2-octyl-2H-isothiazole-3-one (OIT):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

12.2 Persistence and degradability

No data available

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0

Date of last issue: 23.04.2020



SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered:

Number on list 3

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

Not applicable

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de: Not applicable

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

Not applicable

: Not applicable

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 0,01% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,14% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard

according to Regulation (EC) No. 1907/2006

Sika ViscoBond® GR

Revision Date: 29.10.2021 Version 5.0 Print Date 29.10.2021

Date of last issue: 23.04.2020

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Eye Irrit. 2 H319 Calculation method
Skin Sens. 1 H317 Calculation method
Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN