according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Date of last issue: 27.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikasil® SG-500 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Catalyst for 2 Comp. sealants/adhesives.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Specific target organ toxicity - single ex-H335: May cause respiratory irritation.

posure, Category 3, Respiratory system

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary statements : Prevention:

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Date of last issue: 27.01.2022

P261 Avoid breathing mist or vapours.
 P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

Hazardous components which must be listed on the label:

tetraethyl silicate N-[3-(triethoxysilyl)propyl]ethylenediamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
tetraethyl silicate	78-10-4	Flam. Liq. 3; H226	>= 20 - < 25
	201-083-8	Acute Tox. 4; H332	
	01-2119496195-28-	Eye Irrit. 2; H319	
	XXXX	STOT SE 3; H335	

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023

Date of last issue: 27.01.2022

Version 5.2

Print Date 23.02.2023

N-[3-5089-72-5 Skin Irrit. 2; H315 >= 10 - < 20 (triethoxysi-225-806-1 Eye Dam. 1; H318 lyl)propyl]ethylenediamine 01-2120767929-30-Skin Sens. 1: H317 Contains: XXXX N,N'-bis[3-(triethoxysilyl)propyl]ethylenediamine >= 15 -<= 20 % diaminoethylaminopropyltetraethoxydisiloxane >= 3 - <= 5 % trimethoxyoctylsilane 3069-40-7 Skin Irrit. 2; H315 >= 5 - < 10 Contains: 221-338-7 methanol <= 0,2 % 01-2119948401-42-XXXX Silicic acid (H4SiO4), tetraethyl Flam. Liq. 3; H226 >= 0,25 - < 0,3 93925-42-9 ester, reaction products with 300-344-4 Acute Tox. 4; H302 bis(acetyloxy)dibutylstannane 01-2119560586-30-Acute Tox. 4; H332 XXXX Eye Dam. 1; H318 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1: H370 STOT RE 1; H372 Aquatic Chronic 3: H412 specific concentration limit Repr. 1B; H360FD >= 0.6 % Muta. 2; H341 >= 2 % STOT SE 1; H370 >= 20 % STOT SE 2; H371 >= 2 % STOT RE 1; H372 >= 20 % STOT RE 2; H373 >= 2 % Acute toxicity estimate Acute oral toxicity: 1.000 mg/kg

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022



SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B



Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
tetraethyl silicate	78-10-4	TWA	5 ppm	2017/164/EU
			44 mg/m3	
	Further information: Indicative			
		TWA	5 ppm	GR OEL
			44 mg/m3	

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Occupational exposure limits of decomposition products


Components	CAS-No.	Value type (Form	Control parame- ters *	Basis *	
ethanol	64-17-5	of exposure) TWA	1.000 ppm 1.900 mg/m3	GR OEL	
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC	
		Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	200 ppm 260 mg/m3	GR OEL	
	Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity of exposure to workers which are absorbed through the skin at t				

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022



^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : solid Appearance : paste

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023 Date of last issue: 27.01.2022

Colour black Odour very faint

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

Flash point Not applicable

Auto-ignition temperature No data available

Decomposition temperature No data available

ca. 8 - 10 pΗ

Concentration: 100 %

Viscosity

Viscosity, dynamic : ca. 250.000 mPa.s (20 °C)

Viscosity, kinematic $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density ca. 1,07 g/cm3 (20 °C)

Relative vapour density No data available

Particle characteristics No data available

9.2 Other information

Flammable solids

Burning rate > 120 s

Method: UN-Test N1

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition : ethanol, methanol

products

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane:

Acute oral toxicity : LD50 Oral (Rat): 1.000 mg/kg

Acute toxicity estimate: 1.000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Date of last issue: 27.01.2022

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

N-[3-(triethoxysilyl)propyl]ethylenediamine:

Toxicity to fish (Chronic tox- : LC50: 597 mg/l icity) : LC50: 597 mg/l Exposure time: 96 h

Species: Danio rerio (zebra fish)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

Country GR 000000223326

Sika®

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

octamethylcyclotetrasiloxane [D4]:

20-year global warming potential: 2,66 100-year global warming potential: 0,739 500-year global warming potential: 0,211

Atmospheric lifetime: 0,027 yr Radiative efficiency: 0,12 Wm2ppb

Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Avoid dispersal of spilled material a

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation (Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Not applicable

: None of the components are listed (=> 0.1 %).

Not applicable

Not applicable

Not applicable

Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0,01% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

Date of last issue: 27.01.2022



SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H341 : Suspected of causing genetic defects.

H360FD : May damage fertility. May damage the unborn child.

H370 : Causes damage to organs.

H372 : Causes damage to organs through prolonged or repeated

exposure if swallowed.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Muta. : Germ cell mutagenicity
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2006/15/EC : Europe. Indicative occupational exposure limit values
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

GR OEL : Greece. Exposure limit values 2006/15/EC / TWA : Limit Value - eight hours 2017/164/EU / TWA : Limit Value - eight hours GR OEL / TWA : Long term exposure limit GR OEL / STEL : Short term exposure limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

according to Regulation (EC) No. 1907/2006

Sikasil® SG-500 Part B

Date of last issue: 27.01.2022

Revision Date: 23.02.2023 Version 5.2 Print Date 23.02.2023

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
Skin Sens. 1 H317 Calculation method
STOT SE 3 H335 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN