Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Aktivator PRO

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 Skin irritation, Category 2 Serious eye damage, Category 1 Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H225: Highly flammable liquid and vapour. H315: Causes skin irritation. H318: Causes serious eye damage. H336: May cause drowsiness or dizziness.		
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.		
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.		

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms Signal word	:	Danger	
Hazard statements	:	H225	Highly flammable liquid and vapour.

Country GR 000000125402

Revision Date: 24.01.2024 Da



Date of last issue: 27.01.2022	V	Print Date 24.01.2	
	H304 H315 H318 H336 H411	May be fatal if swallowed and Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizz Toxic to aquatic life with long l	ziness.
Precautionary statements :	Prevention:		
	P210	Keep away from heat, hot surf open flames and other ignitior smoking.	
	P273	Avoid release to the environm	ent.
	P280	Wear protective gloves/ protection eye protection/ face protection tection.	
	Response:		
	P301 + P310	IF SWALLOWED: Immediately POISON CENTER/ doctor.	y call a
	P305 + P351 +	P338 + P310 IF IN EYES: Rir with water for several minutes tact lenses, if present and eas tinue rinsing. Immediately call CENTER/ doctor.	s. Remove con- sy to do. Con-
	P331	Do NOT induce vomiting.	
	P370 + P378	In case of fire: Use dry sand, or alcohol-resistant foam to extin	
	P391	Collect spillage.	-
= =			

Varcian 5.0

Hazardous components which must be listed on the label:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics bis(trimethoxysilylpropyl)amine

Additional Labelling

EUH208 Contains 3-trimethoxysilylpropane-1-thiol. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 24.01.2024 Date of last issue: 27.01.2022



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Hydrocarbons, C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>=80
isoalkanes, cyclics	927-510-4	Skin Irrit. 2; H315	
Contains:	01-2119475515-33-	STOT SE 3; H336	
cyclohexane >= 2 %	XXXX [corresponding	Asp. Tox. 1; H304	
	group CAS 64742-49-	Aquatic Chronic 2;	
	0]	H411	
bis(trimethoxysilylpropyl)amine	82985-35-1	Eye Dam. 1; H318	>= 3 - < 5
Contains:	280-084-5		
methanol <= 0,3 %	01-2119969956-12-		
	XXXX		
3-trimethoxysilylpropane-1-thiol	4420-74-0	Acute Tox. 4; H302	>= 0,5 - < 1
Contains:	224-588-5	Skin Sens. 1B; H317	
methanol <= 0,99 %	01-2120763539-41-	Aquatic Chronic 2;	
	XXXX	H411	
		Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		1.701 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plent of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika[®] Aktivator PRO



Revision Date: 24.01.2024 Date of last issue: 27.01.2022	Version 5.0	Print Date 24.01
	Keep eye wide open while rinsing.	
If swallowed :	Do not induce vomiting without medical advis Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconso	
4.2 Most important symptoms and e	effects, both acute and delayed	
Symptoms :	Aspiration may cause pulmonary oedema ar Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed information and symptoms.	
Risks :	Risk of serious damage to the lungs (by asp irritant effects May be fatal if swallowed and enters airways Causes skin irritation.	
	Causes skin initiation. Causes serious eye damage. May cause drowsiness or dizziness.	

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Т	reat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.

fighting		fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known

Revision Date: 24.01.2024



Version 5.0

5.3 Advice for firefighters

Date of last issue: 27.01.2022

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
----------------------	---	--

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).
		Do not get in eyes, on skin, or on clothing.
		For personal protection see section 8.
		Smoking, eating and drinking should be prohibited in the application area.
		Take precautionary measures against static discharge.
		Open drum carefully as content may be under pressure.
		Take necessary action to avoid static electricity discharge
		(which might cause ignition of organic vapours).
		Follow standard hygiene measures when handling chemical

Revision Date: 24.01.2024

Sika ®
Print Date 24.01.2024

Date of last issue: 27.01.2022			
		products	
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away fr open flames/ hot surfaces. No smoking. Take measures against electrostatic discharges.	•
Hygiene measures	:	Handle in accordance with good industrial hyg practice. When using do not eat or drink. Whe smoke. Wash hands before breaks and at the	n using do not
7.2 Conditions for safe storage, including any incompatibilities			
Requirements for storage areas and containers	:	Store in cool place. Containers which are oper carefully resealed and kept upright to prevent in accordance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and applied as dire	eted.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Shee use.	t prior to any

Version 5.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
------------	---------	----------------------------------	---------------------------	---------

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)						
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC				
	Further inform	Further information: Indicative, Identifies the possibility of signifi-						
	cant uptake th	nrough the skin	-					
		TWA 200 ppm GR OEL 260 mg/m3						
	chemical factor the likely cont	nation: The notation ors of the table of pa ribution to of these of workers which are with these.	ragraph of 1 articl	e 3, implies the quantity				
		STEL	250 ppm 325 mg/m3	GR OEL				

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Revision Date: 24.01.2024 Date of last issue: 27.01.2022

Version 5.0



Personal protective equipment

	-			
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water			
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.			
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.			
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.			
Respiratory protection	No special measures required.			
Environmental exposure controls				
General advice	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour	:	liquid colourless hydrocarbon-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	> 70 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e Upper explosion limit / Up- per flammability limit		
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Flash point	:	ca4 °C Method: closed cup
Auto-ignition temperature	:	200 °C

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika[®] Aktivator PRO

Print Date 24.01.2024

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0

Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	ca. 2 mPa.s (20 °C)
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	60 hPa
Density	:	ca. 0,7 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid	:	Strong oxidizing agents
--------------------	---	-------------------------

10.6 Hazardous decomposition products

Print Date 24.01.2024

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0

Hazardous decomposition : methanol products

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components: bis(trimethoxysilylpropyl)amine: Acute oral toxicity : LD50 Oral (Rat): 3.780 mg/kg Acute dermal toxicity LD50 Dermal (Rabbit): 11.865 mg/kg : 3-trimethoxysilylpropane-1-thiol: Acute oral toxicity : LD50 Oral (Rat): 1.701 mg/kg Acute toxicity estimate: 1.701 mg/kg Method: Calculation method Acute dermal toxicity LD50 Dermal (Rat): 2.583 mg/kg 1 Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye irritation Causes serious eye damage. Respiratory or skin sensitisation Skin sensitisation Not classified due to lack of data. **Respiratory sensitisation** Not classified due to lack of data. Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0



STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis(trimethoxysilylpropyl)amine:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l Exposure time: 96 h
		NOEC (Oncorhynchus mykiss (rainbow trout)): 100 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h
3-trimethoxysilylpropane-1-t	thic	ol:
Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 12,3 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): 6,7 mg/l Exposure time: 48 h
12.2 Persistence and degradabili	ty	
No data available		
12.3 Bioaccumulative potential		
No data available		
12.4 Mobility in soil		
No data available		

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0



12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

	Product:					
	Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.			
12.7	12.7 Other adverse effects					
	Product:					
	Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.			

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0



SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1866			
IMDG	:	UN 1866			
ΙΑΤΑ	:	UN 1866			
14.2 UN proper shipping name					
ADR	:	RESIN SOLUTION			
IMDG	:	RESIN SOLUTION (n-heptane)			
ΙΑΤΑ	:	Resin solution			

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
ΙΑΤΑ	: 3	

14.4 Packing group

ADR

Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	II F1 33 3 (D/E)
IMDG Packing group Labels EmS Code	:	ll 3 F-E, <u>S-E</u>
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels		353 Y341 II Flammable Liquids

14.5 Environmental hazards

ADR

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0



Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:			gulation, and/or		
REACH - Restrictions on the main the market and use of certain date mixtures and articles (Annex XVI	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3		
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).		
REACH - List of substances subject to authorisation (Annex XIV)			Not applicable		
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer			Not applicable		
Regulation (EU) 2019/1021 on potants (recast)	ersistent organic pollu-	:	Not applicable		
Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals	•	:	Not applicable		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sika[®] Aktivator PRO

Revision Date: 24.01.2024 Date of last issue: 27.01.2022 Version 5.0



jor-accident hazards involving	FLAMMABLE LIQUIDS
E2	ENVIRONMENTAL HAZARDS
34 Volatile organic compounds	 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 95% w/w Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
	Volatile organic compounds (VOC) content: 95% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 H302 H304 H315 H317 H318 H336 H411		Highly flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox. Aquatic Chronic Asp. Tox. Eye Dam. Flam. Liq. Skin Irrit. Skin Sens. STOT SE 2006/15/EC GR OEL 2006/15/EC / TWA GR OEL / TWA GR OEL / STEL ADR		Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. Indicative occupational exposure limit values Greece. Exposure limit values Limit Value - eight hours Long term exposure limit

Revision Date: 24.01.2024 Date of last issue: 27.01.2022



Version 5.0

	Dangerous Goods by Road
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

Further information

Classification of the m	ixture:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN