
Sika AnchorFix[®]- 2+

DECLARATION OF PERFORMANCE

No. 75735322

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	75735322
2	INTENDED USE/S	ETA 14/0346 of 07/10/2016 Bonded injection type anchor for use in cracked and non-cracked concrete
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 1
6b	EUROPEAN ASSESSMENT DOCUMENT:	ETAG 001-Part 1 and Part 5, edition 2013
	European Technical Assessment:	ETA 14/0346 of 07/10/2016
	Technical Assessment Body:	TECHNICKY A ZKUSEBNI USTAV STAVEBNI PRAHA s.p.
	Notified body/ies:	1020

Declaration of Performance

Sika AnchorFix[®]- 2+
75735322
2017.07 , ver. 1
1138

7 DECLARED PERFORMANCE/S

Reaction to fire - Anchorages satisfy requirements for Class A1

Resistance to fire - No performance assessed

Anchorage subject to:

- Static and quasi-static load.
- Seismic performance category C1: threaded rod size M10, M12, M16, M20, M24

Base materials

- Non-cracked concrete.
- Cracked and non-cracked concrete for threaded rod size M10, M12, M16, M20, M24
- Reinforced or unreinforced normal weight concrete of strength class C20/25 at minimum and C50/60 at maximum according EN 206-1:2000-12.

Temperature range:

- -40°C to +80°C (max. short. term temperature +80°C and max. long term temperature +50°C)

Use conditions (Environmental conditions)

- Structures subject to dry internal conditions (zinc coated steel, stainless steel, high corrosion resistance steel).
- Structures subject to external atmospheric exposure including industrial and marine environment, if no particular aggressive conditions exist (stainless steel, high corrosion resistance steel).
- Structures subject to permanently damp internal condition, if no particular aggressive conditions exist (stainless steel, high corrosion resistance steel).
- Structures subject to permanently damp internal condition, with particular aggressive conditions exist (high corrosion resistance steel).

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used).

Use categories: Category 2 – installation in dry or wet concrete or in flooded hole.

Design:

- The anchorages are designed in accordance with the EOTA Technical Report TR 029 "Design of bonded anchors" under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings.
- Anchorages under seismic actions (cracked concrete) have to be designed in accordance with EOTA Technical Report TR 045 "Design of Metal Anchors under Seismic Action".

Installation:

- Dry or wet concrete or flooded hole.
- Hole drilling by rotary drill mode.
- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site.

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07, ver. 1
1138

Table B1: Installation parameters of threaded rod

Size		M8	M10	M12	M16	M20	M24	M27	M30
Nominal drill hole diameter	$\varnothing d_0$ [mm]	10	12	14	18	22	26	30	35
Diameter of cleaning brush	d_b [mm]	14	14	20	20	29	29	40	40
Torque moment	T_{inst} [Nm]	10	20	40	80	150	200	240	275
$h_{ef,min} = 8d$									
Depth of drill hole	h_0 [mm]	64	80	96	128	160	192	216	240
Minimum edge distance	c_{min} [mm]	35	40	50	65	80	96	110	120
Minimum spacing	s_{min} [mm]	35	40	50	65	80	96	110	120
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			
$h_{ef,max} = 20d$									
Depth of drill hole	h_0 [mm]	160	200	240	320	400	480	540	600
Minimum edge distance	c_{min} [mm]	80	100	120	160	200	240	270	300
Minimum spacing	s_{min} [mm]	80	100	120	160	200	240	270	300
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			

Table B2: Installation parameters of rebar

Size		$\varnothing 8$	$\varnothing 10$	$\varnothing 12$	$\varnothing 16$	$\varnothing 20$	$\varnothing 25$	$\varnothing 32$	
Nominal drill hole diameter	$\varnothing d_0$ [mm]	12	14	16	20	25	32	40	
Diameter of cleaning brush	d_b [mm]	14	14	19	22	29	40	42	
$h_{ef,min} = 8d$									
Depth of drill hole	h_0 [mm]	64	80	96	128	160	200	256	
Minimum edge distance	c_{min} [mm]	35	40	50	65	80	100	130	
Minimum spacing	s_{min} [mm]	35	40	50	65	80	100	130	
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			
$h_{ef,max} = 20d$									
Depth of drill hole	h_0 [mm]	160	200	240	320	400	500	640	
Minimum edge distance	c_{min} [mm]	80	100	120	160	200	250	320	
Minimum spacing	s_{min} [mm]	80	100	120	160	200	250	320	
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			

Table B3: Cleaning

All diameters
- 2 x blowing
- 2 x brushing
- 2 x blowing
- 2 x brushing
- 2 x blowing

Table B4: Minimum curing time

Sika AnchorFix® -2 Normal		
Application temperature	Processing time	Load time
+5 to +10°C	10 mins	145 mins
+10 to +15°C	8 mins	85 mins
+15 to +20°C	6 mins	75 mins
+20 to +25°C	5 mins	50 mins
+25 to +30°C	4 mins	40 mins

Processing time refers to the highest temperature in the range.

Load time refers to the lowest temperature in the range.

Declaration of Performance

Sika AnchorFix® - 2+

75735322

2017.07, ver. 1

1138

Cartridge must be conditioned to a minimum +5°C.

Table C1: Design method TR 029

Characteristic values of resistance to tension load of threaded rod

Steel failure – Characteristic resistance										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	NR _{k,s}	[kN]	15	23	34	63	98	141	184	224
Partial safety factor	γ _{MS} ¹⁾	[-]	2							
Steel grade 5.8	NR _{k,s}	[kN]	18	29	42	79	123	177	230	281
Partial safety factor	γ _{MS} ¹⁾	[-]	1,5							
Steel grade 8.8	NR _{k,s}	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	γ _{MS} ¹⁾	[-]	1,5							
Steel grade 10.9	NR _{k,s}	[kN]	37	58	84	157	245	353	459	561
Partial safety factor	γ _{MS} ¹⁾	[-]	1,4							
Stainless steel grade A4-70	NR _{k,s}	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	γ _{MS} ¹⁾	[-]	1,9							
Stainless steel grade A4-80	NR _{k,s}	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	γ _{MS} ¹⁾	[-]	1,6							
Stainless steel grade 1.4529	NR _{k,s}	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	γ _{MS} ¹⁾	[-]	1,5							

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138



Combined pullout and concrete cone failure in non-cracked concrete C20/25										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Characteristic bond resistance in non-cracked concrete										
Dry and wet concrete	τ_{Rk}	[N/mm ²]	11	10	9,5	9	8,5	8	6,5	5,5
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾						2,1 ³⁾	
Flooded hole	τ_{Rk}	[N/mm ²]	9	8	7,5	7	7	6		
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾							
Factor for concrete C50/60	ψ_c	[-]	1							

Combined pullout and concrete cone failure in cracked concrete C20/25								
Size			M10	M12	M16	M20	M24	
Characteristic bond resistance in cracked concrete								
Dry and wet concrete	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾					
Flooded hole	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾					
Factor for cracked concrete	C30/37		1,12					
	C40/50	ψ_c	1,23					
	C50/60		1,30					

Splitting failure											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Edge distance	$c_{cr,sp}$	[mm]	1,5h _{ef}								
Spacing	$s_{cr,sp}$	[mm]	3,0h _{ef}								
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,8								

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C2: Design method TR 029

Characteristic values of resistance to tension load of rebar

Steel failure – Characteristic resistance										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$N_{Rk,s}$	[kN]	28	43	62	111	173	270	442	
Partial safety factor	γ_{Ms} ¹⁾	[-]	1,4							

Combined pullout and concrete cone failure in non-cracked concrete C20/25										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Characteristic bond resistance in non-cracked concrete										
Dry and wet concrete	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5	
Partial safety factor	γ_{Mc} ¹⁾	[-]	1,8 ²⁾							
Flooded hole	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5	
Partial safety factor	γ_{Mc} ¹⁾	[-]	2,1 ³⁾							
Factor for concrete C50/60	ψ_c	[-]	1							

Splitting failure										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Edge distance	$c_{cr,sp}$	[mm]	1,5 h_{ef}							
Spacing	$s_{cr,sp}$	[mm]	3,0 h_{ef}							
Partial safety factor	γ_{Msp} ¹⁾	[-]	1,8							

¹⁾ In absence of national regulations²⁾ The partial safety factor $\gamma_2=1,2$ is included³⁾ The partial safety factor $\gamma_2=1,4$ is included**Declaration of Performance**

Sika AnchorFix®- 2+

75735322

2017.07 , ver. 1

1138

Table C3: Design method TR 029

Characteristic values of resistance to shear load of threaded rod

Steel failure without lever arm											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Steel grade 4.6	$V_{Rk,s}$	[kN]	7	12	17	31	49	71	92	112	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67								
Steel grade 5.8	$V_{Rk,s}$	[kN]	9	15	21	39	61	88	115	140	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25								
Steel grade 8.8	$V_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25								
Steel grade 10.9	$V_{Rk,s}$	[kN]	18	29	42	79	123	177	230	281	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5								
Stainless steel grade A4-70	$V_{Rk,s}$	[kN]	13	20	30	55	86	124	161	196	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56								
Stainless steel grade A4-80	$V_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33								
Stainless steel grade 1.4529	$V_{Rk,s}$	[kN]	13	20	30	55	86	124	161	196	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25								

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Steel failure with lever arm										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	$M^o_{Rk,s}$	[N.m]	15	30	52	133	260	449	666	900
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67							
Steel grade 5.8	$M^o_{Rk,s}$	[N.m]	19	37	66	166	325	561	832	1125
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 8.8	$M^o_{Rk,s}$	[N.m]	30	60	105	266	519	898	1332	1799
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 10.9	$M^o_{Rk,s}$	[N.m]	37	75	131	333	649	1123	1664	2249
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50							
Stainless steel grade A4-70	$M^o_{Rk,s}$	[N.m]	26	52	92	233	454	786	1165	1574
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56							
Stainless steel grade A4-80	$M^o_{Rk,s}$	[N.m]	30	60	105	266	519	898	1332	1799
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33							
Stainless steel grade 1.4529	$M^o_{Rk,s}$	[N.m]	26	52	92	233	454	786	1165	1574
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Concrete pryout failure										
Factor <i>k</i> from TR 029 Design of bonded anchors, Part 5.2.3.3			2							
Partial safety factor	$\gamma_{M_p}^{1)}$	[-]	1,5							

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Concrete edge failure								
Size	M8	M10	M12	M16	M20	M24	M27	M30
See section 5.2.3.4 of Technical Report TR 029 for the Design of Bonded Anchors								
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]		1,5				

¹⁾ In absence of national regulations

Table C4: Design method TR 029

Characteristic values of resistance to shear load of rebar

Steel failure without lever arm								
Size		$\emptyset 8$	$\emptyset 10$	$\emptyset 12$	$\emptyset 16$	$\emptyset 20$	$\emptyset 25$	$\emptyset 32$
Rebar BSt 500 S	$V_{Rk,s}$ [kN]	14	22	31	55	86	135	221
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]		1,5				

Steel failure with lever arm								
Size		$\emptyset 8$	$\emptyset 10$	$\emptyset 12$	$\emptyset 16$	$\emptyset 20$	$\emptyset 25$	$\emptyset 32$
Rebar BSt 500 S	$M_{oRk,s}$ [N.m]	33	65	112	265	518	1013	2122
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]		1,5				
Concrete pryout failure								
Factor <i>k</i> from TR 029		2						
Design of bonded anchors, Part 5.2.3.3		2						
Partial safety factor	$\gamma_{Mp}^{1)}$	[-]		1,5				

Concrete edge failure								
Size		$\emptyset 8$	$\emptyset 10$	$\emptyset 12$	$\emptyset 16$	$\emptyset 20$	$\emptyset 25$	$\emptyset 32$
See section 5.2.3.4 of Technical Report TR 029 for the Design of Bonded Anchors								
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]		1,5				

¹⁾

In absence of national regulations

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C5: Design method CEN/TS 1992-4

Characteristic values of resistance to tension load of threaded rod

Steel failure – Characteristic resistance										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	$N_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	2							
Steel grade 5.8	$N_{Rk,s}$	[kN]	18	29	42	79	123	177	230	281
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Steel grade 8.8	$N_{Rk,s}$	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Steel grade 10.9	$N_{Rk,s}$	[kN]	37	58	84	157	245	353	459	561
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,4							
Stainless steel grade A4-70	$N_{Rk,s}$	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,9							
Stainless steel grade A4-80	$N_{Rk,s}$	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,6							
Stainless steel grade 1.4529	$N_{Rk,s}$	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							

Combined pullout and concrete cone failure in non-cracked concrete C20/25											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Characteristic bond resistance in non-cracked concrete											
Dry and wet concrete	τ_{Rk}	[N/mm ²]	11	10	9,5	9	8,5	8	6,5	5,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾						2,1 ³⁾		
Flooded hole	τ_{Rk}	[N/mm ²]	9	8	7,5	7	7	6			
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾								
Factor for concrete C50/60	ψ_c	[-]	1								
Factor according to CEN/TS 1992-4-5 Section 6.2.2	k_8		10,1								

Combined pullout and concrete cone failure in cracked concrete C20/25										
Size			M10	M12	M16	M20	M24			
Characteristic bond resistance in cracked concrete										
Dry and wet concrete	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5			
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾							
Flooded hole	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5			
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾							
Factor for cracked concrete	C30/37	ψ_c					1,12			
	C40/50						1,23			
	C50/60						1,30			
Factor according to CEN/TS 1992-4-5 Section 6.2.2	k_8		7,2							

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Concrete cone failure									
Size	M8	M10	M12	M16	M20	M24	M27	M30	
Factor according to CEN/TS 1992-4-5 Section 6.2.3	k_{ucr}			10,1					
	k_{cr}			7,2					
Edge distance	$C_{cr,N}$	[mm]	1,5 h_{ef}						
Spacing	$S_{cr,N}$	[mm]	3,0 h_{ef}						
Splitting failure									
Edge distance	$C_{cr,sp}$	[mm]	1,5 h_{ef}						
Spacing	$S_{cr,sp}$	[mm]	3,0 h_{ef}						
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,8						

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Table C6: Design method CEN/TS 1992-4

Characteristic values of resistance to tension load of rebar

Steel failure – Characteristic resistance									
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32
Rebar BSt 500 S	$N_{Rk,s}$	[kN]	28	43	62	111	173	270	442
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,4						

Combined pullout and concrete cone failure in non-cracked concrete C20/25									
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32
Characteristic bond resistance in non-cracked concrete									
Dry and wet concrete	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾						
Flooded hole	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾						
Factor for concrete C50/60	ψ_c	[-]	1						
Factor according to CEN/TS 1992-4-5 Section 6.2.2	k_g		10,1						

Concrete cone failure									
Size	Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32		
Factor according to CEN/TS 1992-4-5 Section 6.2.3	k_{ucr}			10,1					
Edge distance	$C_{cr,N}$	[mm]	1,5 h_{ef}						
Spacing	$S_{cr,N}$	[mm]	3,0 h_{ef}						
Splitting failure									
Edge distance	$C_{cr,sp}$	[mm]	1,5 h_{ef}						
Spacing	$S_{cr,sp}$	[mm]	3,0 h_{ef}						
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,8						

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Declaration of Performance

Sika AnchorFix®- 2+

75735322

2017.07 , ver. 1

1138

Table C7: Design method CEN/TS 1992-4

Characteristic values of resistance to shear load of threaded rod

Steel failure without lever arm										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	$V_{Rk,s}$	[kN]	7	12	17	31	49	71	92	112
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67							
Steel grade 5.8	$V_{Rk,s}$	[kN]	9	15	21	39	61	88	115	140
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 8.8	$V_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 10.9	$V_{Rk,s}$	[kN]	18	29	42	79	123	177	230	281
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Stainless steel grade A4-70	$V_{Rk,s}$	[kN]	13	20	30	55	86	124	161	196
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56							
Stainless steel grade A4-80	$V_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33							
Stainless steel grade 1.4529	$V_{Rk,s}$	[kN]	13	20	30	55	86	124	161	196
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Ductility factor according to CEN/TS 1992-4-5 Section 6.3.2.1	k_2		0,8							

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Steel failure with lever arm											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Steel grade 4.6	M ^o R _{k,s}	[N.m]	15	30	52	133	260	449	666	900	
Partial safety factor	Y _M s	[-]	1,67								
Steel grade 5.8	M ^o R _{k,s}	[N.m]	19	37	66	166	325	561	832	1125	
Partial safety factor	Y _M s	[-]	1,25								
Steel grade 8.8	M ^o R _{k,s}	[N.m]	30	60	105	266	519	898	1332	1799	
Partial safety factor	Y _M s	[-]	1,25								
Steel grade 10.9	M ^o R _{k,s}	[N.m]	37	75	131	333	649	1123	1664	2249	
Partial safety factor	Y _M s	[-]	1,50								
Stainless steel grade A4-70	M ^o R _{k,s}	[N.m]	26	52	92	233	454	786	1165	1574	
Partial safety factor	Y _M s	[-]	1,56								
Stainless steel grade A4-80	M ^o R _{k,s}	[N.m]	30	60	105	266	519	898	1332	1799	
Partial safety factor	Y _M s	[-]	1,33								
Stainless steel grade 1.4529	M ^o	[N.m]	26	52	92	233	454	786	1165	1574	
Partial safety factor	Y _M s	[-]	1,25								
Concrete pryout failure											
Factor according to CEN/TS 1992-4-5 Section 6.3.3		k ₃	2,0								
Partial safety factor	Y _M	[-]	1,5								

Concrete edge failure									
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32
See section 6.3.4 of CEN/TS 1992-4-5									
Effective length of anchor	l _f	[mm]	l _f = min(h _{ef} ; 8 d _{nom})						
Outside diameter of anchor	d _{nom}	[mm]	8	10	12	16	20	24	30
Partial safety factor	Y _{Mc} ¹⁾	[-]	1,5						

¹⁾ In absence of national regulations

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C8: Design method CEN/TS 1992-4
Characteristic values of resistance to shear load of rebar

Steel failure without lever arm										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	VR _{k,s}	[kN]	14	22	31	55	86	135	221	
Partial safety factor	γ _{Ms} ¹⁾	[-]	1,5							
Ductility factor according to CEN/TS 1992-4-5 Section 6.3.2.1	k ₂		0,8							

Steel failure with lever arm										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	M ^o R _{k,s}	[N.m]	33	65	112	265	518	1013	2122	
Partial safety factor	γ _{Ms} ¹⁾	[-]	1,5							
Concrete pryout failure										
Factor according to CEN/TS 1992-4-5 Section 6.3.3	k ₃		2,0							
Partial safety factor	γ _{Mp} ¹⁾	[-]	1,5							

Concrete edge failure										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
See section 6.3.4 of CEN/TS 1992-4-5										
Effective length of anchor	l _f	[mm]	l _f = min(h _{ef} ; 8 d _{nom})							
Outside diameter of anchor	d _{nom}	[mm]	8	10	12	16	20	24	30	
Partial safety factor	γ _{Mc} ¹⁾	[-]	1,5							

¹⁾ In absence of national regulations

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C9: Displacement of threaded rod under tension and shear load

Anchor size			M8	M10	M12	M16	M20	M24	M27	M30
Non-cracked concrete										
Tension load	F	[kN]	6,3	7,9	11,9	15,9	23,8	29,8	37,7	45,6
Displacement	δ_{N0}	[mm]	0,3	0,3	0,3	0,3	0,4	0,5	0,5	0,5
		$\delta_{N\infty}$	[mm]	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Shear load	F	[kN]	3,1	5,0	7,2	13,5	21,0	30,3	39,4	48,0
Displacement	δ_{V0}	[mm]	1,5	1,5	1,5	1,5	2,0	2,5	2,5	2,5
		$\delta_{V\infty}$	[mm]	2,3	2,3	2,3	2,3	3,0	3,8	3,8
Cracked concrete										
Tension load	F	[kN]		5,1	7,4	13,1	20,5	24,6		
Displacement	δ_{N0}	[mm]		0,4	0,7	0,7	0,7	0,6		

Table C10: Displacement of rebar under tension and shear load

Rebar size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32
Non-cracked concrete									
Tension load	F	[kN]	7,9	9,9	13,9	23,8	29,8	55,6	55,6
Displacement	δ_{N0}	[mm]	0,3	0,3	0,3	0,4	0,4	0,5	0,5
		$\delta_{N\infty}$	[mm]	0,5	0,5	0,5	0,5	0,5	0,5
Shear load	F	[kN]	5,9	9,3	13,3	23,7	37,0	57,9	94,8
Displacement	δ_{V0}	[mm]	0,3	0,4	0,4	0,4	0,4	0,5	0,9
		$\delta_{V\infty}$	[mm]	0,5	0,6	0,6	0,6	0,6	0,8

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C11: Characteristic values of resistance under seismic action category C1 for threaded rods

Size			M10	M12	M16	M20	M24
Tension load							
Steel failure							
Characteristic resistance grade 4.6	$N_{Rk,s,seis}$	[kN]	23	34	63	98	141
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	2,00				
Characteristic resistance grade 5.8	$N_{Rk,s,seis}$	[kN]	29	42	79	123	177
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50				
Characteristic resistance grade 8.8	$N_{Rk,s,seis}$	[kN]	46	67	126	196	282
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50				
Characteristic resistance grade 10.9	$N_{Rk,s,seis}$	[kN]	58	84	157	245	353
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33				
Characteristic resistance A2-70, A4-70	$N_{Rk,s,seis}$	[kN]	41	59	110	172	247
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,87				
Characteristic resistance A4-80	$N_{Rk,s,seis}$	[kN]	46	67	126	196	282
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,60				
Characteristic resistance 1.4529	$N_{Rk,s,seis}$	[kN]	41	59	110	172	247
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50				
Characteristic resistance 1.4565	$N_{Rk,s,seis}$	[kN]	41	59	110	172	247
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,87				
Combined pull-out and concrete cone failure							
Dry and wet concrete	$T_{Rk,seis,C1}$	[N/mm ²]	3,9	3,9	3,9	3,9	3,9
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾				
Flooded hole	$T_{Rk,seis,C1}$	[N/mm ²]	3,9	3,9	3,9	3,9	3,9
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾				

Shear load							
Steel failure without lever arm							
Characteristic resistance grade 4.6	$V_{Rk,s,seis}$	[kN]	7	10	23	30	40
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67				
Characteristic resistance grade 5.8	$V_{Rk,s,seis}$	[kN]	9	13	28	38	51
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25				
Characteristic resistance grade 8.8	$V_{Rk,s,seis}$	[kN]	14	21	45	61	81
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25				
Characteristic resistance grade 10.9	$V_{Rk,s,seis}$	[kN]	18	26	56	76	101
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50				
Characteristic resistance A2-70, A4-70	$V_{Rk,s,seis}$	[kN]	12	18	39	53	71
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56				
Characteristic resistance A4-80	$V_{Rk,s,seis}$	[kN]	14	21	45	61	81
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33				
Characteristic resistance 1.4529	$V_{Rk,s,seis}$	[kN]	12	18	39	53	71
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25				
Characteristic resistance 1.4565	$V_{Rk,s,seis}$	[kN]	12	18	39	53	71
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56				

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Note: Rebars are not qualified for seismic design

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138




**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 1st of February 2019



.....

Name: Spyros Hatzifotis
Function: Managing Director
At Athens on 1st of February



.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sika AnchorFix-2+ for rebar connection	ETA-13/0779	88587701

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

FULL CE MARKING



14

Sika Services AG, Zurich, Switzerland

DoP No. 75735322

ETAG 001, Part 1 "Anchors in general", Part 5 "Bonded anchors"

Notified Body 1020

Bonded injection type anchor for use in cracked and non-cracked concrete

Reaction to fire - Anchorages satisfy requirements for Class A1

Anchorage subject to:

- Static and quasi-static load.
- Seismic performance category C1: threaded rod size M10, M12, M16, M20, M24

Base materials

- Non-cracked concrete.
- Cracked and non-cracked concrete for threaded rod size M10, M12, M16, M20, M24
- Reinforced or unreinforced normal weight concrete of strength class C20/25 at minimum and C50/60 at maximum according EN 206-1:2000-12.

Temperature range: -40°C to +80°C (max. short. term temperature +80°C and max. long term temperature +50°C)

Use conditions (Environmental conditions)

- Structures subject to dry internal conditions (zinc coated steel, stainless steel, high corrosion resistance steel).
- Structures subject to external atmospheric exposure including industrial and marine environment, if no particular aggressive conditions exist (stainless steel, high corrosion resistance steel).
- Structures subject to permanently damp internal condition, if no particular aggressive conditions exist (stainless steel, high corrosion resistance steel).
- Structures subject to permanently damp internal condition, with particular aggressive conditions exist (high corrosion resistance steel).

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used).

Use categories: Category 2 – installation in dry or wet concrete or in flooded hole.

Design:

- The anchorages are designed in accordance with the EOTA Technical Report TR 029 "Design of bonded anchors" under the responsibility of an engineer experienced in anchorages and concrete work.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings.
- Anchorages under seismic actions (cracked concrete) have to be designed in accordance with EOTA Technical Report TR 045 "Design of Metal Anchors under Seismic Action".

Installation:

- Dry or wet concrete or flooded hole.
- Hole drilling by rotary drill mode.
- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site.

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table B1: Installation parameters of threaded rod

Size		M8	M10	M12	M16	M20	M24	M27	M30
Nominal drill hole diameter	$\varnothing d_0$ [mm]	10	12	14	18	22	26	30	35
Diameter of cleaning brush	d_b [mm]	14	14	20	20	29	29	40	40
Torque moment	T_{inst} [Nm]	10	20	40	80	150	200	240	275
$h_{ef,min} = 8d$									
Depth of drill hole	h_0 [mm]	64	80	96	128	160	192	216	240
Minimum edge distance	c_{min} [mm]	35	40	50	65	80	96	110	120
Minimum spacing	s_{min} [mm]	35	40	50	65	80	96	110	120
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			
$h_{ef,max} = 20d$									
Depth of drill hole	h_0 [mm]	160	200	240	320	400	480	540	600
Minimum edge distance	c_{min} [mm]	80	100	120	160	200	240	270	300
Minimum spacing	s_{min} [mm]	80	100	120	160	200	240	270	300
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			

Table B2: Installation parameters of rebar

Size		$\varnothing 8$	$\varnothing 10$	$\varnothing 12$	$\varnothing 16$	$\varnothing 20$	$\varnothing 25$	$\varnothing 32$	
Nominal drill hole diameter	$\varnothing d_0$ [mm]	12	14	16	20	25	32	40	
Diameter of cleaning brush	d_b [mm]	14	14	19	22	29	40	42	
$h_{ef,min} = 8d$									
Depth of drill hole	h_0 [mm]	64	80	96	128	160	200	256	
Minimum edge distance	c_{min} [mm]	35	40	50	65	80	100	130	
Minimum spacing	s_{min} [mm]	35	40	50	65	80	100	130	
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			
$h_{ef,max} = 20d$									
Depth of drill hole	h_0 [mm]	160	200	240	320	400	500	640	
Minimum edge distance	c_{min} [mm]	80	100	120	160	200	250	320	
Minimum spacing	s_{min} [mm]	80	100	120	160	200	250	320	
Minimum thickness of member	h_{min} [mm]	$h_{ef} + 30 \text{ mm} \geq 100 \text{ mm}$				$h_{ef} + 2d_0$			

Table B3: Cleaning

All diameters
- 2 x blowing
- 2 x brushing
- 2 x blowing
- 2 x brushing
- 2 x blowing

Table B4: Minimum curing time

Sika AnchorFix® -2 Normal		
Application temperature	Processing time	Load time
+5 to +10°C	10 mins	145 mins
+10 to +15°C	8 mins	85 mins
+15 to +20°C	6 mins	75 mins
+20 to +25°C	5 mins	50 mins
+25 to +30°C	4 mins	40 mins

Processing time refers to the highest temperature in the range.
Load time refers to the lowest temperature in the range.

Declaration of Performance

Sika AnchorFix® - 2+
75735322
2017.07 , ver. 1
1138

Cartridge must be conditioned to a minimum +5°C.

Table C1: Design method TR 029

Characteristic values of resistance to tension load of threaded rod

Steel failure – Characteristic resistance										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	$N_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	2							
Steel grade 5.8	$N_{Rk,s}$	[kN]	18	29	42	79	123	177	230	281
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Steel grade 8.8	$N_{Rk,s}$	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Steel grade 10.9	$N_{Rk,s}$	[kN]	37	58	84	157	245	353	459	561
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,4							
Stainless steel grade A4-70	$N_{Rk,s}$	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,9							
Stainless steel grade A4-80	$N_{Rk,s}$	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,6							
Stainless steel grade 1.4529	$N_{Rk,s}$	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							

Combined pullout and concrete cone failure in non-cracked concrete C20/25											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Characteristic bond resistance in non-cracked concrete											
Dry and wet concrete	τ_{Rk}	[N/mm ²]	11	10	9,5	9	8,5	8	6,5	5,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾						2,1 ³⁾		
Flooded hole	τ_{Rk}	[N/mm ²]	9	8	7,5	7	7	6			
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾								
Factor for concrete C50/60	ψ_c	[-]	1								
Combined pullout and concrete cone failure in cracked concrete C20/25											
Size			M10	M12	M16	M20	M24				
Characteristic bond resistance in cracked concrete											
Dry and wet concrete	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5				
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾								
Flooded hole	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5				
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾								
Factor for cracked concrete	ψ_c	[-]				1,12					
						1,23					
						1,30					

Splitting failure										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Edge distance	$c_{cr,sp}$	[mm]	1,5 h_{ef}							
Spacing	$s_{cr,sp}$	[mm]	3,0 h_{ef}							
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,8							

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Declaration of Performance

Sika AnchorFix®- 2+

75735322

2017.07 , ver. 1

1138



Table C2: Design method TR 029

Characteristic values of resistance to tension load of rebar

Steel failure – Characteristic resistance										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$N_{Rk,s}$	[kN]	28	43	62	111	173	270	442	
Partial safety factor	γ_{Ms}	¹⁾ [-]	1,4							

Combined pullout and concrete cone failure in non-cracked concrete C20/25										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Characteristic bond resistance in non-cracked concrete										
Dry and wet concrete	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5	
Partial safety factor	γ_{Mc}	¹⁾ [-]	1,8 ²⁾							
Flooded hole	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5	
Partial safety factor	γ_{Mc}	¹⁾ [-]	2,1 ³⁾							
Factor for concrete C50/60	ψ_c	[-]	1							

Splitting failure										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Edge distance	$c_{cr,sp}$	[mm]	1,5 h_{ef}							
Spacing	$s_{cr,sp}$	[mm]	3,0 h_{ef}							
Partial safety factor	γ_{Msp}	¹⁾ [-]	1,8							

¹⁾ In absence of national regulations²⁾ The partial safety factor $\gamma_2=1,2$ is included³⁾ The partial safety factor $\gamma_2=1,4$ is included**Declaration of Performance**

Sika AnchorFix®- 2+

75735322

2017.07 , ver. 1

1138

Table C3: Design method TR 029
Characteristic values of resistance to shear load of threaded rod

Steel failure without lever arm											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Steel grade 4.6	$V_{Rk,s}$	[kN]	7	12	17	31	49	71	92	112	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67								
Steel grade 5.8	$V_{Rk,s}$	[kN]	9	15	21	39	61	88	115	140	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25								
Steel grade 8.8	$V_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25								
Steel grade 10.9	$V_{Rk,s}$	[kN]	18	29	42	79	123	177	230	281	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5								
Stainless steel grade A4-70	$V_{Rk,s}$	[kN]	13	20	30	55	86	124	161	196	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56								
Stainless steel grade A4-80	$V_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33								
Stainless steel grade 1.4529	$V_{Rk,s}$	[kN]	13	20	30	55	86	124	161	196	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25								

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Steel failure with lever arm										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	M^o	[N.m]	15	30	52	133	260	449	666	900
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67							
Steel grade 5.8	M^o	[N.m]	19	37	66	166	325	561	832	1125
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 8.8	M^o	[N.m]	30	60	105	266	519	898	1332	1799
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 10.9	M^o	[N.m]	37	75	131	333	649	1123	1664	2249
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50							
Stainless steel grade A4-70	M^o	[N.m]	26	52	92	233	454	786	1165	1574
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56							
Stainless steel grade A4-80	M^o	[N.m]	30	60	105	266	519	898	1332	1799
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33							
Stainless steel grade 1.4529	M^o	[N.m]	26	52	92	233	454	786	1165	1574
	$R_{k,s}$									
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Concrete pryout failure										
Factor k from TR 029 Design of bonded anchors, Part 5.2.3.3			2							
Partial safety factor	$\gamma_M^{1)}$	[-]	1,5							

Concrete edge failure										
Size			M8	M10	M12	M16	M20	M24	M27	M30
See section 5.2.3.4 of Technical Report TR 029 for the Design of Bonded Anchors										
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,5							

1) In absence of national regulations

Table C4: Design method TR 029

Characteristic values of resistance to shear load of rebar

Steel failure without lever arm										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$V_{Rk,s}$	[kN]	14	22	31	55	86	135	221	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Steel failure with lever arm										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$M_{oRk,s}$	[N.m]	33	65	112	265	518	1013	2122	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Concrete pryout failure										
Factor k from TR 029			2							
Design of bonded anchors, Part 5.2.3.3										
Partial safety factor	$\gamma_{Mp}^{1)}$	[-]	1,5							

Concrete edge failure										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
See section 5.2.3.4 of Technical Report TR 029 for the Design of Bonded Anchors										
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,5							

1)

In absence of national regulations

Table C5: Design method CEN/TS 1992-4 - Characteristic values of resistance to tension load of threaded rod

Steel failure – Characteristic resistance										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	$N_{Rk,s}$	[kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	2							
Steel grade 5.8	$N_{Rk,s}$	[kN]	18	29	42	79	123	177	230	281
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Steel grade 8.8	$N_{Rk,s}$	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Steel grade 10.9	$N_{Rk,s}$	[kN]	37	58	84	157	245	353	459	561
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,4							
Stainless steel grade A4-70	$N_{Rk,s}$	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,9							
Stainless steel grade A4-80	$N_{Rk,s}$	[kN]	29	46	67	126	196	282	367	449
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,6							
Stainless steel grade 1.4529	$N_{Rk,s}$	[kN]	26	41	59	110	172	247	321	393
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							

Combined pullout and concrete cone failure in non-cracked concrete C20/25											
Size			M8	M10	M12	M16	M20	M24	M27	M30	
Characteristic bond resistance in non-cracked concrete											
Dry and wet concrete	τ_{Rk}	[N/mm ²]	11	10	9,5	9	8,5	8	6,5	5,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾						2,1 ³⁾		
Flooded hole	τ_{Rk}	[N/mm ²]	9	8	7,5	7	7	6			
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾								
Factor for concrete C50/60	ψ_c	[-]	1								
Factor according to CEN/TS 1992-4-5Section 6.2.2	k_8		10,1								

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Combined pullout and concrete cone failure in cracked concrete C20/25								
Size			M10	M12	M16	M20	M24	
Characteristic bond resistance in cracked concrete								
Dry and wet concrete	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾					
Flooded hole	τ_{Rk}	[N/mm ²]	5	5	5	4,5	4,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾					
Factor for cracked concrete	C30/37		1,12					
	C40/50	ψ_c	1,23					
	C50/60		1,30					
Factor according to CEN/TS 1992-4-5 Section 6.2.2		k_8	7,2					

Concrete cone failure										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Factor according to CEN/TS 1992-4-5 Section 6.2.3	k_{ucr}		10,1							
	k_{cr}		7,2							
Edge distance	$c_{cr,N}$	[mm]	1,5 h_{ef}							
Spacing	$s_{cr,N}$	[mm]	3,0 h_{ef}							
Splitting failure										
Edge distance	$c_{cr,sp}$	[mm]	1,5 h_{ef}							
Spacing	$s_{cr,sp}$	[mm]	3,0 h_{ef}							
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,8							

¹⁾ In absence of national regulations; ²⁾ The partial safety factor $\gamma_2=1,2$ is included, ³⁾ The partial safety factor $\gamma_2=1,4$ is included

Table C6: Design method CEN/TS 1992-4

Characteristic values of resistance to tension load of rebar

Steel failure – Characteristic resistance										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$N_{Rk,s}$	[kN]	28	43	62	111	173	270	442	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,4							

Combined pullout and concrete cone failure in non-cracked concrete C20/25										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Characteristic bond resistance in non-cracked concrete										
Dry and wet concrete	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,8 ²⁾							
Flooded hole	τ_{Rk}	[N/mm ²]	12	10	10	9	9	9	5,5	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	2,1 ³⁾							
Factor for concrete C50/60	ψ_c	[-]	1							
Factor according to CEN/TS 1992-4-5 Section 6.2.2		k_8	10,1							

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138



Concrete cone failure							
Size	Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32
Factor according to CEN/TS 1992-4-5 Section 6.2.3 k_{ucr}	10,1						
Edge distance $c_{cr,N}$ [mm]	1,5 h_{ef}						
Spacing $s_{cr,N}$ [mm]	3,0 h_{ef}						
Splitting failure							
Edge distance $c_{cr,sp}$ [mm]	1,5 h_{ef}						
Spacing $s_{cr,sp}$ [mm]	3,0 h_{ef}						
Partial safety factor $\gamma_{Ms}^{1)}$ [-]	1,8						

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Table C7: Design method CEN/TS 1992-4 Characteristic values of resistance to shear load of threaded rod

Steel failure without lever arm									
Size		M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	$V_{Rk,s}$ [kN]	7	12	17	31	49	71	92	112
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,67							
Steel grade 5.8	$V_{Rk,s}$ [kN]	9	15	21	39	61	88	115	140
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,25							
Steel grade 8.8	$V_{Rk,s}$ [kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,25							
Steel grade 10.9	$V_{Rk,s}$ [kN]	18	29	42	79	123	177	230	281
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,5							
Stainless steel grade A4-70	$V_{Rk,s}$ [kN]	13	20	30	55	86	124	161	196
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,56							
Stainless steel grade A4-80	$V_{Rk,s}$ [kN]	15	23	34	63	98	141	184	224
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,33							
Stainless steel grade 1.4529	$V_{Rk,s}$ [kN]	13	20	30	55	86	124	161	196
Partial safety factor	$\gamma_{Ms}^{1)}$ [-]	1,25							
Ductility factor according to CEN/TS 1992-4-5 Section 6.3.2.1	k2	0,8							

Declaration of Performance

Sika AnchorFix®- 2+

75735322

2017.07 , ver. 1

1138

Steel failure with lever arm										
Size			M8	M10	M12	M16	M20	M24	M27	M30
Steel grade 4.6	M^o $R_{k,s}$	[N.m]	15	30	52	133	260	449	666	900
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67							
Steel grade 5.8	M^o $R_{k,s}$	[N.m]	19	37	66	166	325	561	832	1125
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 8.8	M^o $R_{k,s}$	[N.m]	30	60	105	266	519	898	1332	1799
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Steel grade 10.9	M^o $R_{k,s}$	[N.m]	37	75	131	333	649	1123	1664	2249
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50							
Stainless steel grade A4-70	M^o $R_{k,s}$	[N.m]	26	52	92	233	454	786	1165	1574
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56							
Stainless steel grade A4-80	M^o $R_{k,s}$	[N.m]	30	60	105	266	519	898	1332	1799
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33							
Stainless steel grade 1.4529	M^o $R_{k,s}$	[N.m]	26	52	92	233	454	786	1165	1574
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25							
Concrete pryout failure										
Factor according to CEN/TS 1992-4-5 Section 6.3.3		k_3	2,0							
Partial safety factor	$\gamma_{MP}^{1)}$	[-]	1,5							

Concrete edge failure										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
See section 6.3.4 of CEN/TS 1992-4-5										
Effective length of anchor	l_f	[mm]	$l_f = \min(h_{ef}; 8 d_{nom})$							
Outside diameter of anchor	d_{nom}	[mm]	8	10	12	16	20	24	30	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,5							

¹⁾ In absence of national regulations

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C8: Design method CEN/TS 1992-4

Characteristic values of resistance to shear load of rebar

Steel failure without lever arm										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$V_{Rk,c}$	[kN]	14	22	31	55	86	135	221	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Ductility factor according to CEN/TS 1992-4-5 Section 6.3.2.1		K_2	0,8							
Steel failure with lever arm										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
Rebar BSt 500 S	$M_{Rk,s}^o$	[N.m]	33	65	112	265	518	1013	2122	
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,5							
Concrete pryout failure										
Factor according to CEN/TS 1992-4-5 Section 6.3.3		K_3	2,0							
Partial safety factor	γ_M	[-]	1,5							
Concrete edge failure										
Size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32	
See section 6.3.4 of CEN/TS 1992-4-5										
Effective length of anchor	l_f	[mm]	$l_f = \min(h_{ef}; 8 d_{nom})$							
Outside diameter of anchor	d_{nom}	[mm]	8	10	12	16	20	24	30	
Partial safety factor	$\gamma_{Mc}^{1)}$	[-]	1,5							

¹⁾ In absence of national regulations**Table C9:** Displacement of threaded rod under tension and shear load

Anchor size			M8	M10	M12	M16	M20	M24	M27	M30
Non-cracked concrete										
Tension load	F	[kN]	6,3	7,9	11,9	15,9	23,8	29,8	37,7	45,6
Displacement	δ_{N0}	[mm]	0,3	0,3	0,3	0,3	0,4	0,5	0,5	0,5
	$\delta_{N\infty}$	[mm]	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Shear load	F	[kN]	3,1	5,0	7,2	13,5	21,0	30,3	39,4	48,0
Displacement	δ_{V0}	[mm]	1,5	1,5	1,5	1,5	2,0	2,5	2,5	2,5
	$\delta_{V\infty}$	[mm]	2,3	2,3	2,3	2,3	3,0	3,8	3,8	3,8
Cracked concrete										
Tension load	F	[kN]		5,1	7,4	13,1	20,5	24,6		
Displacement	δ_{N0}	[mm]		0,4	0,7	0,7	0,7	0,6		

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Table C10: Displacement of rebar under tension and shear load

Rebar size			Ø8	Ø10	Ø12	Ø16	Ø20	Ø25	Ø32
Non-cracked concrete									
Tension load	F	[kN]	7,9	9,9	13,9	23,8	29,8	55,6	55,
Displacement	δ_{N0}	[mm]	0,3	0,3	0,3	0,4	0,4	0,5	0,5
	$\delta_{N\infty}$	[mm]	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Shear load	F	[kN]	5,9	9,3	13,3	23,7	37,0	57,9	94,
Displacement	δ_{V0}	[mm]	0,3	0,4	0,4	0,4	0,4	0,5	0,9
	$\delta_{V\infty}$	[mm]	0,5	0,6	0,6	0,6	0,6	0,8	1,4

Table C11: Characteristic values of resistance under seismic action category C1 for threaded rods

Size			M10	M12	M16	M20	M24
Tension load							
Steel failure							
Characteristic resistance grade 4.6	$N_{Rk,s,seis}$	[kN]	23	34	63	98	141
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	2,00				
Characteristic resistance grade 5.8	$N_{Rk,s,seis}$	[kN]	29	42	79	123	177
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,50				
Characteristic resistance grade 8.8	$N_{Rk,s,seis}$	[kN]	46	67	126	196	282
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,50				
Characteristic resistance grade 10.9	$N_{Rk,s,seis}$	[kN]	58	84	157	245	353
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,33				
Characteristic resistance A2-70, A4-70	$N_{Rk,s,seis}$	[kN]	41	59	110	172	247
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,87				
Characteristic resistance A4-80	$N_{Rk,s,seis}$	[kN]	46	67	126	196	282
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,60				
Characteristic resistance 1.4529	$N_{Rk,s,seis}$	[kN]	41	59	110	172	247
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,50				
Characteristic resistance 1.4565	$N_{Rk,s,seis}$	[kN]	41	59	110	172	247
Partial safety factor	$\gamma_{Ms}^{(1)}$	[-]	1,87				
Combined pull-out and concrete cone failure							
Dry and wet concrete	$\tau_{Rk,seis,C1}$	[N/mm ²]	3,9	3,9	3,9	3,9	3,9
Partial safety factor	$\gamma_{Mc}^{(1)}$	[-]	1,8 ²⁾				
Flooded hole	$\tau_{Rk,seis,C1}$	[N/mm ²]	3,9	3,9	3,9	3,9	3,9
Partial safety factor	$\gamma_{Mc}^{(1)}$	[-]	2,1 ³⁾				

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

Shear load							
Steel failure without lever arm							
Characteristic resistance grade 4.6	$V_{Rk,s,seis}$	[kN]	7	10	23	30	40
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,67				
Characteristic resistance grade 5.8	$V_{Rk,s,seis}$	[kN]	9	13	28	38	51
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25				
Characteristic resistance grade 8.8	$V_{Rk,s,seis}$	[kN]	14	21	45	61	81
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25				
Characteristic resistance grade 10.9	$V_{Rk,s,seis}$	[kN]	18	26	56	76	101
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,50				
Characteristic resistance A2-70, A4-70	$V_{Rk,s,seis}$	[kN]	12	18	39	53	71
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56				
Characteristic resistance A4-80	$V_{Rk,s,seis}$	[kN]	14	21	45	61	81
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,33				
Characteristic resistance 1.4529	$V_{Rk,s,seis}$	[kN]	12	18	39	53	71
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,25				
Characteristic resistance 1.4565	$V_{Rk,s,seis}$	[kN]	12	18	39	53	71
Partial safety factor	$\gamma_{Ms}^{1)}$	[-]	1,56				

¹⁾ In absence of national regulations

²⁾ The partial safety factor $\gamma_2=1,2$ is included

³⁾ The partial safety factor $\gamma_2=1,4$ is included

Note: Rebars are not qualified for seismic design

<http://dop.sika.com>

CE MARKING TO BE PLACED ON THE LABEL



14

Sika Services AG, Zurich, Switzerland

DoP No. 75735322

ETAG 001, Part 1 "Anchors in general", Part 5 "Bonded anchors"

Notified Body 1020

Bonded injection type anchor for use in cracked and non-cracked concrete

For details see accompanying documents

<http://dop.sika.com>

Declaration of Performance

Sika AnchorFix®- 2+

75735322

2017.07 , ver. 1

1138

30/31

BUILDING TRUST



ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica-Greece
www.sika.gr

Declaration of Performance

Sika AnchorFix®- 2+
75735322
2017.07 , ver. 1
1138

31/31

BUILDING TRUST

