

BUILDING TRUST

Sika® ViscoCrete®-5600 HS DECLARATION OF PERFORMANCE No. 23675267

| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE: | 23675267 | |
|----|--|--|--|
| 2 | INTENDED USE/S: | EN 934-2:2009+A1:2012 To be used in concrete High range water reducing / Superplasticizing admixture (Tables 3.1 & 3.2) | |
| 3 | MANUFACTURER: | Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr | |
| 4 | AUTHORISED REPRESENTATIVE: | | |
| 5 | SYSTEM/S OF AVCP: | System 2+ | |
| 6a | HARMONISED STANDARD: | EN 934-2:2009+A1:2012 | |
| | Notified body/ies: | 1128 | |

Declaration of Performance Sika® ViscoCrete®-5600 HS 23675267 2019.09 , Revision 1 7 DECLARED PERFORMANCE/S:

| Essential Characteristics | Performance | Harmonised Technical Specification |
|----------------------------------|--|--|
| Tables 3.1 & 3.2 | | |
| Water reduction | In test mix $\ge 12\%$ compared with control mix | - EN 934- 2:2009+A1:2012 |
| Compressive strength | T3.1: At 1 day: Test mix ≥ 140 % of control mix, At 28 days: Test mix ≥ 115 % of control mix | |
| | T3.2: At 28 days: test mix ≥ 90 % of control mix | |
| Air content in fresh concrete | Test mix \leq 2 % by volume above control mix | |
| Increase in consistence | Increase in slump ≥ 120 mm from initial (30 ± 10) mm | |
| Retention of consistence | 30 min after the addition the consistence of the test mix does not fall below the value of the initial consistence of the control mix | |
| General Characteristics | Performance | |
| Chloride ion content | Chloride free | |
| Alkali content | ≤ 0.5 % by mass | |
| Corrosion behavior | Contains components only from EN 934- 1:2008, Annex A.1 | |
| Dangerous Substances | NPD* | - |
| *NPD - No performance determined | | - |

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

End of information as required by Regulation (EU) No 305/2011

Signed for and on behalf of the manufacturer by:

Name : Manolis Mavratzotis Function: R&D/QC Manager At Athens on 09 September 2019

Name : Spyros Hatzifotis Function: General Manager At Athens on 09 September 2019

BUILDING TRUST



Declaration of Performance Sika® ViscoCrete®-5600 HS 23675267 2019.09 , Revision 1

CE

Sika Hellas ABEE, Athens - Greece

23675267

EN 934-2:2009+A1:2012

1128

Sika® ViscoCrete®-5600 HS To be used in concrete High range water reducing / Superplasticizing admixture (Tables 3.1 & 3.2)

For essential characteristics please refer to Declaration of Performance

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance Sika® ViscoCrete®-5600 HS 23675267 2019.09 , Revision 1





Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance Sika® ViscoCrete®-5600 HS 23675267 2019.09 , Revision 1



BUILDING TRUST