

Sikafloor®-2650

DECLARATION OF PERFORMANCE

No 82789841

1	Unique identification code of the product-type:	82789841	
2	Intended use/es:	For internal uses subject to reaction to fire regulations — Synthetic resin screed material All other uses — Synthetic resin screed material	
3	Manufacturer:	Sika Services AG	
		Tüffenwies 16	
		8064 Zürich	
		Switzerland	
5	System/s of AVCP:	System 3 (For internal uses subject to reaction to fire regulations) System 4 (All other uses)	
6a	Harmonised standard:	EN 13813:2002	
		Screed material and floor screeds — Screed material — Properties and requirements	
	Notified body/ies:	1611	

7 Declared performance/s:				
Essential Characteristics	Performance		AVCP	Harmonised Technical Specification
Reaction to fire	Class B _{fl} -s1		System 3	_
Release of corrosive substances	SR		System 4	
Water permeability	NPD		System 4	
Mechanical resistance	Wear resistance	AR0,5	System 4	005
	Bond strength	B2,0		3813:2002
	Impact resistance	IR4		1381
Sound insulation	NPD		System 4	_ Z
Sound absorption	NPD		System 4	_
Thermal resistance	NPD		System 4	_
Chemical resistance	NPD		System 4	_

The product is tested as a part of a system build-up.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski

Function: Corporate Standardisation and Approvals

At Warsaw on 2022/05/18

Name: Maciej Michalewski

Function: Standardisation and Approvals

At Warsaw on 2022/05/18

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

	C€		
	22		
	Sika Services AG, Zürich,	Switzerland	
	82789841		
Reaction to fire	Class B _{fi} -s1		
Release of corrosive substances	SR		
Mechanical resistance	Wear resistance	AR0,5	
	Bond strength	B2,0	
	Impact resistance	IR4	
	EN 13813:200	2	
	1611		
For internal u	ses subject to reaction to fire regulati All other uses — Synthetic res	ons — Synthetic resin screed material n screed material	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.