

PRODUCT DATA SHEET

Sarnafast® SF-4.8

Carbon Steel Fastener for Mechanically Fastened Roof Waterproofing Membranes and Thermal Insulation

DESCRIPTION

Case hardened carbon steel fastener with self drilling tip for mechanical fastening roof waterproofing membranes and thermal insulation.

USES

Steel fastener for mechanical fastening roof waterproofing membranes and thermal insulation into steel or timber decks. Used in combination with:

- Sarnafast® KT
- Sarnafast® DT
- Sarnabar® Fastening Profiles
- Sarnafast® IF/IG-C

FEATURES

- Fast and easy installation due to optimised drill tip
- High pull-out values with asymmetric fastener thread
- High quality corrosion protection, environment friendly, free of Chromium VI
- Support thread under the fastener head provides a steadfast fastening system



CERTIFICATES AND TEST REPORTS

- European Technical Approval ETA-23/0859
- FM Approval Standard 4470

PRODUCT INFORMATION

Composition

Case hardened carbon steel with Durocoat® corrosion protection.

Packaging	Length	Packaging
	60 mm	500 pcs/box
	70 mm	500 pcs/box
	80 mm	500 pcs/box
	90 mm	500 pcs/box
	100 mm	500 pcs/box
	120 mm	500 pcs/box
	140 mm	250 pcs/box
	160 mm	250 pcs/box
	180 mm	100 pcs/box
	200 mm	100 pcs/box
	220 mm	100 pcs/box
	240 mm	100 pcs/box
	260 mm	100 pcs/box
	280 mm	100 pcs/box
	300 mm	100 pcs/box

Shelf life	5 years from date of production
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions. Always refer to packaging.
Head type	<ul style="list-style-type: none"> ▪ Hexagon head diameter 8 mm ▪ Head height 4 mm

TECHNICAL INFORMATION

Corrosion resistance	Resistance 15 cycles Kesternich test according to: <ul style="list-style-type: none"> • EAD 030351-00-0402, A2.4
-----------------------------	---

APPLICATION INFORMATION

Ambient air temperature	Minimum	-20 °C
	Maximum	+60 °C
Substrate temperature	Minimum	-30 °C
	Maximum	+60 °C

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.
- The use of the Sarnafast® SF-4.8 is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of

APPLICATION INSTRUCTIONS

APPLICATION

Installation works to be carried out only by Sika instructed contractors for roofing. Sarnafast® SF-4.8 must be installed in accordance with Sika application manual and installation instructions:

a) on steel deck:

Substrate quality:	S235 – S320GD
Substrate thickness:	min. 0.6 mm max. 2 × 1.25 mm or 1 × 2.0 mm
Setting depth:	min. 20 mm + roof build-up

b) on timber deck:

Substrate material thickness:	min. 18 mm
Setting depth:	min. 30 mm + roof build-up

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE

15, Protomagias Str.
GR 145 68, Kryoneri, Attica
Tel.: +30 210 81 60 600
E-mail: info@gr.sika.com
www.sika.gr



Product Data Sheet

Sarnafast® SF-4.8
March 2025, Version 03.01
020945051100001000

SarnafastSF-48-en-GR-(03-2025)-3-1.pdf