
according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B



Jika

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-831 HP Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : For professional users only.

1.3 Details of the supplier of the safety data sheet

Company : Sika Hellas ABEE

Protomagias Street 15 14568 Kyroneri / Athens

Telephone : +302108160600 E-mail address : EHS@gr.sika.com

1.4 Emergency telephone number

Emergency telephone num-

ber

: Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour. Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - repeated H373: May cause damage to organs through pro-

Specific target organ toxicity - repeated exposure, Category 2 H373: May cause damage to longed or repeated exposure.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Harmful R48/22: Harmful: danger of serious damage to

health by prolonged exposure if swallowed.

Irritant R36: Irritating to eyes.

Dangerous for the environment R51/53: Toxic to aquatic organisms, may cause

long-term adverse effects in the aquatic environ-

ment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1

Print Date 27.07.2015

Hazard pictograms









Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H319 Causes serious eye irritation. H373 May cause damage to organs

May cause damage to organs through pro-

longed or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water/shower.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

• 270-877-4 diethylmethylbenzenediamine

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Polyetherpolyol	R52/53	Aquatic Chronic3; H412	>= 50 - <= 100
diethylmethylbenzenediamine 68479-98-1 270-877-4 01-2119486805-25-XXXX	Xn; R21/22- R48/22 Xi; R36 N; R50/53	Acute Tox.4; H302 Acute Tox.4; H312 Eye Irrit.2; H319 STOT RE2; H373	>= 20 - < 25

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B



 Revision Date 27.07.2015
 Version 1.1
 Print Date 27.07.2015

Aquatic Acute1; H400 Aquatic Chronic1; H410

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Country GR 100000009209 3 / 12

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1 Print Date 27.07.2015

Unsuitable extinguishing

media

: Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod
: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers. Collect contam-

> inated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with

local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

> Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local


/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B





SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic

discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B



proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : various

Odour : characteristic

Odour Threshold : No data available

Flash point : $> 60 \, ^{\circ}\text{C}$

Ignition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : Note: Not applicable

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1 Print Date 27.07.2015

Melting point/range / Freez- : No data available

ing point

Boiling point/boiling range

: No data available

Vapour pressure : No data available

Density : ca.1,01 g/cm3

at 23 °C

Water solubility : No data available

Partition coefficient: n-

octanol/water

Viscosity, dynamic

: No data available

: ca.600 mPa.s at ca. 25 °C

Viscosity, kinematic : No data available

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

diethylmethylbenzenediamine:

Acute oral toxicity : LD50 Oral (Rat): 738 mg/kg

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1 Print Date 27.07.2015



12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 3082

14.2 Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

14.3 Class: 914.4 Packing group: IIIClassification Code: M6Labels: 9Tunnel restriction code: (E)14.5 Environmentally hazard-: yes

ous

IATA

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1 Print Date 27.07.2015

14.1 UN number : 3082

14.2 Description of the goods : Environmentally hazardous substance, liquid, n.o.s.

14.3 Class 14.4 Packing group : 111 Labels : 9 14.5 Environmentally hazard-: ves

IMDG

14.1 UN number : 3082

14.2 Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

14.3 Class : 9 14.4 Packing group : 111 Labels : 9 EmS Number 1 : F-A EmS Number 2 : S-F 14.5 Marine pollutant : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances.

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

: Not applicable

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : Not applicable

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B

Revision Date 27.07.2015 Version 1.1 Print Date 27.07.2015



15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R21/22 Harmful in contact with skin and if swallowed.

R36 Irritating to eyes.

R48/22 Harmful: danger of serious damage to health by prolonged exposure if

swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

Full text of H-Statements

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms





Harmful

Dangerous for the environment

R-phrase(s) : R36 Irritating to eyes.

R51/53

R48/22 Harmful: danger of serious damage to

health by prolonged exposure if swallowed.
Toxic to aquatic organisms, may cause
long-term adverse effects in the aquatic

environment.

Hazardous components which must be listed on the label:

• 270-877-4 diethylmethylbenzenediamine

Full text of other abbreviations

Acute Tox. Acute toxicity
Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity

Eye Irrit. Eye irritation

STOT RE Specific target organ toxicity - repeated exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemcial Abstracts Service

according to Regulation (EC) No. 1907/2006

Sikalastic®-831 HP Part B



Revision Date 27.07.2015 Version 1.1 Print Date 27.07.2015

DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LC50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LD50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the
	Council of 18 December 2006 concerning the Registration, Evaluation,
	Authorisation and Restriction of Chemicals (REACH), establishing a
	European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!