

Sika® Plastocrete® N

DECLARATION OF PERFORMANCE

No. 83136579

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	83136579
2	INTENDED USE/S:	EN934-2:2009+A1:2012 To be used in concrete Water reducing / Plasticizing admixture (Table 2) Water resisting admixture (Table 9)
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN934-2:2009+A1:2012
	Notified body/ies:	1128

Sika® Plastocrete® N 83136579 2016.10 , Revision 1

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	Harmonised Technical Specification
Table 2		
Water reduction	In test mix ≥ 5 % compared with control mix	-
Compressive strength	At 7 and 28 days: Test mix ≥ 110 % of control mix	-
Air content in fresh concrete	Test mix ≤ 2 % by volume above control mix	-
Table 9		-
Capillary absorption	Tested for 7 days after 7 days curing: test mix ≤ 50 % by mass of control mix Tested for 28 days after 90 days curing: test mix ≤ 60 % by mass of control mix	EN934- 2:2009+A1:2012
Compressive strength	At 28 days: test mix ≥ 85 % of control mix	-
Air content in fresh concrete	Test mix ≤ 2 % by volume above control mix	-
General Characteristics	Performance	-
Chloride ion content	Chloride free	-
Alkali content	≤ 6.0 % by mass	-
Corrosion behavior	Contains components only from EN934-1:2008, Annex A.1	-
Dangerous Substances	NPD*	-
*NPD - No performance determined		-

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Manolis Mavratzotis Function: R&D/QC Manager At Athens on 05 October 2016 Name: Spyros Hatzifotis Function: General Manager At Athens on 05 October 2016

End of information as required by Regulation (EU) No 305/2011

Sika ®

Sika® Plastocrete® N 83136579 2016.10 , Revision 1



Ω4

Sika Hellas ABEE, Athens - Greece

83136579

EN934-2:2009+A1:2012

1128

Sika® Plastocrete® N
To be used in concrete
Water reducing / Plasticizing admixture
(Table 2)
Water resisting admixture
(Table 9)

For essential characteristics please refer to Declaration of Performance

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

Sika® Plastocrete® N 83136579 2016.10 , Revision 1

