

# Sikacryl® Universal Pro

## DECLARATION OF PERFORMANCE

### No. 93314471

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	93314471
2	<b>INTENDED USE/S:</b>	EN 15651-1:2017 Non-structural Sealant for façade elements for exterior and interior application F-EXT-INT: Class 7,5P
3	<b>MANUFACTURER:</b>	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 3 System 3 for reaction to fire
6a	<b>HARMONISED STANDARD:</b>	EN 15651-1:2017
	Notified body/ies:	2538

#### Declaration of Performance

Sikacryl® Universal Pro

93314471

2018.10 , Revision 1

**7 DECLARED PERFORMANCE/S:**

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	
Release of chemicals dangerous to the environment and health	NPD*	
Water Tightness and Air Tightness:		
Resistance to flow	0 mm	EN 15651-1:2017
Loss of volume	≤ 25%	
Adhesion / Cohesion properties after immersion in water	> 25%	
Durability	Pass	

NPD\*: No performance determined

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Stamatios Kollias  
Function: TMM Sealing & Bonding/Industry  
At Athens on 04 June 2019



Name : Spyros Hatzifotis  
Function: General Manager  
At Athens on 04 June 2019



End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikacryl® Universal Pro  
93314471  
2018.10, Revision 1



19

Sika Hellas ABEE, Athens - Greece

DoP No. 93314471

EN 15651-1: 2017

Notified Body 2538

Non-structural Sealant for façade elements for exterior and interior application  
F-EXT-INT: Class 7,5P

Reaction to fire	Class E
Resistance to flow	0 mm
Loss of volume	≤ 25%
Adhesion / Cohesion properties after immersion in water	> 25%
Durability	Pass

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sikacryl® Universal Pro

93314471

2018.10, Revision 1



**Sika Hellas ABEE**  
15 Protomagias Str.  
GR 145 68 Kryoneri  
Athens - Greece  
[www.sika.gr](http://www.sika.gr)

**Declaration of Performance**  
Sikacryl® Universal Pro  
93314471  
2018.10, Revision 1