

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikafloor®-378 Part A

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 Eye irritation, Category 2 Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Category 2 H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	•
Hazard statements	:	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

# Sikafloor<sup>®</sup>-378 Part A

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



Precautionary statements	:	Prevention:	
		P261 P264 P273 P280	Avoid breathing mist or vapours. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
		Response:	
		P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
		P391	Collect spillage.

#### Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane bis-[4-(2,3-epoxypropoxy)phenyl]methane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

#### Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# Sikafloor<sup>®</sup>-378 Part A

Revision Date: 28.03.2024 Date of last issue: 30.04.2020



Version 3.0

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 $\longrightarrow$ specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 25 - < 40
bis-[4-(2,3- epoxypropoxy)phenyl]methane	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 2,5 - < 5
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	>= 1 - < 2,5
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5
Substances with a workplace expo Titanium dioxide (> 10 µm)	13463-67-7		>= 5 - < 10
For explanation of abbreviations so	236-675-5 01-2119489379-17- XXXX		

For explanation of abbreviations see section 16.

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



#### **SECTION 4: First aid measures**

4.1 Description of first aid measu	res	5
General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms and	d e	ffects, both acute and delayed
Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	irritant effects sensitising effects
		Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
4.3 Indication of any immediate m	ned	lical attention and special treatment needed
Treatment	:	Treat symptomatically.
SECTION 5: Firefighting meas	ure	es
5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

# Sikafloor®-378 Part A



Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0

one opeenal mazar de ariering menn	••••	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protect	tive	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			

Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
		respective authorities.
	Environmental precautions	Environmental precautions :

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being</li> </ul>
		used.

# Sikafloor<sup>®</sup>-378 Part A



Revision Date: 28.03.2024 Date of last issue: 30.04.2020		Version 3.0	Print Date 28.03.202
		Smoking, eating and drinking should be prohibite plication area. Follow standard hygiene measures when handlir products	·
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygier practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the er	using do not
7.2 Conditions for safe storage, in	nc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Containers which are opened must be car sealed and kept upright to prevent leakage. Stor- ance with local regulations.	efully re-
Further information on stor- age stability	:	No decomposition if stored and applied as direct	ed.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet p use.	rior to any

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable)	10 mg/m3	GR OEL
		TWA (respirable)	5 mg/m3	GR OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment						
Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water					
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.					
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm)					

# Sikafloor®-378 Part A

Revision Date: 28.03.2024



Date of last issue: 30.04.2020		
	Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	<ul> <li>Protective clothing (e.g. Safety shoes acc. to I long-sleeved working clothing, long trousers). and protective boots are additionaly recomme and stirring work.</li> </ul>	Rubber aprons
Respiratory protection	<ul> <li>In case of inadequate ventilation wear respirate Respirator selection must be based on known exposure levels, the hazards of the product are ing limits of the selected respirator. organic vapor filter (Type A) A1: &lt; 1000 ppm; A2: &lt; 5000 ppm; A3: &lt; 1000 Ensure adequate ventilation. This can be achi exhaust extraction or by general ventilation. (F ods for determining inhalation exposure). This ticular to the mixing / stirring area. In case this to keep the concentrations under the occupati limits then respiration protection measures must</li> </ul>	or anticipated ad the safe work- 0 ppm eved by local EN 689 - Meth- applies in par- is not sufficent onal exposure
Environmental exposure	controls	
General advice	: Do not flush into surface water or sanitary sew If the product contaminates rivers and lakes o	

respective authorities.

Version 3.0

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid						
Appearance	:	viscous						
Colour	:	various						
Odour	:	epoxy-like						
Melting point/range / Freezing point	:	No data available						
Boiling point/boiling range	:	No data available						
Flammability (solid, gas)	:	No data available						
Upper/lower flammability or explosive limits								
Upper explosion limit / Upper flammability limit	:	No data available						
Lower explosion limit / Lower flammability limit	:	No data available						
Flash point	:	ca. 86 °C Method: closed cup						

# Sikafloor<sup>®</sup>-378 Part A

Revision Date: 28.03.2024 Date of last issue: 30.04.2020



Version 3.0

Auto-ignition temperature	:	ca. 436 °C
Decomposition temperature	:	No data available
рН	:	ca. 6,5 (20 °C) Concentration: 100 %
Viscosity		
Viscosity, dynamic	:	ca. 4.000 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,63 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available
9.2 Other information		

No data available

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

#### 10.5 Incompatible materials

Materials to avoid : No data available

# Sikafloor<sup>®</sup>-378 Part A

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Acute toxicity

Not classified based on available information.

#### **Components:**

#### bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg

#### Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

#### oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg

#### benzyl alcohol:

Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method

#### p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 6.000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

# Sikafloor<sup>®</sup>-378 Part A

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Components:

# bis-[4-(2,3-epoxipropoxi)phenyl]propane:Toxicity to fish:LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l<br/>Exposure time: 96 hToxicity to daphnia and other<br/>aquatic invertebrates:EC50 (Daphnia magna (Water flea)): 1,8 mg/l<br/>Exposure time: 48 h

#### bis-[4-(2,3-epoxypropoxy)phenyl]methane:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l



Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0

			Exposure time: 96 h				
	Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h				
	Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h				
	<b>benzyl alcohol:</b> Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h				
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h				
12.2	2 Persistence and degradabili No data available	ity					
12.3	Bioaccumulative potential No data available						
12.4	<b>I Mobility in soil</b> No data available						
12.5	12.5 Results of PBT and vPvB assessment						
	Product: Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher				
12.6	12.6 Endocrine disrupting properties						
	Product: Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.				
12.7	7 Other adverse effects						
	Product: Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.				

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	The generation of waste should be avoided or minimize wherever possible. Empty containers or liners may retain some product res This material and its container must be disposed of in a way. Dispose of surplus and non-recyclable products via a li waste disposal contractor. Disposal of this product, solutions and any by-products at all times comply with the requirements of environme protection and waste disposal legislation and any regio local authority requirements. Avoid dispersal of spilled material and runoff and conta soil, waterways, drains and sewers.	sidues. a safe censed s should ntal nal
European Waste Catalogue	08 01 11* waste paint and varnish containing organic s vents or other dangerous substances	sol-
Contaminated packaging	15 01 10* packaging containing residues of or contamined by dangerous substances	nated

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR	:	UN 3082		
IMDG	:	UN 3082		
ΙΑΤΑ	:	UN 3082		
14.2 UN proper shipping name				
ADR	:	ENVIRONMENTALLY N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, LIQUI	D,
IMDG	:	ENVIRONMENTALLY N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, LIQUI	D,
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)		
14.3 Transport hazard class(es)				
		Class	Subsidiary risks	
ADR	:	9		
IMDG	:	9		
ΙΑΤΑ	:	9		
Country GR 10000007406				12

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



#### 14.4 Packing group ADR Ш Packing group ÷ Classification Code M6 Hazard Identification Number : 90 Labels 9 Tunnel restriction code : (-) IMDG Packing group Ш 2 Labels 9 EmS Code ÷ F-A, S-F IATA (Cargo) Packing instruction (cargo : 964 aircraft) Packing instruction (LQ) Y964 ÷ Packing group Ш Miscellaneous Labels : IATA (Passenger) Packing instruction (passen-: 964 ger aircraft) Packing instruction (LQ) Y964 Packing group Ш Labels Miscellaneous 14.5 Environmental hazards

# ADREnvironmentally hazardous: yesIMDGMarine pollutant: yesIATA (Passenger)Environmentally hazardous: yesIATA (Cargo)Environmentally hazardous: yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Country GR 10000007406

# Sikafloor<sup>®</sup>-378 Part A

Print Date 28.03.2024

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0

REACH Information:			gulation, and/or		
REACH - Restrictions on the main the market and use of certain date mixtures and articles (Annex XVI	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3		
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		:	None of the components are listed $(=> 0.1 \%)$ .		
REACH - List of substances subject to authorisation (Annex XIV)		:	Not applicable		
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer		:	Not applicable		
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)		:	Not applicable		
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 3,38% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,38% w/w

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0



#### **SECTION 16: Other information**

Full text of H-Statements					
H302 :	Harmful if swallowed.				
H315 :	Causes skin irritation.				
H317 :	May cause an allergic skin reaction.				
H319 :	Causes serious eye irritation.				
H332 :	Harmful if inhaled.				
H411 :	Toxic to aquatic life with long lasting effects.				
Full text of other abbreviations					
Acute Tox.	Acute toxicity				
Aquatic Chronic :	Long-term (chronic) aquatic hazard				
Eye Irrit.	Eye irritation				
Skin Irrit.	Skin irritation				
Skin Sens.	Skin sensitisation				
GR OEL :	Greece. Exposure limit values				
GR OEL / TWA	Long term exposure limit				
ADR :	European Agreement concerning the International Carriage of				
ADIX .	Dangerous Goods by Road				
CAS :	Chemical Abstracts Service				
DNEL :	Derived no-effect level				
EC50 :	Half maximal effective concentration				
GHS :					
	Globally Harmonized System				
IATA :	International Air Transport Association				
IMDG :	International Maritime Code for Dangerous Goods				
LD50 :	Median lethal dosis (the amount of a material, given all at				
	once, which causes the death of 50% (one half) of a group of				
	test animals)				
LC50 :	ledian lethal concentration (concentrations of the chemical in				
	air that kills 50% of the test animals during the observation				
	period)				
MARPOL :	International Convention for the Prevention of Pollution from				
	Ships, 1973 as modified by the Protocol of 1978				
OEL :	Occupational Exposure Limit				
PBT :	Persistent, bioaccumulative and toxic				
PNEC :	Predicted no effect concentration				
REACH :	Regulation (EC) No 1907/2006 of the European Parliament				
	and of the Council of 18 December 2006 concerning the Reg-				
	istration, Evaluation, Authorisation and Restriction of Chemi-				
	cals (REACH), establishing a European Chemicals Agency				
SVHC :	Substances of Very High Concern				
vPvB :	Very persistent and very bioaccumulative				

#### **Further information**

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method

# Sikafloor<sup>®</sup>-378 Part A



Revision Date: 28.03.2024 Date of last issue: 30.04.2020 Version 3.0

Aquatic Chronic 2

H411

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN