

# Sika<sup>®</sup> Sigunit<sup>®</sup>-2206 L Max

## DECLARATION OF PERFORMANCE No. 80955494

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	80955494
2	<b>INTENDED USE/S:</b>	EN934-5:2007 To be used in sprayed concrete Sprayed concrete set accelerating admixture (Table 2)
3	<b>MANUFACTURER:</b>	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+
6a	<b>HARMONISED STANDARD:</b>	EN934-5:2007
	Notified body/ies:	1128

### Declaration of Performance

Sika<sup>®</sup> Sigunit<sup>®</sup>-2206 L Max  
80955494  
2023.05 , Revision 1

**7 DECLARED PERFORMANCE/S:**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
<b>Table 2</b>		System 2+	
Setting Time	Initial setting time ≤ 10 min. Final setting time ≤ 60min (average of three tests)	System 2+	
Compressive Strength	At 28 days: Compressive strength of test mix ≥ 75 % compressive strength of control mix. At 90 days: Compressive strength of test mix ≥ compressive strength of test mix at 28 days	System 2+	EN934-5:2007
<b>General Characteristics</b>	<b>Performance</b>	System 2+	
Chloride ion content	Chloride free	System 2+	
Alkali content	≤ 21.0 % by mass	System 2+	
Corrosion behavior	Contains components only from EN 934-1:2008, Annex A.1	System 2+	
Dangerous Substances	NPD*		


\* NPD - No performance determined

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Giorgos Katsantonis  
 Function: Target Market Concrete Manager  
 At Athens on 19 May 2023



.....

Name: Angeliki Zacharopoulou  
 Function: QEHS Manager  
 At Athens on 19 May 2023



.....

End of information as required by Regulation (EU) No 305/2011





23

Sika Hellas ABEE, Athens - Greece

80955494

EN934-5:2007

1128

Sika® Sigunit® L-22 E  
To be used in sprayed concrete  
Sprayed concrete set accelerating admixture (Table 2)

For essential characteristics please refer to Declaration of Performance

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sika® Sigunit®-2206 L Max E

80955494

2023.05 , Revision 1



**Sika Hellas ABEE**  
15 Protomagias Str.  
GR 145 68 Kryoneri  
Athens - Greece  
[www.sika.gr](http://www.sika.gr)

© Sika Services AG

**Declaration of Performance**  
Sika® Sigunit®-2206 L Max E  
80955494  
2023.05 , Revision 1