according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Date of last issue: 21.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-570 Top Coat

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Liquid applied membranes

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P272 Contaminated work clothing should not be

allowed out of the workplace.

P280 Wear protective gloves.

Response:

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

P333 + P313 If skin irrit

If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)

1,2-benzisothiazol-3(2H)-one (BIT)

2-methyl-2H-isothiazol-3-one (MIT)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
4-ethylmorpholine	100-74-3 202-885-0 01-2120120216-72- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314	< 1
4,5-dichloro-2-octyl-2H-isothiazol- 3-one (DCOIT)	64359-81-5 264-843-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 10	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

1,2-benzisothiazol-3(2H)-one

pyridine-2-thiol 1-oxide, sodium

2-methyl-2H-isothiazol-3-one

Revision Date: 25.02.2021 Version 3.0

2634-33-5

220-120-9

3811-73-2

223-296-5

2682-20-4

220-239-6

XXXX

01-2120764690-50-

XXXX

01-2120761540-60-

Date of last issue: 21.01.2019

(BIT)

salt

(MIT)



	Jika
)	Print Date 25.02.202
Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400 M-Factor (Acute aquatic toxicity): 100	>= 0,0025 - < 0,025

>= 0,0025 - <

0,025

Acute Tox. 3; H301

Acute Tox. 2; H330

Acute Tox. 3; H311

Skin Corr. 1B; H314

	Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	
	M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
	specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Date of last issue: 21.01.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

according to Regulation (EC) No. 1907/2006

Sikalastic[®]-570 Top Coat

Revision Date: 25.02.2021 Version 3.0 Print Date 25.02.2021

Date of last issue: 21.01.2019

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Do not breathe vapours or spray mist. Advice on safe handling

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Handle in accordance with good industrial hygiene and safety Hygiene measures

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat



Date of last issue: 21.01.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
4-ethylmorpholine	100-74-3	STEL	20 ppm 94 mg/m3	GR OEL
	Further information: The notation 'skin' (D), pointing out cer chemical factors of the table of paragraph of 1 article 3, im the likely contribution to of these chemical factors to the qu of exposure to workers which are absorbed through the ski direct contact with these.			e 3, implies the quantity
		TWA	5 ppm 23 mg/m3	GR OEL

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Date of last issue: 21.01.2019



exposure levels, the hazards of the product and the safe working limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid Colour : white Odour : mild

Odour Threshold : No data available

pH : 7,6 - 7,8 (20 °C)

Melting point/range / Freezing :

ooint

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 23 hPa

Relative vapour density : No data available

Density : ca. 1,23 g/cm3 (20 °C)

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Date of last issue: 21.01.2019

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 1,3 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

4-ethylmorpholine:

Acute oral toxicity : LD50 Oral (Rat): 1.780 mg/kg

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Date of last issue: 21.01.2019

Acute dermal toxicity : LD50 Dermal (Rabbit): 900 mg/kg

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Acute oral toxicity : LD50 Oral (Rat): 1.636 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,26 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

Acute inhalation toxicity : LC50: 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

2-methyl-2H-isothiazol-3-one (MIT):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Revision Date: 25.02.2021 Version 3.0

Date of last issue: 21.01.2019



Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Components:

4-ethylmorpholine:

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 580 mg/l

aquatic invertebrates Exposure time: 48 h

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Toxicity to fish : LC50 (Fish): 0,0027 mg/l

Exposure time: 96 h

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 10

toxicity)

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 3 mg/l

aquatic invertebrates Exposure time: 48 h

pyridine-2-thiol 1-oxide, sodium salt:

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 0,022 mg/l

aquatic invertebrates Exposure time: 48 h

M-Factor (Acute aquatic tox- : 100

icity)

2-methyl-2H-isothiazol-3-one (MIT):

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic :

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Revision Date: 25.02.2021 Version 3.0 Print Date 25.02.2021

Date of last issue: 21.01.2019

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

Sikalastic[®]-570 Top Coat

Revision Date: 25.02.2021 Version 3.0 Print Date 25.02.2021 Date of last issue: 21.01.2019

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

None of the components are listed

Number on list 3

: Not applicable

(=> 0.1 %).

Not applicable

Not applicable

Not applicable

Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 0,94 %

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,45 %







according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

Revision Date: 25.02.2021 Version 3.0 Print Date 25.02.2021

Date of last issue: 21.01.2019

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled.
H332 : Harmful if inhaled.
H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Flam. Liq. : Flammable liquids Skin Corr. : Skin corrosion Skin Irrit. : Skin sensitisation : Skin sensitisation

GR OEL : Greece. Exposure limit values
GR OEL / TWA : Long term exposure limit
GR OEL / STEL : Short term exposure limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

according to Regulation (EC) No. 1907/2006

Sikalastic®-570 Top Coat

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN