

Version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikalastic[®]-601 BC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealing system, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Category 3 H317: May cause an allergic skin reaction. H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 H412	May cause an allergic skin reaction. Harmful to aquatic life with long lasting ef- fects.
Precautionary statements	:	Prevention: P261	Avoid breathing dust/ fume/ gas/ mist/ va- pours/ spray.
		P273	Avoid release to the environment.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic® 601 BC

Sikalastic[®]-601 BC

Print Date 30.12.2021

Revision Date: 30.12.2021 Date of last issue: 25.08.2020 Version 4.0

P280	Wear protective gloves.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate Isophorondiisocyanate homopolymer 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Pentamethyl piperidylsebacate 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 10 - < 20
Contains:	203-603-9	STOT SE 3; H336	
2-methoxypropyl acetate <= 1 %	01-2119475791-29-		
	XXXX		
Diphenyl tolyl phosphate MCS	Not Assigned	Aquatic Acute 1;	>= 10 - < 20
	945-730-9	H400	
	01-2119511174-52-	Aquatic Chronic 3;	
	XXXX	H412	
bis[2-[2-(1-methylethyl)-3-	59719-67-4	Eye Irrit. 2; H319	>= 2,5 - < 5
oxazolidinyl]ethyl] hexane-1,2-	261-879-6	Skin Sens. 1B; H317	
diylbiscarbamate	01-2119983487-19-	Aquatic Chronic 2;	
-	XXXX	H411	
Isophorondiisocyanate homopol-	53880-05-0	Skin Sens. 1B; H317	< 1
ymer	933-047-9	STOT SE 3; H335	
Contains:	500-125-5	(Respiratory system)	
3-isocyanatomethyl-3,5,5-	01-2119488734-24-		
trimethylcyclohexyl isocyanate <=	XXXX		
0,49 %			

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikalastic[®]-601 BC

Revision Date: 30.12.2021 Date of last issue: 25.08.2020 Version 4.0



3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	>= 0,25 - < 0,5
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1	>= 0,1 - < 0,25
		M-Factor (Chronic aquatic toxicity): 1	
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21- XXXX	Repr. 2; H361d	< 1

Sikalastic[®]-601 BC

Revision Date: 30.12.2021 Date of last issue: 25.08.2020 Version 4.0



4,5-dichloro-2-octyl-2H-isothiazol- 3-one (DCOIT)	64359-81-5 264-843-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,025 - < 0,1
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti- mate	
For our longition of obbrouidtions of		Acute oral toxicity: 567 mg/kg Acute inhalation tox- icity (dust/mist): 0,16 mg/l	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.

Sikalastic[®]-601 BC



Revision Date: 30.12.2021 Date of last issue: 25.08.2020		Version 4.0	Print Date 30.12.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	s person.
4.2 Most important symptoms an	nd e	effects, both acute and delayed	
Symptoms	:	Allergic reactions See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction.	
4.3 Indication of any immediate r	no	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media		In case of fire, use water/water spray/water jet/caide/sand/foam/alcohol resistant foam/chemical p	
		extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	g apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas			
6.1 Personal precautions, protec	tiv	e equipment and emergency procedures	

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
---------------------------	---	---

Version 4.0

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up
- : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

e limits (see
ems or asth-
ease should ature is being
d in the ap-
ig chemical
ne and safety Ising do not d of workday.
•
entilated efully re- e in accord-



Version 4.0

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC	
	Further inform through the sl	nation: Identifies the kin, Indicative	possibility of signi	ficant uptake	
		TWA	50 ppm 275 mg/m3	2000/39/EC	
		TWA	50 ppm 275 mg/m3	GR OEL	
	chemical factor the likely cont of exposure to	Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity of exposure to workers which are absorbed through the skin at th direct contact with these.			
		STEL	100 ppm 550 mg/m3	GR OEL	
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,01 ppm 0,09 mg/m3	GR OEL	
	chemical factor the likely cont	nation: The notation brs of the table of pa ribution to of these of workers which are with these.	ragraph of 1 articl	e 3, implies the quantity	
		STEL	0,02 ppm 0,18 mg/m3	GR OEL	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis[2-[2-(1-methylethyl)- 3-oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	Workers	Inhalation	Long-term systemic effects	29,4 mg/m3
	Workers	Skin contact	Long-term systemic effects	16,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	6,25 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8,3 mg/kg
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis[2-[2-(1-methylethyl)-3-	Fresh water	0,0186 mg/l
oxazolidinyl]ethyl] hexane-1,2-		-



diylbiscarbamate		
	Marine water	0,00186 mg/l
	Fresh water sediment	0,709 mg/kg
	Marine sediment	0,0709 mg/kg
	Soil	1,131 mg/kg

8.2 Exposure controls

Personal protective equipment					
Eye protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.				
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.				
Environmental exposure controls					
General advice :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	red

Sikalastic[®]-601 BC



Revision Date: 30.12.2021 Da

Version 4.0

Date of last issue: 25.08.2020				
Odour	: hydrocarbon-like			
Boiling point/boiling range	: No data available			
Flash point	: 62 °C Method: closed cup			
Auto-ignition temperature	: ca. 315 °C			
рН	: Not applicable			
Viscosity Viscosity, kinematic	: > 7 mm2/s (40 °C)			
Solubility(ies)				
Water solubility	: insoluble			
Vapour pressure	: 3,1 hPa			
Density	: ca. 1,35 g/cm3 (20 °C)			
9.2 Other information				

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Print Date 30.12.2021

Revision Date: 30.12.2021 Date of last issue: 25.08.2020 Version 4.0

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity
Not classified based on available information.Components:2-methoxy-1-methylethyl acetate:
Acute oral toxicity:2.methoxy-1-methylethyl acetate:
LD50 Oral (Rat): > 5.000 mg/kgAcute dermal toxicity::LD50 Dermal (Rabbit): > 5.000 mg/kgDiphenyl tolyl phosphate MCS:
Acute oral toxicity::LD50 Oral (Rat): > 5.000 mg/kgAcute dermal toxicity::LD50 Oral (Rat): > 5.000 mg/kg:LD50 Oral (Rat): > 5.000 mg/kg

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
-----------------------	---	-------------------------------------

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): 4.814 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Acute oral toxicity	:	Acute toxicity estimate: 567 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
Acute inhalation toxicity	:	Acute toxicity estimate: 0,16 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Skin corrosion/irritation

Not classified based on available information.

Sikalastic[®]-601 BC

Revision Date: 30.12.2021 Date of last issue: 25.08.2020 Version 4.0



Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

icity)

Components:

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 87,1 mg/l Exposure time: 48 h		
Toxicity to algae/aquatic plants	:	EC50 (Scenedesmus capricornutum (fresh water algae)): 18,6 mg/l Exposure time: 72 h		
Pentamethyl piperidylsebacate:				
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h		
M-Factor (Acute aquatic tox-	:	1		

M-Factor (Chronic aquatic : 1

Version 4.0



toxicity)

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Toxicity to fish	: LC50 (Fish): 0,0027 mg/l Exposure time: 96 h

M-Factor (Acute aquatic tox- : 100 icity)

M-Factor (Chronic aquatic : 100 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

 Product
 : The generation of waste should be avoided or minimized wherever possible.

 Empty containers or liners may retain some product residues.

 This material and its container must be disposed of in a safe way.

 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

Sikalastic[®]-601 BC



Revision Date: 30.12.2021 Date of last issue: 25.08.2020		Version 4.0	Print Date 30.12.202
		local authority requirements. Avoid dispersal of spilled material and rur soil, waterways, drains and sewers.	noff and contact with
European Waste Catalogue	:	08 01 11* waste paint and varnish contai vents or other dangerous substances	ning organic sol-
Contaminated packaging	:	15 01 10* packaging containing residues by dangerous substances	of or contaminated

SECTION 14: Transport information

14.1 UN number					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.2 UN proper shipping name					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.3 Transport hazard class(es)					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.4 Packing group					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
IATA (Cargo)	:	Not regulated as a dangerous good			
IATA (Passenger)	:	Not regulated as a dangerous good			
14.5 Environmental hazards					
Not regulated as a dangerous good					
14.6 Special precautions for user					

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.



Version 4.0

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture						
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3			
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			Not applicable			
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).			
REACH - List of substances so (Annex XIV)	ubject to authorisation	:	Not applicable			
Regulation (EC) No 1005/2009 plete the ozone layer	Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer					
Regulation (EU) 2019/1021 or tants (recast)	:	Not applicable				
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			Not applicable			
		gulation, and/or				

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 18,11% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 18,15% w/w

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Sikalastic[®]-601 BC

Revision Date: 30.12.2021 Date of last issue: 25.08.2020 Version 4.0



SECTION 16: Other information

Full text of H-Statements		
H226		Elammable liquid and vanour
	:	Flammable liquid and vapour. Harmful if swallowed.
H302	·	
H314	÷	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361d	:	Suspected of damaging the unborn child.
H361f		Suspected of damaging fertility.
H400		Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
11412	•	Tarrifur to aquatic life with long lasting effects.
Full text of other abbreviatio	ons	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Resp. Sens.	÷	Respiratory sensitisation
Skin Corr.		Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
	:	
2000/39/EC	·	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
GR OEL	÷	Greece. Exposure limit values
2000/39/EC / TWA	÷	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GR OEL / TWA	:	Long term exposure limit
GR OEL / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		,

Sikalastic[®]-601 BC

Jika ®
Print Date 30.12.2021

Revision Date: 30.12.2021 Date of last issue: 25.08.2020		Version 4.0	Print Date 30.12.20		
		test animals)			
LC50	:	Median lethal concentration (concen air that kills 50% of the test animals period)			
MARPOL	:	International Convention for the Prev Ships, 1973 as modified by the Prote			
OEL	:	Occupational Exposure Limit			
PBT	:	Persistent, bioaccumulative and toxic			
PNEC	:	Predicted no effect concentration			
REACH	:	Regulation (EC) No 1907/2006 of the and of the Council of 18 December 2 istration, Evaluation, Authorisation a cals (REACH), establishing a Europe	2006 concerning the Reg- nd Restriction of Chemi-		
SVHC	:	Substances of Very High Concern			
vPvB	:	Very persistent and very bioaccumu	lative		
Further information					
Classification of the mixture:		Classificat	ion procedure:		
Skin Sens. 1	НЗ	17 Calculation	method		
Aquatic Chronic 3	H4	12 Calculation	method		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN