

# Sikaplan® WP 1100-15 HL

## Declaration of Performance No 11857081

1	<b>Unique identification code of the product-type:</b>	11857081
2	<b>Intended use/es:</b>	As fluid barriers in tunnels and underground structures — Geosynthetic barrier (polymeric, bituminous, clay)
3	<b>Manufacturer:</b>	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	<b>System/s of AVCP:</b>	System 2+ (As fluid barriers in tunnels and underground structures)
6a	<b>Harmonised standard:</b>	EN 13491:2004/A1:2006
	Notified body/ies:	1213

### Declaration of Performance

Sikaplan® WP 1100-15 HL

11857081

25/03/2024 1

1011

1 / 3

**7 Declared performance/s:**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Tensile strength	Longitudinal (MD)	17 N/mm <sup>2</sup> ± 2 N/mm <sup>2</sup>	System 2+
	Transversal (CMD)	16 N/mm <sup>2</sup> ± 2 N/mm <sup>2</sup>	
Resistance to static puncture	1.8 kN ± 0.2 kN	System 2+	EN 13491-2:2004/A1:2006
Durability	Oxidation	> 75 % retained tensile strength and elongation	
	Weathering	> 75 % retained tensile strength and elongation	
Dangerous substances	NPD	System 2+	
Liquid tightness	< 10 <sup>-6</sup> m <sup>3</sup> ·m <sup>-2</sup> ·d <sup>-1</sup>	System 2+	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski

Function: Corporate Product Certification Manager

At Warsaw on 2024-03-25

Name: Wiktor Karpala

Function: Data Processing Specialist CTD

At Warsaw on 2024-03-25

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

**Declaration of Performance**

Sikaplan® WP 1100-15 HL

11857081

25/03/2024 1

1011

2 / 3

BUILDING TRUST



CE

23

Sika Services AG, Zürich, Switzerland

11857081

Tensile strength	Longitudinal (MD)	17 N/mm <sup>2</sup> ± 2 N/mm <sup>2</sup>
	Transversal (CMD)	16 N/mm <sup>2</sup> ± 2 N/mm <sup>2</sup>
Resistance to static puncture	1.8 kN ± 0.2 kN	
Durability	Oxidation	> 75 % retained tensile strength and elongation
	Weathering	> 75 % retained tensile strength and elongation
Liquid tightness	< 10 <sup>-6</sup> m <sup>3</sup> ·m <sup>-2</sup> ·d <sup>-1</sup>	
EN 13491:2004/A1:2006		
1213		
As fluid barriers in tunnels and underground structures — Geosynthetic barrier (polymeric, bituminous, clay)		

<http://dop.sika.com>**ECOLOGY, HEALTH AND SAFETY (REACH)**

For information and advice on the safe handling, storage and use of this product, users shall refer to the most recent Product Data Sheet (PDS).

**LEGAL NOTES**

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

**Declaration of Performance**

Sikaplan® WP 1100-15 HL

11857081

25/03/2024 1

1011

**3 / 3**

BUILDING TRUST

