according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® Marine KG-202 N

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

Sikafloor® Marine KG-202 N



Revision Date 09.02.2020

Version 2.0

Print Date 09.02.2020

pours/ spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

Hazardous components which must be listed on the label:

- Cement (chromium reduced)
- · Cement, portland, chemicals

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration		
	EC-No.		(% w/w)		
	Registration number				
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 10 - < 20		
	266-043-4	Eye Dam. 1; H318			
		STOT SE 3; H335			
Cement, portland, chemicals	65997-15-1	Skin Irrit. 2; H315	>= 5 - < 10		
	266-043-4	Eye Dam. 1; H318			
		Skin Sens. 1; H317			
		STOT SE 3; H335			
Substances with a workplace exposure limit :					
Ashes (residues)	68131-74-8		>= 10 - < 20		
	931-257-5				
	268-627-4				
	01-2119484641-35-				
	XXXX				
calcium sulfate	7778-18-9		>= 2,5 - < 5		
	231-900-3				
	01-2119444918-26-				
	XXXX				

Sikafloor® Marine KG-202 N

Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N



Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Pick up and arrange disposal without creating dust. Methods for cleaning up

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should

Sikafloor® Marine KG-202 N



Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place. No decomposition if stored and applied

as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
Ashes (residues)	68131-74-8	TWA (respirable)	2 mg/m3	GR OEL
calcium sulfate	7778-18-9	TWA (inhalable)	10 mg/m3	GR OEL
		TWA (respirable)	5 mg/m3	GR OEL

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons

according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N



Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

and protective boots are additionaly recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : powder Colour : grey

Odour : characteristic
Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : ca. 0,72 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N

JIKa

Revision Date 09.02.2020

Version 2.0

: No data available

: No data available

Print Date 09.02.2020

Partition coefficient: n-

Auto-ignition temperature

octanol/water

ater

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N

Revision Date 09.02.2020 Version 2.0



Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N

Jika

Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 17 01 06* mixtures of, or separate fractions of concrete,

bricks, tiles and ceramics containing dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Sikafloor® Marine KG-202 N



Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered: Cement (chromium reduced)

None of the components are listed

(Number on list 47)

: Not applicable

(=> 0.1 %).

Not applicable

Not applicable

Not applicable

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0,01 %

no VOC duties

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N



Revision Date 09.02.2020 Version 2.0 Print Date 09.02.2020

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

GR OEL : Greece. Exposure limit values
GR OEL / TWA : Long term exposure limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikafloor® Marine KG-202 N

Sika ®

Revision Date 09.02.2020

Version 2.0

Print Date 09.02.2020