

BUILDING TRUST

Sika® Monoseal-101 H Grey

DECLARATION OF PERFORMANCE

No. 10875041

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	10875041
2	INTENDED USE/S	EN 1504-2:2004 Surface protection product – Coating Principle 2 (Moisture control) – Method 2.3 and Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-2:2004
-	Notified body/ies:	1128

Sika® Monoseal-101 H Grey 10875041 2017.12 , Revision 1

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Capillary absorption and permeability to water	w < 0.1 kg/m ² ·h ^{0.5}	
Adhesion strength by pull off test	≥ 1.0 MPa	EN 1504-2:2004
Permeability to water vapour	Class I, Sp < 5 m	
Dangerous substances	comply with 5.3	
Reaction to fire	NPD*	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Manolis Mavratzotis Function: R&D/QC Manager At Athens on 18 December 2017 Name: Spyros Hatzifotis Function: General Manager At Athens on 18 December 2017

End of information as required by Regulation (EU) No 305/2011

17		
Sika Hellas ABEE, A	thens - Greece	
DoP No. 10845041		
EN 1504-2	:2004	
Notified Boo	ly 1128	
Surface protection pr	oduct – Coating	
Capillary absorption and permeability to water	w < 0.1 kg/m ² ·h ^{0.5}	
Adhesion strength by pull off test	≥ 1.0 MPa	
Permeability to water vapour	Class I	
Dangerous substances	comply with 5.3	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.





Sika Hellas ABEE

15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

Sika® Monoseal-101 H Grey 10875041 2017.12 , Revision 1

