

BUILDING TRUST

Sikalastic[®]-831 HP DECLARATION OF PERFORMANCE No. 69885151

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	69885151	
2	INTENDED USE/S	EN 1504-2:2004 Surface protection product – Coating Principle 1 (Protection against ingress) – Method 1.3, Principle 5 (Increasing physical resistance) – Method 5.1, Principle 6 (Resistance to Chemicals) – Method 6.1, and Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008	
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr	
4	AUTHORISED REPRESENTATIVE:		
5	SYSTEM/S OF AVCP:	System 4	
6a	HARMONISED STANDARD:	EN 1504-2:2004	
	Notified body/ies:	-	

Declaration of Performance Sikalastic®-831 HP 69885151 2018.10 , Revision 1 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Capillary absorption and permeability to water	w < 0.1 kg/m ² ·h ^{0.5}	
Adhesion strength by pull off test	≥ 2.0 MPa	
Permeability to water vapour	Class II	
Permeability to CO ₂	S _D > 50 m	
Resistance to sever chemical attack	Class II	EN 1504-2:2004
Impact resistance	Class III	
Abrasion resistance	< 3000 mg	
Dangerous substances	NPD*	
Reaction to fire	NPD*	
*No performance determined		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Stamatis Antonakos Function: Target Market Manager Roofing & Waterproofing At Athens on 26 October 2018

Z. Venviake

Name : Spyros Hatzifotis Function: General Manager At Athens on 26 October 2018

18

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikalastic [®] -831 HP	EN 13813:2002	61834139

Declaration of Performance Sikalastic®-831 HP 69885151 2018.10 , Revision 1



BUILDING TRUST

CE

18		
Sika Hellas ABEE, At	thens - Greece	
DoP No. 698	85151	
EN 1504-2	:2004	
Surface protection pr	oduct – coating	
Capillary absorption and permeability to water	w < 0.1 kg/m ² ·h ^{0.5}	
Adhesion strength by pull off test	≥ 2.0 MPa	
Permeability to water vapour	Class II	
Permeability to CO ₂	S _D > 50 m	
Resistance to sever chemical attack	Class II	
Impact resistance	Class III	
Abrasion resistance	< 3000 mg	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance Sikalastic®-831 HP 69885151 2018.10 , Revision 1





Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance Sikalastic®-831 HP 69885151 2018.10 , Revision 1



BUILDING TRUST