

Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-262 AS N /262 AS N Thixo Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the un- born child.
Specific target organ toxicity - repeated	H373: May cause damage to organs through pro-
exposure, Category 2	longed or repeated exposure.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.
2.2 Label elements	
Labelling (REGULATION (EC) No 1272/20	008)
Hazard pictograms :	



Print Date 17.01.2024

Revision Date: 17.01.2024 Date of last issue: 04.02.2022		V	ersion 6.0	Print Date 17.0
		H314 H317 H361	Causes severe skin burns and e May cause an allergic skin reac Suspected of damaging fertility child.	tion.
		H373	May cause damage to organs the longed or repeated exposure.	rough pro-
		H412	Harmful to aquatic life with long fects.	lasting ef-
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory trac	t.
Precautionary statements	:	Prevention:		
		P201 P260 P280	Obtain special instructions before Do not breathe mist or vapours. Wear protective gloves/ protection eye protection/ face protection.	
		Response:		
		P303 + P361 + I	P353 IF ON SKIN (or hair): Tak ately all contaminated clothing. with water.	
		P304 + P340 + I	P310 IF INHALED: Remove pe air and keep comfortable for bre mediately call a POISON CENT	eathing. Im-
		P305 + P351 + I		e cautiously Remove con- to do. Con-

Hazardous components which must be listed on the label:

Adduct IXA-P (epoxy amine adduct, polymer) 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) 2-piperazin-1-ylethylamine Cashew, nutshell liq. 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor®-262 AS N /262 AS N Thixo Part B

Print Date 17.01.2024

Revision Date: 17.01.2024 Date of last issue: 04.02.2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	>= 40 - < 60
212580-83-1 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 10 - < 20
2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity esti- mate Acute oral toxicity:	>= 10 - < 20
	EC-No. Registration number 100-51-6 202-859-9 01-2119492630-38- XXXX 212580-83-1 Not Assigned 2855-13-2 220-666-8 01-2119514687-32-	EC-No. Registration numberAcute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319100-51-6 202-859-9 01-2119492630-38- XXXXAcute Tox. 4; H302 Acute Tox. 4; H319Acute oral toxicity estimateAcute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l212580-83-1 Not AssignedAcute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 3; H4122855-13-2 220-666-8 01-2119514687-32- XXXXAcute Tox. 4; H302 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 %

Revision Date: 17.01.2024 Date of last issue: 04.02.2022

Version 6.0



or last issue. 04.02.2022			
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071	>= 5 - < 10
		Acute toxicity esti- mate	
		Acute oral toxicity: 930 mg/kg Acute inhalation tox- icity (dust/mist): 1,34 mg/l	
2-piperazin-1-ylethylamine Contains: 2-(2-aminoethylamino)ethanol <= 0,29 %	140-31-8 205-411-0 01-2119471486-30- XXXX	Repr. 2; H361 STOT RE 1; H372 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 5 - < 10
		Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg Acute dermal toxicity:	
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	866 mg/kg Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 5 - < 10
Cashew, nutshell liq.	8007-24-7 700-991-6 01-2119502450-57- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 3 - < 5
		Acute toxicity esti- mate Acute oral toxicity: 500 mg/kg Acute dermal toxicity: 2.000 mg/kg	

Sikafloor®-262 AS N /262 AS N Thixo Part B



Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0

2-Propenenitrile, reaction prod- ucts with 2,2,4(or 2,4,4)-trimethyl- 1,6-hexanediamine	90530-20-4 292-059-6 01-2120773937-35- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 1 - < 2,5
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	25513-64-8 247-063-2 01-2119560598-25- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 0,1 - < 0,5
		Acute toxicity esti- mate	
		Acute oral toxicity: 910 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Genera	Il advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
lf inhale	ed	:	Move to fresh air. Consult a physician after significant exposure.
In case	of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case	of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swalld	owed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most im	portant symptoms and	l e	ffects, both acute and delayed
Sympto	oms	:	Gastrointestinal discomfort Allergic reactions Dermatitis



Revision Date: 17.01.2024 Date of last issue: 04.02.2022		Version 6.0	Print Date 17.01.2
		See Section 11 for more detailed information and symptoms.	ation on health effects
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects	
		Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility or the un May cause damage to organs through pr exposure. Corrosive to the respiratory tract. Causes severe burns.	
4.3 Indication of any immediate r	ne	dical attention and special treatment ne	eded
Treatment	:	Treat symptomatically.	
5.1 Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/wa ide/sand/foam/alcohol resistant foam/che extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
		No hazardous combustion products are	known
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained b	preathing apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	ie i	neasures	
6.1 Personal precautions, protec	tiv	e equipment and emergency procedure	S
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitar If the product contaminates rivers and la	

respective authorities.

Sikafloor®-262 AS N /262 AS N Thixo Part B



Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, ir	nclu	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	

Sikafloor®-262 AS N /262 AS N Thixo Part B

Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0



Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipme	t i i i i i i i i i i i i i i i i i i i	
Eye/face protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.	
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.	
Respiratory protection	No special measures required.	
Environmental exposure con	ols	
General advice	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour	:	liquid yellow amine-like		
Melting point/range / Freezing point	:	No data available		
Boiling point/boiling range	:	No data available		
Flammability (solid, gas)	:	No data available		
Upper/lower flammability or explosive limits				

Upper explosion limit / Up-	:	No data available
per flammability limit		

Print Date 17.01.2024

Revision Date: 17.01.2024
Date of last issue: 04.02.2022

Version 6.0

Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	ca. 11 (20 °C) Concentration: 50 %
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,07 hPa
Density	:	ca. 1,03 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed.		
Components:		
benzyl alcohol:		
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
		Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method
3-aminomethyl-3,5,5-trimet	hylc	cyclohexylamine:
Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg
m-phenylenebis(methylam	ine):	:
Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg
		Acute toxicity estimate: 930 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l
CP = 10000002704		10 /

Sikafloor®-262 AS N /262 AS N Thixo Part B

Print Date 17.01.2024

Revision Date: 17.01.2024
Date of last issue: 04.02.2022

Version 6.0

		Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
		Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	LD50 Dermal (Rat): > 3.100 mg/kg
2-piperazin-1-ylethylamine:		
Acute oral toxicity	:	LD50 Oral (Rat): > 1.999 mg/kg
		Acute toxicity estimate: 1.999 mg/kg Method: Calculation method
Acute dermal toxicity	:	LD50 Dermal (Rabbit): ca. 866 mg/kg
		Acute toxicity estimate: 866 mg/kg Method: Calculation method
2,4,6-tris(dimethylaminome	thv	l)phenol:
Acute oral toxicity	-	LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008
Cashew, nutshell liq.:		
Acute oral toxicity	:	LD50 Oral (Rat): 500 mg/kg
		Acute toxicity estimate: 500 mg/kg Method: Calculation method
Acute dermal toxicity	:	LD50 Dermal (Rat): 2.000 mg/kg
		Acute toxicity estimate: 2.000 mg/kg Method: Calculation method
2,2,4(or 2,4,4)-trimethylhexa	ane	-1,6-diamine:
Acute oral toxicity	:	LD50 Oral (Rat): 910 mg/kg
		Acute toxicity estimate: 910 mg/kg Method: Calculation method
Skin corrosion/irritation		
Causes severe burns.		
Components:		

2,4,6-tris(dimethylaminomethyl)phenol:

Print Date 17.01.2024

Revision Date: 17.01.2024
Date of last issue: 04.02.2022

Version 6.0

Species Assessment Method	Rabbit Corrosive OECD Test Guideline 404
Assessment Remarks	irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	-	Rabbit Causes serious eye damage.
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

1

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation



Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1	Toxicity
------	----------

Components:					
benzyl alcohol: Toxicity to fish :	LC50 (Fish): > 100 mg/l Exposure time: 96 h				
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h				
3-aminomethyl-3,5,5-trimethylo	cyclohexylamine:				
Toxicity to algae/aquatic : plants					
	NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h				
m-phenylenebis(methylamine)					
Toxicity to fish :	LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h				
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h				
2-piperazin-1-ylethylamine: Toxicity to fish :	LC50 (Fish): > 100 mg/l Exposure time: 96 h				
2,4,6-tris(dimethylaminomethyl)phenol:					
Toxicity to algae/aquatic : plants	EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l Exposure time: 72 h				
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:					
Toxicity to algae/aquatic : plants					
Toxicity to fish (Chronic tox- : icity)	LC50: 174 mg/l Exposure time: 48 h				

Print Date 17.01.2024

Revision Date: 17.01.2024 Date of last issue: 04.02.2022

Version 6.0

Species: Leuciscus idus (Golden orfe)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:		
Assessment :		The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor- : mation	-	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods Product : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with



Revision Date: 17.01.2024 Date of last issue: 04.02.2022		Version 6.0	Print Date 17.01.202	
		soil, waterways, drains and sewers.		
European Waste Catalogue	:	08 01 11* waste paint and varnish contain vents or other dangerous substances	ing organic sol-	
Contaminated packaging	:	15 01 10* packaging containing residues o by dangerous substances	f or contaminated	

SECTION 14: Transport information

14.1 UN number or ID number					
ADR	:	UN 1760			
IMDG	:	UN 1760			
ΙΑΤΑ	:	UN 1760			
14.2 UN proper shipping name					
ADR	:	CORROSIVE LIQUID (3-aminomethyl-3,5,5- phenylenebis(methyla	-trimethylcyclohexylamine, m-		
IMDG	:	CORROSIVE LIQUID (3-aminomethyl-3,5,5- phenylenebis(methyla	-trimethylcyclohexylamine, m-		
ΙΑΤΑ	:	Corrosive liquid, n.o.s (3-aminomethyl-3,5,5- phenylenebis(methyla	-trimethylcyclohexylamine, m-		
14.3 Transport hazard class(es)					
		Class	Subsidiary risks		
ADR	:	8			
IMDG	:	8			
ΙΑΤΑ	:	8			
14.4 Packing group					
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: : : : : : : : : : : : : : : : : : : :	II C9 80 8 (E)			
IMDG Packing group Labels EmS Code Remarks	:	ll 8 F-A, S-B Alkalis			

Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0



IATA (Cargo)

Packing instruction (cargo	:	855
aircraft)		
Packing instruction (LQ)	:	Y840
Packing group	:	II
Labels	:	Corrosive
IATA (Passenger)		
Packing instruction (passen-	:	851
ger aircraft)		
Packing instruction (LQ)	:	Y840
Packing group	:	11
Labels	:	Corrosive

14.5 Environmental hazards

ADR Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

: Not applicable

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

Sikafloor[®]-262 AS N /262 AS N Thixo Part B



Revision Date: 17.01.2024 Date of last issue: 04.02.2022	Version 6	6.0		Print Date 17.01.2024
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the component (=> 0.1 %).	ts are listed
REACH - List of substances subj (Annex XIV)	ect to authorisation	:	Not applicable	
Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de-	:	Not applicable	
Regulation (EU) 2019/1021 on pettants (recast)	ersistent organic pollu-	:	Not applicable	
Regulation (EC) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable				
Volatile organic compounds :	(VOCV)		or volatile organic compo ds (VOC) content: 42,6%	
			4 November 2010 on ind ution prevention and con	

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Volatile organic compounds (VOC) content: 42,6% w/w

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H361	: Suspected of damaging fertility or the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0



Full text of other abbreviations

Acute Tox. Aquatic Chronic	:	Acute toxicity Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Repr. Skin Corr.		Reproductive toxicity Skin corrosion
Skin Con. Skin Irrit.		Skin conosion Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
ADR	:	European Agreement concerning the International Carriage of
	•	Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
OEL		Ships, 1973 as modified by the Protocol of 1978
PBT	:	Occupational Exposure Limit Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH		Regulation (EC) No 1907/2006 of the European Parliament
	•	and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the n	Classification procedure:	
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method



Revision Date: 17.01.2024 Date of last issue: 04.02.2022 Version 6.0

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN