

SikaScreed®-1 (GR)

DECLARATION OF PERFORMANCE

No. 65770592

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	65770592
2	INTENDED USE/S:	EN13813:2002 Cementitious floor screed material, CT-C30-F6
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN13813:2002

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	Harmonised Technical Specification	
Reaction to fire	Class A1 _{fl}	EN13813:2002	
Release of corrosive substances	СТ		
Compressive strength	C30		
Flexural strength	F6		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Angeliki Zacharopoulou Function: QEHS Manager At Atheas on 22 February 2021 Name: Kostas Mourikis

Function: Target Market Flooring Manager

At Athens on 22 February 2021

End of information as required by Regulation (EU) No 305/2011



21

Sika Hellas ABEE, Athens - Greece

65770592

EN13813:2002

Cementitious floor screed material, CT-C30-F6

Reaction to fire	Class A1 _{fl}	
Release of corrosive substances	СТ	
Compressive strength	C30	
Flexural strength	F6	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

SikaScreed®-1 (GR) 65770592 2021.02, Version 1 1200

