

Sika MonoTop®-722 Mur E

DECLARATION OF PERFORMANCE No. 54364182

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	54364182
2	INTENDED USE/S:	EN 998-1:2016 General purpose rendering / plastering mortar for external and internal use (GP)
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4 System 3 (for uses subject to reaction to fire regulations)
6a	HARMONISED STANDARD:	EN 998-1:2016

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Water absorption	$W_c 2$	EN 998-1:2016
Water vapour permeability	$\mu \leq 70$	
Adhesion	$\geq 0.8 \text{ MPa} - \text{FP: A}$	
Thermal conductivity	$(\lambda_{10, \text{dry, mat}}) 0.8 \text{ W/m}\cdot\text{K}$ (tab. Mean value, P=50%)	
Reaction to fire	A1/A1 _{fl}	
Durability	NPD*	

*NPD – No performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Name: Nikos Anagnostopoulos
Function: Target Market Manager
Refurbishment
At Athens on 25 October 2020

Name: Alexandros Melissourgos
Function: Technical Manager

At Athens on 25 October 2020



.....



.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sika MonoTop®-722 Mur E	EN 1504-3:2005	98572474
Sika MonoTop®-722 Mur E	EN 998-2:2016	14109313

Declaration of Performance

Sika MonoTop®-722 Mur E
54364182
2020.10, Version 1
1200



18

Sika Hellas ABEE, Athens - Greece

DoP No. 54364182

EN 998-1:2016

General purpose rendering / plastering mortar
for external and internal use (GP)

Water absorption	$W_c 2$
Water vapour permeability	$\mu \leq 70$
Adhesion	$\geq 0.8 \text{ MPa} - \text{FP: A}$
Thermal conductivity	$(\lambda_{10, \text{dry, mat}}) 0.8 \text{ W/m}\cdot\text{K}$ (tab. Mean value, P=50%)
Reaction to fire	A1/A1 _{fl}

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika MonoTop®-722 Mur E
54364182
2020.10, Version 1
1200



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
Sika MonoTop®-722 Mur E
54364182
2020.10, Version 1
1200