

Sikaflex[®]-112 Crystal Clear

DECLARATION OF PERFORMANCE No. 51448837

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	51448837
2	INTENDED USE/S	EN 15651-1:2012 Sealants for exterior and interior application F EXT-INT
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONIZED STANDARD:	EN 15651-1:2012
	Notified body/ies:	2538, 1508

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of dangerous substances	NPD		
Water tightness and air tightness			
Resistance to flow	≤3 mm	System 3	
Loss of volume	≤ 10 %	System 3	
Tensile properties (i.e. elongation) at maintained extension after water immersion (Elastic)	NF at 60% elongation	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Stamatios Kollias
Function: TMM Sealing & Bonding/Industry
At Athens on 30 November 2018

Name: Spyros Hatzifotis
Function: Managing Director
At Athens on 30 November 2018



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikaflex®-112 Crystal Clear
51448837
2018.09 , ver. 1
1213



18

Sika Services AG, Zurich, Switzerland

DoP No. 51448837

EN 15651-1:2012

Notified Body 2538, 1508

Sealants for exterior and interior application F EXT-INT

Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤3 mm
Loss of volume	≤ 10 %
Tensile properties (i.e. elongation) at maintained extension after water immersion (Elastic)	NF at 60% elongation
Durability	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikaflex®-112 Crystal Clear

51448837

2018.09 , ver. 1

1213

3/4

BUILDING TRUST





Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
Sikaflex®-112 Crystal Clear
51448837
2018.09 , ver. 1
1213

4/4

BUILDING TRUST

