

## PRODUCT DATA SHEET

# Sikagard<sup>®</sup>-200 Wood Stain Colour

High quality impregnating wood varnish

### DESCRIPTION

High performance, silicon based, water repellent, impregnation wood varnish. It contains special additives which prevent mold growth.

### USES

Suitable for exterior and interior use. It can be used on wooden houses, wooden roofs, beams, wooden windows, stairs, furniture, etc

### FEATURES

- High impregnating properties
- Allows the breathing of the wood
- Very good resistance against weather changes
- Easy to apply
- Protects wooden surfaces from peeling-off
- Prevents mold growth
- No thinning needed

### PRODUCT INFORMATION

Packaging	Metallic pail	0.75 lt and 2.5 lt
Shelf life	In undamaged original sealed packaging: 36 months from production date	
Storage conditions	Store the product in the original sealed packaging in dry conditions between 5 – 25°C. PROTECT FROM FROST	
Colour	Matt finish Transparent and twelve ready - colored shades (oak, light oak, chestnut, walnut, oregon, pine, mahogany, teak, rose, wild cherry, blue and green).	
Density	0,83 ± 0,02 gr/cm <sup>3</sup>	(ISO 2811)

### TECHNICAL INFORMATION

Curing conditions	Touch dry	6 – 8 hours
	Recoating	24 hours
Touch dry and recoating time might be elongated according to temperature and humidity conditions.		

### APPLICATION INFORMATION

Consumption	6 – 8 m <sup>2</sup> /lt, depending on the kind and the absorptivity of the surface ~150 gr/m <sup>2</sup>	
Ambient air temperature	Min.	+10 °C
	Max.	+35 °C

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

Information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS), containing physical, ecological, toxicological and other safety related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

Substrate must be clean, dry and free of all contaminants, such as dirt, dust, grease, coatings, wax etc. by rubbing with a sandpaper.

### APPLICATION

Shake the container well before use.

Apply the product with roller or brush in the same direction of the natural grains of the wood.

To obtain uniform result, apply 2 coats of Sikagard®-200 Wood Stain Colour for interior application or 2 to 3 coats for exterior application.

In external areas, apply Sikagard®-105 Wood Treatment prior to the application of Sikagard®-200 Wood Stain Colour, for protection against fungi and insects.

#### Please Note

The product is not suitable for application on non-absorbent wooden surfaces.

### CLEANING OF EQUIPMENT

Clean all tools and application equipment with water and soap immediately after use. Hardened and/or cured material can only be removed mechanically.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### Sika Hellas ABEE

15, Protomagias Str.  
GR 145 68, Kryoneri, Attica  
Tel.: +30 210 81 60 600  
E-mail: info@gr.sika.com  
www.sika.gr



Product Data Sheet  
Sikagard®-200 Wood Stain Colour  
June 2024, Version 01.01  
020612020000000001

Sikagard-200WoodStainColour-en-GR-(06-2024)-1-1.pdf