

Sikafloor®-330

DECLARATION OF PERFORMANCE

No. 32218860

6a

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	32218860
2	INTENDED USE/S	EN 13813:2002 Synthetic resin screed for internal uses
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4 (for internal uses)

EN 13813:2002

Notified body/ies: 0620

HARMONIZED STANDARD:

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire:	E _{fl}	System 4	
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	_
Wear resistance:	≤ AR1	System 4	
Bond strength:	≥ B1,5	System 4	
Impact resistance:	≥ IR4	System 4	EN 13813:2002
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	_
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	_

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis Function: TMM Flooring At Athens on 23 March 2020 Name: Alexandros Melissourgos Function: Technical Manager At Athens on 23 March 2020

.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product name	Harmonized standard	DoP number
Sikafloor®-330	EN 1504-2:2004	90381567

Declaration of Performance

Sikafloor®-330 32218860 2018.09, ver. 1 1041



	CE
	09
1	EN 13813:2002
Do	DP No. 32218860
Sika Servic	ces AG, Zürich, Switzerland
No	otified Body 0620
Synthetic res	sin screed for internal uses
Synthetic res Reaction to fire:	sin s creed for internal uses Ef
Reaction to fire:	En
Reaction to fire: Release of corrosive substances:	E _{fl} SR
Reaction to fire: Release of corrosive substances: Wear resistance:	E _{fl} SR ≤ AR1

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

15 Protomagias Str. 14568 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

Sikafloor®-330 32218860 2018.09, ver. 1 1041

