

Sika MonoTop®-722 Mur E

DECLARATION OF PERFORMANCE

No. 14109313

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	14109313
2	INTENDED USE/S:	EN 998-2:2016
		Designed general purpose masonry mortar for external
		use in elements subject to structural requirements
3	MANUFACTURER:	Sika Hellas ABEE
		15 Protomagias Str.
		GR 145 68 Kryoneri
		Athens - Greece
		www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
		System 3 (for uses subject to reaction to fire)
6a	HARMONISED STANDARD:	EN 998-2:2016
	Notified body/ies:	1128

Sika MonoTop®-722 Mur E 14109313 2020.10 , Version 1 1200

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Compressive strength	Class M20	
Shear bond strength	0.15 N/mm² (tabulated value)	-
Contents of chlorides	< 0.1 %	
Water absorption	$\leq 0.2 [kg/(m^2 \cdot min^{0.5})]$	
Water vapour permeability	μ 15/35	EN 998-2:2016
Thermal conductivity	(λ _{10,dry,mat}) 0.8 W/m·K (tab. mean value, P=50%)	LN 998-2.2010
Durability	NPD*	
Dangerous substances	according to 5.4.9	
Reaction to fire	A1/A1 _{fl}	

APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos Function: Target Market Manager

*NPD - No performance determined

Refurbishment

8

At Athens on 25 October 2020

Name: Alexandros Melissourgos Function: Technical Manager

At Athens on 25 October 2020

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sika MonoTop®-722 Mur E	EN 1504-3:2005	98572474
Sika MonoTop®-722 Mur E	EN 998-1:2016	54364182





15

Sika Hellas	ADEE	1+hone	Crosso
Sika Helias	ABEE.	Aunens	- Greece

DoP No. 14109313

EN 998-2:2016

Notified Body 1128

Designed general purpose masonry mortar for external use in elements subject to structural requirements

Compressive Strength	Class M20	
Shear bond strength	0.15 N/mm² (tabulated value)	
Contents of chlorides	< 0.1 %	
Water absorption	≤ 0.2 [kg/(m²·min ^{0.5})]	
Water vapour permeability	μ 15/35	
Thermal conductivity	(λ _{10,dry,mat}) 0.8 W/m·K (tab. mean value, P=50%)	
Dangerous substances	according to 5.4.9	
Reaction to fire	A1/A1 _{fl}	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.





Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece

www.sika.gr

Declaration of Performance

Sika MonoTop®-722 Mur E 14109313 2020.10 , Version 1 1200

