

Sikaflex® PRO-3 SL

DECLARATION OF PERFORMANCE

No. 60981430

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	60981430
2	INTENDED USE/S	EN 14188-2:2004 Cold applied joint sealants intended for use on roads, airfields, bridge decks and parking decks
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 14188-2:2004
	Notified body/ies:	1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Bonding strength	NPD	System 4	
Cohesion	NPD	System 4	
Watertightness	NPD	System 4	
Resistance to deformation:			
Loss of volume	≤5 %	System 4	
Elastic recovery	≥ 70 %	System 4	EN 14188- 2:2004
Durability of watertightness against chemicals	≤ 50 %	System 4	
Durability of cohesion against liquid chemicals	Pass	System 4	
Durability of all mandated characteristics against ageing	Change of tensile modulus at 100 % extension ≤ ±20 %	System 4	
Resistance to flame	NPD	System 4	<u> </u>

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Stamatios Kollias Function: TMM Sealing &

Bonding/Industry

At Athens on 26 February 2019

Name: Spyros Hatzifotis Function: Managing Director

At Athens on 26 February 2019

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikaflex® PRO-3 SL	EN 15651-4:2012	24868181





18

Sika Services AG, Zurich, Switzerland

DoP No. 60981430

EN 14188-2:2004

Notified Body 1213

Cold applied joint sealants intended for use on roads, airfields, bridge decks and parking decks

Resistance to deformation:

Loss of volume ≤5%Elastic recovery ≥70%Durability of watertightness against chemicals ≤50%Durability of cohesion against liquid chemicals Pass

Durability of all mandated characteristics against Change of tensile modulus at ageing 100 % extension ≤ ±20 %

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

Protomagias 15 14568 Kryoneri Attica - Greece www.sika.gr

Declaration of Performance

Sikaflex® PRO-3 SL 60981430 2018.12 , ver. 2 1009

