according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Date of last issue: 25.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-264 N Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects.

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

Revision Date: 21.04.2023

P261	Avoid breathing mist or vapours.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane bis-[4-(2,3-epoxypropoxy)phenyl]methane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 25 - < 40
bis-[4-(2,3- epoxypropoxy)phenyl]methane	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 2,5 - < 5
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.620 mg/kg Acute inhalation toxicity (dust/mist): 4,178 mg/l	>= 1 - < 2,5
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5
Substances with a workplace expo Titanium dioxide (> 10 µm)	osure limit : 13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 5 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

5.2 Special hazards arising from the substance or mixture

fighting

Specific hazards during fire-: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Personal precautions

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022



Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable)	10 mg/m3	GR OEL
		TWA (respirable)	5 mg/m3	GR OEL

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Date of last issue: 25.05.2022



Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Appearance : viscous
Colour : various
Odour : very faint

Melting point/range / Freezing :

noint

No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- :

per flammability limit

: No data available

Lower explosion limit / Lower flammability limit

: No data available

Flash point : ca. 86 °C

Method: closed cup

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Auto-ignition temperature : ca. 436 °C

Decomposition temperature : No data available

pH : ca. 6,5 (20 °C)

Concentration: 100 %

Viscosity

Viscosity, dynamic : ca. 3.600 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0,01 hPa

0,01 hPa

Density : ca. 1,6 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity LD50 Dermal (Rabbit): > 5.000 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute toxicity estimate: 1.620 mg/kg

Method: Calculation method

: LC50 (Rat): > 4,178 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:

Acute oral toxicity LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.466 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 6.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

octamethylcyclotetrasiloxane [D4]:

20-year global warming potential: 2,66 100-year global warming potential: 0,739 500-year global warming potential: 0,211

Atmospheric lifetime: 0,027 yr Radiative efficiency: 0,12 Wm2ppb

Further information: Miscellaneous compounds

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082 IMDG : UN 3082 IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Date of last issue: 25.05.2022

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

Remarks : Transport in accordance with special provision 375

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

Remarks : Transport in accordance with 2.10.2.7 of the IMDG-Code

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

Remarks : Transport in accordance with special regulation A 197

IATA (Passenger)

Packing instruction (passen: 964

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

All substances contained in our Products are **REACH Information:**

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

ENVIRONMENTAL HAZARDS

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 2,88% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,88% w/w

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Revision Date: 21.04.2023 Version 4.0 Print Date 21.04.2023

Date of last issue: 25.05.2022

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GR OEL : Greece. Exposure limit values
GR OEL / TWA : Long term exposure limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method

according to Regulation (EC) No. 1907/2006

Sikafloor®-264 N Part A

Sika®

Revision Date: 21.04.2023	Version 4.0	Print Date 21.04.2023
Date of last issue: 25.05.2022		

Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN