

Sikafloor® Level-30

DECLARATION OF PERFORMANCE No. 36581792

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	36581792
2	INTENDED USE/S	EN 1504-3:2005 Structural and nonstructural repair products for concrete intended for use in building and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ and System 3 for Reaction to Fire
6a	HARMONIZED STANDARD:	EN 1504-3:2005
	Notified body/ies:	1139

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP System	Harmonized Technical Specification
Compressive strength	Class R3	System 2+	EN 1504-3:2005
Chloride Ion Content	≤ 0.05%	System 2+	
Adhesive bond	≥ 1,5 MPa	System 2+	
Restrained Shrinkage / Expansion	NPD	System 2+	
Carbonation Resistance	NPD	System 2+	
Elastic Modules	≥ 15 GPa	System 2+	
Thermal Compatibility freeze-thaw	≥ 1.5 MPa	System 2+	
coefficient of thermal expansion	16.3 μm/m °C	System 2+	
Skid resistance	NPD	System 2+	
Capillary absorption	≤ 0.5 kg.m ⁻² .h ^{0.5}	System 2+	
Reaction to Fire	A1 _{fl}	System 3	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis
Function: TMM Flooring
At Athens on 13 April 2020



Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 13 April 2020



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikafloor® Level-30	EN 13813:2002	90432755

Declaration of Performance

Sikafloor® Level-30

36581792
2020.4, ver. 3
1029



13

DoP No. 36581792

Sika Services AG, Zurich, Switzerland

EN 1504-3:2005

Notified Body 1139

Structural and nonstructural repair products for concrete intended for use in building and civil engineering works

Compressive strength	Class R3
Chloride Ion Content	$\leq 0.05\%$
Adhesive bond	$\geq 1,5 \text{ MPa}$
Elastic Modules	$\geq 15 \text{ GPa}$
Thermal Compatibility freeze-thaw	$\geq 1,5 \text{ MPa}$
coefficient of thermal expansion	$16.3 \mu\text{m}/\text{m}^\circ\text{C}$
Capillary absorption	$\leq 0.5 \text{ kg}\cdot\text{m}^{-2}\cdot\text{h}^{0.5}$
Reaction to Fire	A1fl

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikafloor® Level-30

36581792
2020.4, ver. 3
1029

3/4

BUILDING TRUST





Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
Sikafloor® Level-30

36581792
2020.4 , ver. 3
1029

4/4

BUILDING TRUST

