

SikaRep®-200 Multi

DECLARATION OF PERFORMANCE

No. 74946376

| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | 74946376 |
|----|---|---|
| 2 | INTENDED USE/S: | EN 998-2:2016 Designed General purpose mortar for use in masonry walls, columns and partitions |
| 3 | MANUFACTURER: | Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | System 2+ |
| 6a | HARMONISED STANDARD: | EN 998-2:2016 |
| | Notified body/ies: | 1128 |

SikaRep®-200 Multi 74946376 2021.10 , Version 1

7 DECLARED PERFORMANCE/S

| Essential Characteristics | Performance | AVCP | Harmonised Technical Specification | |
|---------------------------|--|-----------|--|--|
| Compressive strength | Class M20 | System 2+ | | |
| Shear bond strength | 0.15 N/mm² (tabulated value) | System 2+ | | |
| Content of chlorides | < 0.1 % | System 2+ | | |
| Water absorption | $\leq 0.2 [kg/(m^2 \cdot min^{0.5})]$ | System 2+ | | |
| Water vapour permeability | μ 15/35 | System 2+ | —— EN 998-2:2016 | |
| Thermal conductivity | (λ _{10,dry,mat}) 0.8 W/m·K (tab. mean value, P=50%) | System 2+ | —— LN 558-2.2010 | |
| Durability | NPD* | System 2+ | | |
| Dangerous substances | according to 5.4.9 | System 2+ | | |
| Reaction to fire | Class A1 | System 2+ | | |

^{*}NPD - No performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos Function: Target Market Manager

Refurbishment

At Athens on 27 October 2021

Name: Angeliki Zacharopoulou Function: QEHS Manager

At Athens on 27 October 2021

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

| Product Name | Harmonised technical specification | DoP Number |
|--------------------|------------------------------------|------------|
| SikaRep®-200 Multi | EN 1504-3:2005 | 47055563 |
| SikaRep®-200 Multi | EN 998-1:2016 | 80744666 |





| 21 | | | | | |
|----------------------------|--|--|--|--|--|
| Sika | Hellas ABEE, Athens - Greece | | | | |
| | DoP No. 74946376 | | | | |
| | EN 998-2:2016 | | | | |
| | Notified Body 1128 | | | | |
| Designed General purpose m | ortar for use in masonry walls, columns and partitions | | | | |
| Compressive Strength | Class M20 | | | | |
| Shear bond strength | 0.15 N/mm² (tabulated value) | | | | |
| Content of chlorides | < 0.1 % | | | | |
| Water absorption | $\leq 0.2 \text{ [kg/(m}^2 \cdot \text{min}^{0.5})]$ | | | | |
| Water vapour permeability | μ 15/35 | | | | |
| Thermal conductivity | (λ _{10,dry,mat}) 0.8 W/m·K | | | | |
| Thermal conductivity | (tab. mean value, P=50%) | | | | |
| Danasanawa awhatanasa | according to 5.4.9 | | | | |
| Dangerous substances | | | | | |

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in the commendation of the commendationgood faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

SikaRep®-200 Multi 74946376 2021.10 , Version 1

