

SikaWall®-1045 Pro

DECLARATION OF PERFORMANCE

No. 37482513

**1 UNIQUE IDENTIFICATION
CODE OF THE PRODUCT-
TYPE:**

37482513

2 INTENDED USE/S:

EN998-1:2016

General purpose rendering / plastering
mortar for external and internal use (GP)

3 MANUFACTURER:

Sika Romania SRL
Str. Izvor 92-96
Cladirea Forum III
Bucuresti Sect. 5
www.sika.ro

**4 AUTHORISED
REPRESENTATIVE:**

5 SYSTEM/S OF AVCP:

System 4

6a HARMONISED STANDARD: EN998-1:2016

Notified body/ies:

-

Declaration of Performance

SikaWall®-1045 Elite Grey

37482513

2025.08, Version 1

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1	System 4	EN998-1:2016
Water absorption	Wc 2		
Water vapour permeability	$\mu \leq 15$		
Adhesion	$\geq 0.5 \text{ MPa}$ - FP:B (Substrate: Concrete)		
Thermal conductivity	$(\lambda_{10,\text{dry}}) 0.49 \text{ W/mK}$ (tab. mean value, P= 50 %)		

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION:**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Angeliki Zacharopoulou
Function: QEHS Manager
At Athens on 25 August 2025



Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 25 August 2025



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance
SikaWall®-1045 Pro
37482513
2025.08 , Version 1



24

Sika Hellas ABEE, Athens - Greece

DoP No. 37482513

EN998-1:2016

General purpose rendering / plastering mortar for external and internal use, GP

Reaction to fire	Class A1
Water absorption	Wc 2
Water vapour permeability	$\mu \leq 15$
Adhesion	$\geq 0.5 \text{ MPa}$ - FP:B (Substrate: Concrete)
Thermal conductivity	$(\lambda_{10,\text{dry}}) 0.49 \text{ W/mK}$ (tab. mean value, P= 50 %)

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaWall®-1045 Pro

37482513

2025.08 , Version 1



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
SikaWall®-1045 Pro
37482513
2025.08 , Version 1