according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Date of last issue: 27.01.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaTack® Panel

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Date of last issue: 27.01.2022

according to Regulation (EC) No. 1907/2006

## SikaTack® Panel

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face

protection.

P284 In case of inadequate ventilation wear respir-

atory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

#### Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxvsilane

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

#### **Additional Labelling**

EUH204 Contains isocyanates. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or pro-

fessional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024 Version 4.0 Print Date 04.01.2024

Date of last issue: 27.01.2022

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chamical name	CACNO	Classification	Concentration
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Urea,N,N"-(methylenedi-4,1-	77703-56-1	Aquatic Chronic 4;	>= 2,5 - < 5
phenylene)bis[N'-butyl-	416-600-4	H413	
, , ,	01-0000016345-72-		
	XXXX		
reaction mass of ethylbenzene	Not Assigned	Flam. Liq. 3; H226	>= 2,5 - < 5
and xylene	905-588-0	Acute Tox. 4; H332	
•	01-2119488216-32-	Acute Tox. 4; H312	
	xxxx	Skin Irrit. 2; H315	
		Eye Irrit. 2; H319	
		STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	
		-	
		Asp. Tox. 1; H304	
		Aquatic Chronic 3;	
		H412	
calcium oxide	1305-78-8	Skin Irrit. 2; H315	>= 1 - < 2,5
	215-138-9	Eye Dam. 1; H318	
	01-2119475325-36-	STOT SE 3; H335	
	XXXX	Í	


according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024

Date of last issue: 27.01.2022

Version 4.0



4,4'-methylenediphenyl diisocya-101-68-8 Acute Tox. 4; H332 >= 0,5 - < 1 nate 202-966-0 Skin Irrit. 2; H315 01-2119457014-47-Eye Irrit. 2; H319 XXXX Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l Reaction product of Hexameth-192526-20-8 Skin Sens. 1A; H317 >= 0,5 - < 1 ylene diisocyanate, oligomers with 924-669-1 Aquatic Chronic 4; Mercaptopropyltrimethoxysilane 01-2120768758-32-H413 XXXX

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Version 4.0 Print Date 0

Revision Date: 04.01.2024 Date of last issue: 27.01.2022

	Sika ®
	Print Date 04.01.2024
)	>= 0,1 - < 0,25

3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411	>= 0,1 - < 0,25
		specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	
		Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 0,031 mg/l	

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Version 4.0 Print Date 04.01.2024

Revision Date: 04.01.2024 Date of last issue: 27.01.2022

dibutyltin dichloride	683-18-1 211-670-0 01-2119496066-31- XXXX	Acute Tox. 3; H301 Acute Tox. 1; H330 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10  specific concentration limit Skin Corr. 1B; H314 >= 5 % Skin Irrit. 2; H315 0,01 - < 5 % Eye Dam. 1; H318 3 - < 5 % Eye Irrit. 2; H319 0,01 - < 3 %  Acute toxicity estimate  Acute oral toxicity: 219 mg/kg	>= 0,01 - < 0,025
Substances with a workplace expo		<u> </u>	25.5
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5		>= 2,5 - < 5
	01-2119489379-17- XXXX		

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Date of last issue: 27.01.2022

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Allergic reactions
Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024 Version 4.0 Print Date 04.01.2024

5.3 Advice for firefighters

Date of last issue: 27.01.2022

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice. When using do not eat or drink. When using do not

Date of last issue: 27.01.2022

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024 Version 4.0 Print Date 04.01.2024

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

smoke. Wash hands before breaks and at the end of workday.

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame- ters *	Basis *
recetion made of other the property and you	Not Appiguant	of exposure) TWA		2000/20/50
reaction mass of ethylbenzene and xy- lene	Not Assigned		50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant		ficant uptake	
	through the skin, Indicative			
		STEL	100 ppm	2000/39/EC
			442 mg/m3	
		TWA	100 ppm	GR OEL
		<u> </u>	435 mg/m3	<u> </u>
		ation: The notation		
	chemical facto	rs of the table of pa	ragraph of 1 articl	e 3, implies
		ibution to of these o		
		workers which are	absorbed through	the skin at the
	direct contact	with these.		
		STEL	150 ppm	GR OEL
			650 mg/m3	
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable)	10 mg/m3	GR OEL
		TWA (respirable)	5 mg/m3	GR OEL
calcium oxide	1305-78-8	TWA (Respirable	1 mg/m3	2017/164/EU
		fraction)		
	Further information: Indicative			
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU
		TWA (Respirable	1 mg/m3	GR OEL
		fraction)	-	
		STEL (Respirable fraction)	4 mg/m3	GR OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 ppm 0,2 mg/m3	GR OEL
		STEL	0,02 ppm	GR OEL
			0,2 mg/m3	
3-isocyanatomethyl-3,5,5-	4098-71-9	TWA	0,01 ppm	GR OEL
trimethylcyclohexyl isocyanate	<u> </u>	<u> </u>	0,09 mg/m3	<u> </u>
	Further information: The notation 'skin' (D), pointing out certain			

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel



Revision Date: 04.01.2024 Date of last issue: 27.01.2022

chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity of exposure to workers which are absorbed through the skin at the direct contact with these.			
STEL	-	0,02 ppm 0,18 mg/m3	GR OEL

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

### 8.2 Exposure controls

## **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

# Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024 Version 4.0 Print Date 04.01.2024

Date of last issue: 27.01.2022

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

In case of inadequate ventilation wear respiratory protection. Respiratory protection

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour beige

Odour characteristic

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

Flash point : ca. 80 °C

Method: closed cup

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Date of last issue: 27.01.2022

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : No data available

**Viscosity** 

Viscosity, kinematic :  $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$ 

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,15 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel



Date of last issue: 27.01.2022

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

## **Components:**

### **Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Method: OECD Test Guideline 402

## reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

## 4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

# Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethox-

ysilane:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

#### 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l

Test atmosphere: dust/mist Method: Calculation method

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

dibutyltin dichloride:

Acute oral toxicity : LD50 Oral (Rat): 219 mg/kg

Acute toxicity estimate: 219 mg/kg Method: Calculation method

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

## Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024 Version 4.0 Print Date 04.01.2024

Date of last issue: 27.01.2022

### **SECTION 12: Ecological information**

### 12.1 Toxicity

#### Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox-

icity)

NOEC: > 1.3 mg/lExposure time: 56 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC: 1,17 mg/l Exposure time: 7 d

ic toxicity)

Species: Daphnia (water flea)

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

dibutyltin dichloride:

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1,4 mg/l

Exposure time: 48 h

M-Factor (Acute aquatic tox- :

icity)

10

M-Factor (Chronic aquatic

toxicity)

10

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Date of last issue: 27.01.2022

## 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic

solvents or other dangerous substances

Date of last issue: 27.01.2022

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

4,4'-methylenediphenyl diisocyanate (Number on list 74, 56)
3-isocyanatomethyl-3,5,5trimethylcyclohexyl isocyanate (Number on list 74)
1,2-Benzenedicarboxylic acid, di-C911-branched alkyl esters, C10-rich (Number on list 52)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

dibutyltin dichloride

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 3,11% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,11% w/w

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Date of last issue: 27.01.2022

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H301 : Toxic if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H330 : Fatal if inhaled. H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H341 : Suspected of causing genetic defects.

H351 : Suspected of causing cancer.

H360FD : May damage fertility. May damage the unborn child.

H370 : Causes damage to organs.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Muta. : Germ cell mutagenicity

Repr. : Germ cell mutagenicity
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Version 4.0 Print Date 04.01.2024

Date of last issue: 27.01.2022

Revision Date: 04.01.2024

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

GR OEL

2000/39/EC / TWA

2000/39/EC / STEL

2017/164/EU / STEL

2017/164/EU / TWA

GR OEL / TWA

: Greece. Exposure limit values

Limit Value - eight hours

Short term exposure limit

Limit Value - eight hours

Limit Value - eight hours

Long term exposure limit

Short term exposure limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

# Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Irrit. 2 H319 Calculation method
Resp. Sens. 1 H334 Calculation method
Skin Sens. 1 H317 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

according to Regulation (EC) No. 1907/2006

# SikaTack® Panel

Revision Date: 04.01.2024 Version 4.0

Date of last issue: 27.01.2022



Changes as compared to previous version!

GR / EN